



## 0.5 AMP NEGATIVE VOLTAGE REGULATOR




Pin 1 – Ground  
 Pin 2 –  $V_{OUT}$   
 Case –  $V_{IN}$

H Package – TO-39



Pin 1 – Ground  
 Pin 2 –  $V_{IN}$   
 Case –  $V_{OUT}$

SMD Package - SMD1  
 CERAMIC SURFACE MOUNT



8 Pin J Package

### FEATURES

- OUTPUT CURRENT UP TO 0.5A
- OUTPUT VOLTAGES OF -5, -12, -15V
- 0.01% / V LINE REGULATION
- 0.3% / A LOAD REGULATION
- THERMAL OVERLOAD PROTECTION
- SHORT CIRCUIT PROTECTION
- OUTPUT TRANSISTOR SOA PROTECTION
- 1% VOLTAGE TOLERANCE (-A VERSIONS)

### Order Information

Part Number	H-Pack (TO-39)	J-Pack CERDIP	SMD-Pack SMD1	Temp. Range
IP79MxxAzz	✓	✓	✓	-55 to +150°C
IP79Mxxzz	✓	✓	✓	"
IP120MAzz-xx	✓		✓	"
IP120Mzz-xx	✓		✓	"

#### Note:

xx = Voltage Code (05, 12, 15)  
 zz = Package Code (H, J)  
 eg. IP79M05J IP120MAH-12

### DESCRIPTION

The IP120MA and IP79M00A series of voltage regulators are fixed output regulators intended for local, on-card voltage regulation. These devices are available in -5, -12, and -15 volt options and are capable of delivering in excess of 500mA over temperature.

The A suffix devices are fully specified at 0.5A, provide 0.01% / V line regulation, 0.3% / A load regulation, and  $\pm 1\%$  output voltage tolerance at room temperature. Protection features include safe operating area, current limiting and thermal shutdown.

### ABSOLUTE MAXIMUM RATINGS ( $T_C = 25^\circ\text{C}$ unless otherwise stated)

$V_I$	DC Input Voltage (for $V_O = -5, -12, -15\text{V}$ )	-35V
$P_D$	Power Dissipation	Internally limited
$R_{\theta JC}$	Thermal Resistance Junction to Case	- H Package 20°C / W - SMD Package TBA°C / W
$R_{\theta JA}$	Thermal Resistance Junction to Ambient	- H Package 120°C / W - J Package 119°C / W
$T_J$	Operating Junction Temperature Range	-55 to 150°C
$T_{stg}$	Storage Temperature	-65 to 150°C

Note 1. Although power dissipation is internally limited, these specifications are applicable for maximum power dissipation  $P_{MAX}$  of 2W for the H-Package, 1.05W for the J-Package and 15W for the SG-Package.

## ELECTRICAL CHARACTERISTICS

Parameter	Test Conditions	IP79M05A IP120MA-05			IP79M05 IP120M-05			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	
$V_O$ Output Voltage	$I_O = 100\text{mA}$ $V_{IN} = -10\text{V}$	-4.95	-5	-5.05	-4.8	-5	-5.2	V
	$I_O = 5\text{mA to } 350\text{mA}$ $P_D \leq P_{MAX}$ $V_{IN} = -7\text{V to } -25\text{V}$ $T_J = -55 \text{ to } 150^\circ\text{C}$	-4.85		-5.15	-4.75		-5.25	
$\Delta V_O$ Line Regulation	$I_O = 350\text{mA}$ $V_{IN} = -7\text{V to } -25\text{V}$ $V_{IN} = -8\text{V to } -18\text{V}$ $T_J = -55 \text{ to } 150^\circ\text{C}$		3	10			50	mV
			3	10			30	
$\Delta V_O$ Load Regulation	$I_O = 5\text{mA to } 500\text{mA}$ $V_{IN} = -10\text{V}$ $T_J = -55 \text{ to } 150^\circ\text{C}$		5	50			100	mV
$I_Q$ Quiescent Current	$V_{IN} = -10\text{V}$ $I_O = 350\text{mA}$ $T_J = -55 \text{ to } 150^\circ\text{C}$		1	2		1	2	mA
$\Delta I_Q$ Quiescent Current Change	$I_O = 5\text{mA to } 500\text{mA}$ $V_{IN} = -10\text{V}$ $T_J = -55 \text{ to } 150^\circ\text{C}$		0.1	0.4			0.4	mA
	$I_O = 200\text{mA}$ $V_{IN} = -8\text{V to } -25\text{V}$ $T_J = -55 \text{ to } 150^\circ\text{C}$		0.1	0.4			0.4	
$V_N$ Output Noise Voltage	$f = 10\text{Hz to } 100\text{kHz}$		40	400			400	$\mu\text{V}$
$\frac{\Delta V_{IN}}{\Delta V_O}$ Ripple Rejection	$f = 120\text{Hz}$ $I_O = 300\text{mA}$	65	80		54			dB
	$V_{IN} = -8\text{V to } -18\text{V}$ $I_O = 100\text{mA}$ $T_J = -55 \text{ to } 150^\circ\text{C}$	65	80		54			
Dropout Voltage	$I_O = 350\text{mA}$		1.1	2.3			2.3	V
$I_{sc}$ Short Circuit Current	$V_{IN} = -35\text{V}$		300	600		300	600	mA
$I_{pk}$ Peak Output Current	$V_{IN} = -10\text{V}$	0.5	1.0	1.4	0.5	1.0	1.6	A
Average Temperature Coefficient of $V_O$	$I_O = 5\text{mA}$		0.5	2.0		0.5		$\frac{\text{mV}}{^\circ\text{C}}$

- 1) All characteristics are measured with a capacitor across the input of  $0.22\mu\text{F}$  and a capacitor across the output of  $0.1\mu\text{F}$ .  
All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques ( $t_p \leq 10\text{ms}$ ,  $\delta \leq 5\%$ ). Output voltage changes due to changes in internal temperature must be taken into account separately.
- 2) Test Conditions unless otherwise stated:  $T_J = 25^\circ\text{C}$   
 $P_{MAX} = 2\text{W}$  for H Package (TO-39)  
 $P_{MAX} = 1.05\text{W}$  for J Package (CERDIP)  
 $P_{MAX} = 15\text{W}$  for SMD1 Package (SMD1)

## ELECTRICAL CHARACTERISTICS

Parameter	Test Conditions	IP79M12A IP120MA-12			IP79M12 IP120M-12			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	
$V_O$ Output Voltage	$I_O = 100\text{mA}$ $V_{IN} = -19\text{V}$	-11.88	-12	-12.12	-11.5	-12	-12.5	V
	$I_O = 5\text{mA to } 350\text{mA}$ $P_D \leq P_{MAX}$ $V_{IN} = -14.5\text{V to } -30\text{V}$ $T_J = -55 \text{ to } 150^\circ\text{C}$	-11.64		-12.36	-11.4		-12.6	
$\Delta V_O$ Line Regulation	$I_O = 350\text{mA}$ $V_{IN} = -14.5\text{V to } -30\text{V}$ $T_J = -55 \text{ to } 150^\circ\text{C}$		4	18			80	mV
			4	18			50	
$\Delta V_O$ Load Regulation	$I_O = 5\text{mA to } 500\text{mA}$ $V_{IN} = -19\text{V}$ $T_J = -55 \text{ to } 150^\circ\text{C}$		10	60			240	mV
$I_Q$ Quiescent Current	$V_{IN} = -19\text{V}$ $I_O = 350\text{mA}$ $T_J = -55 \text{ to } 150^\circ\text{C}$		1.5	3		1.5	3	mA
$\Delta I_Q$ Quiescent Current Change	$I_O = 5\text{mA to } 500\text{mA}$ $V_{IN} = -19\text{V}$ $T_J = -55 \text{ to } 150^\circ\text{C}$		0.1	0.4			0.4	mA
	$I_O = 200\text{mA}$ $V_{IN} = -14.5\text{V to } -30\text{V}$ $T_J = -55 \text{ to } 150^\circ\text{C}$		0.1	0.4			0.4	
$V_N$ Output Noise Voltage	$f = 10\text{Hz to } 100\text{kHz}$		96	960			960	$\mu\text{V}$
$\frac{\Delta V_{IN}}{\Delta V_O}$ Ripple Rejection	$f = 120\text{Hz}$ $I_O = 300\text{mA}$	58	72		54			dB
	$V_{IN} = -15\text{V to } -25\text{V}$ $I_O = 100\text{mA}$ $T_J = -55 \text{ to } 150^\circ\text{C}$	58	72		54			
Dropout Voltage	$I_O = 350\text{mA}$		1.1	2.3			2.3	V
$I_{sc}$ Short Circuit Current	$V_{IN} = -35\text{V}$		300	600		300	600	mA
$I_{pk}$ Peak Output Current	$V_{IN} = -19\text{V}$	0.5	1.0	1.4	0.5	1.0	1.6	A
Average Temperature Coefficient of $V_O$	$I_O = 5\text{mA}$		1.2	4.8		1.2		$\text{mV}/^\circ\text{C}$

- 1) All characteristics are measured with a capacitor across the input of  $0.22\mu\text{F}$  and a capacitor across the output of  $0.1\mu\text{F}$ .  
 All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques ( $t_p \leq 10\text{ms}$ ,  $\delta \leq 5\%$ ). Output voltage changes due to changes in internal temperature must be taken into account separately.
- 2) Test Conditions unless otherwise stated:  $T_J = 25^\circ\text{C}$   
 $P_{MAX} = 2\text{W}$  for H Package (TO-39)  
 $P_{MAX} = 1.05\text{W}$  for J Package (CERDIP)  
 $P_{MAX} = 15\text{W}$  for SMD Package (SMD1)

## ELECTRICAL CHARACTERISTICS

Parameter	Test Conditions	IP79M15A IP120MA-15			IP79M15 IP120M-15			Units	
		Min.	Typ.	Max.	Min.	Typ.	Max.		
V <sub>O</sub> Output Voltage	I <sub>O</sub> = 100mA V <sub>IN</sub> = -23V	-14.85	-15	-15.15	-14.4	-15	-15.6	V	
	I <sub>O</sub> = 5mA to 350mA P <sub>D</sub> ≤ P <sub>MAX</sub> V <sub>IN</sub> = -17.5V to -30V T <sub>J</sub> = -55 to 150°C	-14.55		-15.45	-14.25		-15.75		
ΔV <sub>O</sub> Line Regulation	I <sub>O</sub> = 350mA V <sub>IN</sub> = -17.5V to -30V T <sub>J</sub> = -55 to 150°C		4	22			80	mV	
			4	22			50		
ΔV <sub>O</sub> Load Regulation	I <sub>O</sub> = 5mA to 500mA V <sub>IN</sub> = -23V T <sub>J</sub> = -55 to 150°C		12	75			240	mV	
I <sub>Q</sub> Quiescent Current	V <sub>IN</sub> = -23V I <sub>O</sub> = 350mA T <sub>J</sub> = -55 to 150°C		1.5	3		1.5	3	mA	
ΔI <sub>Q</sub> Quiescent Current Change	I <sub>O</sub> = 5mA to 500mA V <sub>IN</sub> = -23V T <sub>J</sub> = -55 to 150°C		0.1	0.4			0.4	mA	
	I <sub>O</sub> = 200mA V <sub>IN</sub> = -17.5V to -30V T <sub>J</sub> = -55 to 150°C		0.1	0.4			0.4		
V <sub>N</sub> Output Noise Voltage	f = 10Hz to 100kHz		120	1200			1200	μV	
$\frac{\Delta V_{IN}}{\Delta V_O}$ Ripple Rejection	f = 120Hz V <sub>IN</sub> = -18.5V to -28.5V	I <sub>O</sub> = 300mA	57	70		54		dB	
		I <sub>O</sub> = 100mA T <sub>J</sub> = -55 to 150°C	57	70		54			
Dropout Voltage	I <sub>O</sub> = 350mA		1.1	2.3			2.3	V	
I <sub>sc</sub> Short Circuit Current	V <sub>IN</sub> = -35V		300	600		300	600	mA	
I <sub>pk</sub> Peak Output Current	V <sub>IN</sub> = -23V		0.5	1.0	1.4	0.5	1.0	1.6	A
Average Temperature Coefficient of V <sub>O</sub>	I <sub>O</sub> = 5mA		1.5	6.0		1.5		mV/°C	

1) All characteristics are measured with a capacitor across the input of 0.22μF and a capacitor across the output of 0.1μF.

All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques ( $t_p \leq 10\text{ms}$ ,  $\delta \leq 5\%$ ). Output voltage changes due to changes in internal temperature must be taken into account separately.

2) Test Conditions unless otherwise stated: T<sub>J</sub> = 25°C

P<sub>MAX</sub> = 2W for H Package (TO-39)

P<sub>MAX</sub> = 1.05W for J Package (CERDIP)

P<sub>MAX</sub> = 15W for SMD Package (SMD1)



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.