

U-H-F AMPLIFIERS (Cont'd)

Type NPN	Maximum Ratings				Electrical Characteristics @ 25°C										Case
	Pd Ambient mW	VCB Volts	VCE Volts	VEB Volts	HFE @ IC		f _t MHz Min	C _{ob} pF Max	G _{pe} @ f		P _o @ f		NF @ f		
					Min/Max	mA			dB Min	MHz	mW Min	MHz	dB Max	MHz	
2N3292	200	25	15	3	10	2	250	2.0	16	200	-	-	9	200	TO-72
2N3293	200	20	15	3	10	2	250	2.0	-	-	2	257	9	200	TO-72
2N3294	200	20	15	3	10	2	250	2.0	14	200	-	-	9	200	TO-72
2N918	200	30	15	3	20	3	600	1.7	15	200	30	500	6	60	TO-72
2N3478	200	30	15	2	25/150	2	750	0.7	11.5	200	-	-	5	470	TO-72
2N2857	200	30	15	2.5	30/150	3	1000	1.0	12.5	450	30	500	5	450	TO-72
2N3839	200	30	15	2.5	30/150	3	1000	1.0	12.5	450	30	500	3.9	450	TO-72
2N3600	200	30	15	3	20/150	3	850	1.0	17	200	20	500	3	60	TO-72
2N5851	500	30	15	4.5	40/	10	800	1.5	-	-	-	-	4	200	TO-72
2N5852	500	30	15	4.5	40/	10	1100	1.5	-	-	-	-	4	200	TO-72
2N4252	200	30	18	4	50/	2	600	0.5	-	-	-	-	-	-	TO-72
2N4253	200	30	18	4	30/150	2	600	0.5	-	-	-	-	-	-	TO-72
2N3287	200	40	20	3	15/100	2	350	1.1	17	200	-	-	6	200	TO-72
2N3288	200	35	20	3	30/200	2	700	1.5	15	200	-	-	7.5	200	TO-72
2N3932	200	30	20	2.5	40/150	2	750	0.55	11.5	200	-	-	4.5	200	TO-72
2N4874	720	30	20	2	20/100	50	900	3.5	1.0	400	1000	400	-	-	TO-39
2N3308	200	40	25	3	25/250	2	300	1.6	17	200	-	-	6	200	TO-72
2N4875	720	40	25	2	20/100	50	800	3.5	9.5	400	820	400	-	-	TO-39
2N3307	200	40	30	3	40/250	2	300	1.3	17	200	-	-	4.5	200	TO-72
2N3933	200	40	30	2.5	60/200	2	750	0.55	14	200	-	-	4	200	TO-72
2N5181	200	45	30	3	27/275	1	700	0.4	15	200	-	-	-	-	TO-72
2N5182	200	45	30	3	27/275	1	700	0.4	20	200	-	-	-	-	TO-72
2N4934	200	40	30	3	40/170	2	700	0.25	18	200	-	-	3.5	200	TO-72
2N4957	200	30	30	3	20/120	2	1000	0.8	17	450	-	-	3	450	TO-72
2N4958	200	30	30	3	20/120	2	1000	0.8	16	450	-	-	3.5	450	TO-72
2N4959	200	30	30	3	20/120	2	1000	0.8	15	450	-	-	4	450	TO-72
2N5829	200	30	30	3	20/150	2	1200	0.8	17	450	-	-	2.5	450	TO-72
2N4259	175	40	30	2.5	60/250	2	1000	0.55	11	450	-	-	5	450	TO-72
2N4876	720	40	30	2	20/100	50	650	3.5	8.5	400	710	400	-	-	TO-39
40235	200	45	-	4.5	40/170	1	700	0.65	20	216	-	-	-	-	TO-72
40236	200	45	-	4.5	40/275	1	700	0.65	-	-	-	-	-	-	TO-72
40237	200	45	-	4.5	27/275	1	700	0.9	-	-	-	-	-	-	TO-72
40238	200	45	-	4.5	40/170	1	500	0.65	30	45	-	-	-	-	TO-72
40239	200	45	-	4.5	27/100	1	500	0.65	30	45	-	-	-	-	TO-72
40240	200	45	-	4.5	27/275	1	500	0.65	30	45	-	-	-	-	TO-72
2N4935	200	50	40	3	60/200	2	700	0.5	21	200	-	-	3	200	TO-72
2N4936	200	50	40	3	60/250	2	700	0.5	13	200	-	-	4.5	200	TO-72
40242	200	45	45	4.5	40/170	1	700	0.8	25	100	-	-	2.5	200	TO-72
40243	200	45	45	4.5	40/170	1	700	0.8	25	60	-	-	4	200	TO-72
40244	200	45	45	4.5	27/170	1	700	0.8	-	-	-	-	4	200	TO-72
40245	200	45	45	4.5	70/275	1	700	0.8	35	10.7	-	-	4	200	TO-72
40246	200	45	45	4.5	27/90	1	700	0.8	35	10.7	-	-	4	200	TO-72

NPN GENERAL PURPOSE MEDIUM SPEED AMPLIFIERS

Type NPN	Maximum Ratings				Electrical Characteristics @ 25°C							Case
	Pd Ambient mW	VCB Volts	VCE Volts	VEB Volts	HFE @ IC		VCE(Sat) @ IC/IC		f _t MHz Min	C _{ob} pF Max		
					Min/Max	mA	Volts	mA/mA				
2N5183	500	18	18	6	75/400	10	0.5	300/30	125	20	TO-18	
2N332	150	45	-	1	9/20	1	1	5/2.2	6	30	TO-5	
2N333	150	45	-	1	18/40	1	1	5/2.2	8	30	TO-5	
2N334	150	45	-	1	18/90	1	1	5/2.2	10	30	TO-5	
2N335	150	45	-	1	36/90	1	1	5/2.2	12	30	TO-5	
2N336	150	45	-	1	76/333	1	1	5/2.2	13	30	TO-5	
2N337	125	45	30	1	20/55	10	1.5	10/1	20	3	TO-5	
2N338	125	45	30	1	45/150	10	1.5	10/1	30	3	TO-5	
2N1420	600	60	30*	5	100/300	150	1.5	150/15	50	35	TO-5	
2N696	600	60	40*	5	20/60	150	1.5	150/15	40	35	TO-5	
2N697	600	60	40*	5	40/120	150	1.5	150/15	50	35	TO-5	
2N731	500	60	40*	5	40/120	150	1.5	150/15	50	35	TO-18	
2N718	400	60	40*	5	40/120	150	1.5	150/15	50	35	TO-18	
2N3241A	500	30	25	7.5	100/300	10	0.25	200/20	100	20	TO-18	
2N2195	800	45	25	5	20/	150	0.35	150/15	50	20	TO-5	

This datasheet has been downloaded from:

www.DatasheetCatalog.com

Datasheets for electronic components.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.