


**Chip Type 2C5664**  
**Geometry 9221**  
**Polarity NPN**

**Generic Packaged Parts:**  
**2N5664, 2N5666**



[Request Quotation](#)

Chip type **2C5664** by Semicoa Semiconductors provides performance similar to these devices.

**Part Numbers:**  
 2N5664, 2N5666

**Product Summary:**

**APPLICATIONS:** Designed for high voltage, high speed switching and power amplifier applications.

**Features:**

- High voltage ratings

Mechanical Specifications		
Metallization	Top	Al - 37.5 kÅ min.
	Backside	Au - 6.5 kÅ nom.
Bonding Pad Size	Emitter	12 mils x 40 mils
	Base	12 mils x 30 mils
Die Thickness	8 mils nominal	
Chip Area	100 mils x 100 mils	
Top Surface	Silox Passivated	

Electrical Characteristics				
$T_A = 25^\circ\text{C}$				
Parameter	Test conditions	Min	Max	Unit
$BV_{CER}$	$I_C = 10 \text{ mA}$ , $R = 100 \text{ ohms}$	250	---	V dc
$BV_{EBO}$	$I_E = 10 \text{ }\mu\text{A}$	6.0	---	$\mu\text{A}$
$I_{CES}$	$V_{CE} = 200 \text{ V}$ , $I_E = 0$	---	0.2	$\mu\text{A}$
$h_{FE}$	$I_C = 500 \text{ mA dc}$ , $V_{CE} = 2.0 \text{ V}$	50	---	---
$h_{FE}$	$I_C = 1.0 \text{ A dc}$ , $V_{CE} = 5.0 \text{ V}$	25	75	---

*Due to limitations of probe testing, only dc parameters are tested. This must be done with pulse width less than 300  $\mu\text{s}$ , duty cycle less than 2%.*

This datasheet has been downloaded from:

[www.DatasheetCatalog.com](http://www.DatasheetCatalog.com)

Datasheets for electronic components.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.