

AN7090FHQ

Peripheral analog IC for audio signal processing

■ Overview

The AN7090FHQ is a one chip IC of audio signal processing analog circuit for use in various information systems including microcomputer.


Small-sizing of system and low power dissipation are possible.

■ Features

- Built-in head phone amplifier
- Built-in external/internal microphone switching circuit
- Enables power save mode


■ Applications

- Note-type personal computer, desk-top personal computer, portable information terminal and others



Note) The package of this product will be changed to lead-free type (LQFP048-P-0707A). See the new package dimensions section later of this datasheet.

■ Block Diagram



■ Pin Descriptions

Pin No.	Description	Pin No.	Description
1	Power on control	25	Mic. V_{REF}
2	Line-out jack L-channel	26	External mic. input
3	Line-out input L-channel	27	Mic. GND
4	VR-input L-channel	28	Internal mic. input
5	Mono out	29	Mic. select (int./ext.)
6	$-5V_{DD}$ (power)	30	Mic. gain
7	$+5V_{DD}$ (power)	31	Mic. output
8	Speaker enable	32	Mic. mute
9	VR-input R-channel	33	Mic. NF
10	Line-out input R-channel	34	CD-out L-channel
11	Line-out jack R-channel	35	CD-out GND
12	Power GND	36	CD-out R-channel
13	Speaker-out R-channel	37	GND
14	GND (power)	38	CD-in R-channel 1
15	Headphone-out R-channel	39	CD-in R-channel 2
16	$+5V_{DD}$	40	CD-in GND
17	GND	41	CD-in L-channel 1
18	$-5V_{DD}$	42	CD-in L-channel 2
19	Line-in jack L-channel	43	$+5V_{DD}$
20	Line-in jack R-channel	44	$-5V_{DD}$
21	GND	45	GND
22	Line-in output R-channel	46	Headphone-out L-channel
23	Line-in output L-channel	47	Power GND
24	Mic. amp. V_{DD}	48	Speaker-out L-channel

■ Absolute Maximum Ratings

Parameter	Symbol	Rating	Unit
Supply voltage	V_{CC}	± 6	V
Supply current	I_{CC}	15	mA
Power dissipation *2	P_D	180	mW
Operating ambient temperature *1	T_{opr}	-20 to +70	°C
Storage temperature *1	T_{stg}	-55 to +125	°C

Note) *1 : $T_a = 25^\circ\text{C}$ except operating ambient temperature and storage temperature.

*2 : $T_a = 75^\circ\text{C}$

■ Recommended Operating Range

Parameter	Symbol	Range	Unit
Supply voltage	V_{CC}	± 4.5 to ± 5.0 typ. to ± 5.5	V

■ Electrical Characteristics at $V_{CC} = \pm 5$ V, $f = 1$ kHz, $T_a = 25^\circ\text{C}$

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Line-out jack block						
Line-out gain *1	VLO_{LR}	$V_{IN} = 1$ V[rms], $f = 1$ kHz	-1	0	1	dB
Line-out total harmonic distortion *1	VLO_{TH}	$V_{IN} = 1$ V[rms], $f = 1$ kHz	—	0.01	0.02	%
Line-out output residual noise *2	VLO_{SN}	$V_{IN} = 0$ V[rms], $R_g = 4.7$ k Ω	—	-90	-80	dB
Cross talk 1 *1	CT1	$V_{IN} = 1$ V[rms], $f = 1$ kHz	—	-70	-60	dB
Speaker-out block						
Sp-out gain *1	VSP_{LR}	$V_{IN} = 1$ V[rms], $f = 1$ kHz	-1	0	1	dB
Sp-out total harmonic distortion 2 *1	VSP_{TH}	$V_{IN} = 1$ V[rms], $f = 1$ kHz	—	0.01	0.02	%
Sp-out residual noise *2	VSP_{SN}	$V_{IN} = 0$ V[rms], $R_g = 4.7$ k Ω	—	-85	-80	dB
Sp-out mute attenuation 1 *1	VMU1	$V_{IN} = 1$ V[rms], $f = 1$ kHz	—	-85	-80	dB
Cross talk 2 *1	CT2	$V_{IN} = 1$ V[rms], $f = 1$ kHz	—	-70	-60	dB
Headphone amplifier block						
Rated output *1	HP_{THD4}	$f = 1$ kHz, distortion : 1%, load : 32 Ω	80	100	120	mW
HP-out total harmonic distortion 3 *1	THD3	$V_{IN} = 1$ V[rms], $f = 1$ kHz, load : 32 Ω	—	0.01	0.02	%
HP-out residual noise *2	HS/N	$V_{IN} = 0$ V[rms], $f = 1$ kHz, $R_g = 4.7$ k Ω , load : 32 Ω	—	-85	-80	dB
HP-out mute attenuation 2 *1	VMU2	$V_{IN} = 1$ V[rms], $f = 1$ kHz, load : 32 Ω	—	-85	-80	dB
Cross talk 3 *1	CT3	$V_{IN} = 1$ V[rms], $f = 1$ kHz, load : 32 Ω	—	-70	-60	dB
Line-in jack block						
L-jack gain *1	VLJ	$V_{IN} = 1$ V[rms], $f = 1$ kHz	-1	0	1	dB
L-jack total harmonic distortion 4 *1	THDJ	$V_{IN} = 1$ V[rms], $f = 1$ kHz	—	0.01	0.02	%
L-jack output residual noise *2	LJSN	$V_{IN} = 0$ V[rms], $R_g = 4.7$ k Ω	—	-90	-80	dB
Cross talk 4 *1	CT4	$V_{IN} = 1$ V[rms], $f = 1$ kHz	—	-70	-60	dB
CD-ROM block						
CD in gain *1	VCDIN	$V_{IN} = 1$ V[rms], $f = 1$ kHz	-1	0	1	dB
CD in total harmonic distortion 5 *1	CDTHD5	$V_{IN} = 1$ V[rms], $f = 1$ kHz	—	0.01	0.02	%
CD in output residual noise *2	CDSN	$V_{IN} = 0$ V[rms], $R_g = 4.7$ k Ω	—	-85	-80	dB
Cross talk 5 *1	CT5IN	$V_{IN} = 1$ V[rms], $f = 1$ kHz	—	-70	-60	dB

Note) *1 : Using the DIN audio filter.

*2 : Using the A curve filter.

■ Electrical Characteristics at $V_{CC} = \pm 5\text{ V}$, $f = 1\text{ kHz}$, $T_a = 25^\circ\text{C}$ (continued)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Internal-mic. block						
Mic.-out voltage 1 *1	V_{INT0}	$V_{IN} = 3\text{ mV[rms]}$, $f = 1\text{ kHz}$	0.3	0.7	1	V[rms]
Mic.-out voltage 2 *1	V_{INT1}	$V_{IN} = 3\text{ mV[rms]}$, $f = 1\text{ kHz}$	0.03	0.07	0.1	V[rms]
Mic.-out output residual noise *2	MICSN1	$V_{IN} = 0\text{ V[rms]}$, $R_g = 2.2\text{ k}\Omega$	—	-80	-75	dB
Mic.-out total harmonic distortion 6 *1	THDM6	$V_{IN} = 25\text{ mV[rms]}$, $f = 1\text{ kHz}$	—	0.02	0.1	%
Mic.-out mute attenuation 3 *1	VMIMU1	$V_{IN} = 3\text{ mV[rms]}$, $f = 1\text{ kHz}$	—	-75	-70	dB
External-mic. block						
Mic.-out voltage 1 *1	V_{EXT0}	$V_{IN} = 5\text{ mV[rms]}$, $f = 1\text{ kHz}$	0.3	0.7	1	V[rms]
Mic.-out voltage 2 *1	V_{EXT1}	$V_{IN} = 5\text{ mV[rms]}$, $f = 1\text{ kHz}$	0.03	0.07	0.1	V[rms]
Mic.-out output residual noise *2	MICSN2	$V_{IN} = 0\text{ V[rms]}$, $R_g = 2.2\text{ k}\Omega$	—	-80	-75	dB
Mic.-out total harmonic distortion 7 *1	THDM7	$V_{IN} = 25\text{ mV[rms]}$, $f = 1\text{ kHz}$	—	0.02	0.1	%
Mic.-out mute attenuation 4 *1	VMIMU2	$V_{IN} = 5\text{ mV[rms]}$, $f = 1\text{ kHz}$	—	-75	-70	dB
Mic. use V_{REF} voltage						
Mic. use V_{REF} DC voltage *1	$MICV_{REFDC}$	Flow out current at pin 25 : 3.3 mA	2.3	2.5	2.7	V
Mic. use V_{REF} voltage ripple noise *1	$MICV_{REFRI}$	Flow out current at pin 25 : 3.3 mA	—	—	0.01	V[p-p]
Circuit current						
Circuit current at no load 1	I_{TOTA1}	No input signal (+ V_{CC} side)	5	7	10	mA
Circuit current at no load 2	I_{TOTA2}	No input signal (- V_{CC} side)	5	7	10	mA
Circuit current at power save 1	I_{PWON1}	No input signal (+ V_{CC} side)	0.3	1	5	mA
Circuit current at power save 2	I_{PWON2}	No input signal (- V_{CC} side)	0.3	1	5	mA
Low-level mic. balance	MICBL	$V_{EXT1} - V_{INT1}$	—	0	30	mV[rms]
High-level mic. balance	MICBH	$V_{EXT0} - V_{INT0}$	—	0	200	mV[rms]

Note) *1 : Using the DIN audio filter.

*2 : Using the A curve filter.

■ Terminal Equivalent Circuits

Pin No.	Equivalent circuit	Description	Pin voltage (V)
1		<p>PON : Switching control pin of power save mode</p>	—
2		<p>OUTL : Output pin of L-channel line-out jack</p>	0
3		<p>LOIL : Input pin of L-channel line-out jack</p>	0

■ Terminal Equivalent Circuits (continued)

Pin No.	Equivalent circuit	Description	Pin voltage (V)
4		<p>VINL : Input pin of L-channel VR</p>	0
5		<p>MOUT : Mono output pin of L-channel and R-channel VR</p>	0
6	—	<p>NV_{DD} : -V_{DD} for power stage</p>	-5
7	—	<p>PV_{DD} : +V_{DD} for power stage</p>	+5
8		<p>SENB : Speaker enable</p>	—

■ Terminal Equivalent Circuits (continued)

Pin No.	Equivalent circuit	Description	Pin voltage (V)
9		<p>VINR : Input pin of R-channel VR</p>	0
10		<p>LOIR : Input pin of R-channel line-out jack</p>	0
11		<p>OUTR : Output pin of R-channel line-out jack</p>	0
12	<p style="text-align: center;">—</p>	<p>PGND : Ground pin</p>	0

■ Terminal Equivalent Circuits (continued)

Pin No.	Equivalent circuit	Description	Pin voltage (V)
13		SPOR : Output pin of R-channel speaker	0
14	—	GND : Ground pin	0
15		HPOR : Output pin of R-channel head-phone	0
16	—	PV _{DD} : V _{DD}	+5
17	—	GND : Ground pin	0
18	—	NV _{DD} : -V _{DD}	-5
19		LIJL : Input pin of L-channel line-in jack	0

■ Terminal Equivalent Circuits (continued)

Pin No.	Equivalent circuit	Description	Pin voltage (V)
20		LIJR : Input pin of R-channel line-in jack	0
21	—	GND : Ground pin	0
22		LINR : Output pin of R-channel line-in jack	0
23		LINL : Output pin of L-channel line-in jack	0
24	—	MV _{DD} : Power supply for mic. amp.	+5
25		MV _{RE} : Power supply for mic.	2.5

■ Terminal Equivalent Circuits (continued)

Pin No.	Equivalent circuit	Description	Pin voltage (V)
26		<p>EMIC : Input pin of external mic. amp.</p>	0
27	<p style="text-align: center;">—</p>	<p>MGND : Ground pin for mic.</p>	0
28		<p>IMIC : Input pin of internal mic. amp.</p>	0
29		<p>MSEL : Mic. selector (int./ext.)</p>	—
30		<p>MGAI : Mic. gain control</p>	—

■ Terminal Equivalent Circuits (continued)

Pin No.	Equivalent circuit	Description	Pin voltage (V)
31		<p>MICO : Output pin of mic. amp.</p>	0
32		<p>MDET : Mic. mute control</p>	—
33		<p>Mic. NF : Negative feedback pin of mic. amp.</p>	0
34		<p>CDOL : Output pin of L-channel CD-ROM</p>	0

■ Terminal Equivalent Circuits (continued)

Pin No.	Equivalent circuit	Description	Pin voltage (V)
35		COGN : Ground pin	0
36		CDOR : Output pin of R-channel CD-ROM	0
37	—	GND : Ground pin	0
38		CDR1 : Input pin of R-channel CD-ROM1	0
39		CDR2 : Input pin of R-channel CD-ROM2	0
40	Refer to pin 35.	CIGN : Ground pin	0

■ Terminal Equivalent Circuits (continued)


Pin No.	Equivalent circuit	Description	Pin voltage (V)
41		CDL1 : Input pin of L-channel CD-ROM1	0
42		CDL2 : Input pin of L-channel CD-ROM2	0
43	—	PV _{DD} : +power supply	+5
44	—	NV _{DD} : -power supply	-5
45	—	GND : Ground pin	0
46		HPOL : Output pin of L-channel head-phone	0
47	—	PGND : Ground pin	0
48		SPOL : Output pin of L-channel speaker	0

■ Technical Information

• Description of each control pin


Parameter	Pin No.	Low	High
POWERON	1	Power save mode on	Power save mode off
SPKENB	8	Headphone output mute	Speaker output mute
MICGAIN	30	Mic. amp. gain low	Mic. amp. gain high
MICSEL	29	External mic. selection	Internal mic. selection
MICDET	32	Mic. amp. output mute on	Mic. amp. output mute off

■ Application Circuit Example



■ New Package Dimensions (Unit: mm)

- LQFP048-P-0707A (Lead-free package)



Request for your special attention and precautions in using the technical information and semiconductors described in this material

- (1) An export permit needs to be obtained from the competent authorities of the Japanese Government if any of the products or technologies described in this material and controlled under the "Foreign Exchange and Foreign Trade Law" is to be exported or taken out of Japan.
- (2) The technical information described in this material is limited to showing representative characteristics and applied circuit examples of the products. It does not constitute the warranting of industrial property, the granting of relative rights, or the granting of any license.
- (3) The products described in this material are intended to be used for standard applications or general electronic equipment (such as office equipment, communications equipment, measuring instruments and household appliances).
Consult our sales staff in advance for information on the following applications:
 - Special applications (such as for airplanes, aerospace, automobiles, traffic control equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
 - Any applications other than the standard applications intended.
- (4) The products and product specifications described in this material are subject to change without notice for reasons of modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (5) When designing your equipment, comply with the guaranteed values, in particular those of maximum rating, the range of operating power supply voltage and heat radiation characteristics. Otherwise, we will not be liable for any defect which may arise later in your equipment.
Even when the products are used within the guaranteed values, redundant design is recommended, so that such equipment may not violate relevant laws or regulations because of the function of our products.
- (6) When using products for which dry packing is required, observe the conditions (including shelf life and after-unpacking standby time) agreed upon when specification sheets are individually exchanged.
- (7) No part of this material may be reprinted or reproduced by any means without written permission from our company.

Please read the following notes before using the datasheets

- A. These materials are intended as a reference to assist customers with the selection of Panasonic semiconductor products best suited to their applications.
Due to modification or other reasons, any information contained in this material, such as available product types, technical data, and so on, is subject to change without notice.
Customers are advised to contact our semiconductor sales office and obtain the latest information before starting precise technical research and/or purchasing activities.
- B. Panasonic is endeavoring to continually improve the quality and reliability of these materials but there is always the possibility that further rectifications will be required in the future. Therefore, Panasonic will not assume any liability for any damages arising from any errors etc. that may appear in this material.
- C. These materials are solely intended for a customer's individual use.
Therefore, without the prior written approval of Panasonic, any other use such as reproducing, selling, or distributing this material to a third party, via the Internet or in any other way, is prohibited.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.