SPECIFICATION

Device Name : IGBT Module

Type Name : 7MBR75SB060-01

Spec. No. : MS6M 0552

Date : Jun. - 02 - 2000

This material and the information herein is the property of Fuji Electric Co.,Ltd They shall be neither reproduced, copied lent, or disclosed in any way whatsoever for the use of any third party,nor used for the manufacturing purposes without the express written consent of Fuji Electric Co.,Ltd.

Fuji Electric Co., Ltd.
Matsumoto Factory

	DATE	NAME	APPROVED
DRAWN	Jun. - 2 - '00	Y. Kobayashi	
CHECKED	June - 2 - 00	S. Mitta	T. Miyasaka

Fuji Electric Co.,Ltd.

DWG.NO. MS6M 0552 1/10

H04-004-05

Revised Records

Date	Classi-fication	Ind.	Content	Applied date	Drawn	Checked	Approved
Jun.-2-'00	enactment	—	—	Issued date	—	S.Mita	T.Miyasaka

This material and the information herein is the property of Fuji Electric Co.,Ltd They shall be neither reproduced, copied lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd

7MBR75SB060-01

1. Outline Drawing (Unit : mm)



2. Equivalent circuit



This material and the information herein is the property of Fuji Electric Co.Ltd They shall be neither reproduced copied lent or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

3. Absolute Maximum Ratings (at Tc= 25℃ unless otherwise specified)

Items		Symbols	Conditions	Maximum Ratings	Units
Inverter	Collector-Emitter voltage	VCES		600	V
	Gate-Emitter voltage	VGES		±20	V
	Collector current	Ic	Continuous	75	A
		Icp	1ms	150	A
		-Ic		75	A
	Collector Power Dissipation	Pc	1 device	300	W
Brake	Collector-Emitter voltage	VCES		600	V
	Gate-Emitter voltage	VGES		±20	V
	Collector current	Ic	Continuous	50	A
		Icp	1ms	100	A
	Collector Power Dissipation	Pc	1 device	200	W
	Repetitive peak reverse Voltage(Diode)	VRRM		600	V
Converter	Repetitive peak reverse Voltage	VRRM		800	V
	Average Output Current	Io	50Hz/60Hz sine wave	75	A
	Surge Current (Non-Repetitive)	IFSM	Tj=150℃, 10ms half sine wave	525	A
	I^2t (Non-Repetitive)	I^2t		1378	A^2s
Junction temperature		Tj		150	℃
Storage temperature		Tstg		-40～ +125	℃
Isolation voltage	between terminal and copper base (*1)	Viso	AC : 1min.	2500	V
	between thermistor and others (*2)			2500	V
Mounting Screw Torque (*3)				3.5	N・m

(*1) All terminals should be connected together when isolation test will be done.

(*2) Terminal 8 and 9 should be connected together. Terminal 1 to 7 and 10 to 24 should be connected together and shorted to copper base.

(*3) Recommendable Value : 2.5～3.5 N・m (M5)

This material and the information herein is the property of Fuji Electric Co.,Ltd. They shall be neither reproduced, copied lent, or disclosed in any way whatsoever for the use of any third party or used for the manufacturing purposes without the express written consent of Fuji Electric Co.,Ltd.

4. Electrical characteristics (at Tj= 25C unless otherwise specified)

	Items	Symbols	Conditions		Characteristics min.	typ.	Max.	Units
Inverter	Zero gate voltage Collector current	ICES	VGE 0 V, VCE 600 V				1.0	mA
	Gate-Emitter leakage current	IGES	VCE 0 V, VGE +-20 V				200	nA
	Gate-Emitter threshold voltage	VGE(th)	VCE 20 V, Ic = 75 m		5.5	7.8	8.5	V
	Collector-Emitter saturation voltage	VCE(sat)	VGE 15 V, Ic = 75 A	chip		1.8		V
				terminal		2.1	2.55	
	Input capacitance	Cies	VGE 0 V, VCE 10 V f = 1 MHz			7500		pF
	Turn-on time	ton	Vcc= 300 V Ic = 75 A VGE +-15 V RG = 33 ohm			0.45	1.2	us
		tr				0.25	0.6	
		$tr_{(i)}$				0.08		
	Turn-off time	toff				0.40	1.0	
		tf				0.05	0.35	
	Forward on voltage	VF	IF = 75 A	chip		1.7		V
				terminal		2.0	2.7	
	Reverse recovery time	trr	IF = 75 A				300	ns
Brake	Zero gate voltage Collector current	ICES	VGE 0 V, VCE 600 V				1.0	mA
	Gate-Emitter leakage current	IGES	VCE 0 V, VGE +-20 V				200	nA
	Collector-Emitter saturation voltage	VCE(sat)	VGE 15 V, Ic = 50 A	chip		1.8		V
				terminal		2.05	2.5	
	Turn-on time	ton	Vcc= 300 V Ic = 50 A VGE +-15 V RG = 51 ohm			0.45	1.2	us
		tr				0.25	0.6	
	Turn-off time	toff				0.40	1.0	
		tf				0.05	0.35	
	Reverse current	IRRM	VR = 600 V				1.0	mA
Converter	Forward on voltage	VFM	IF = 75 A	chip		1.1		V
				terminal		1.2	1.5	
	Reverse current	IRRM	VR = 800 V				1.0	mA
Thermistor	Resistance	R	T = 25C			5000		ohm
			T =100C		465	495	520	
	B value	B	T = 25/50C		3305	3375	3450	K

5. Thermal resistance characteristics

Items	Symbols	Conditions	Characteristics min.	typ.	Max.	Units
Thermal resistance (1 device)	Rth(j-c)	Inverter IGBT			0.42	C/W
		Inverter FWD			0.90	
		Brake IGBT			0.63	
		Converter Diode			0.70	
Contact Thermal resistance	Rth(c-f)	with Thermal Compound (*)		0.05		C/W

* This is the value which is defined mounting on the additional cooling fin with thermal compound.

This material and the information herein is the property of Fuji Electric Co. Ltd They shall be neither reproduced, copied lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co. Ltd

6. Indication on module



7. Applicable category

This specification is applied to Power Integrated Module named 7MBR75SB060-01.

8. Storage and transportation notes

- The module should be stored at a standard temperature of 5 to 35°C and humidity of 45 to 75% .
- Store modules in a place with few temperature changes in order to avoid condensation on the module surface.
- Avoid exposure to corrosive gases and dust.
- Avoid excessive external force on the module.
- Store modules with unprocessed terminals.
- Do not drop or otherwise shock the modules when transporting.
- Please connect adequate fuse or protector of circuit between three-phase line and this product to prevent the equipment from causing secondary destruction.

This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

9. Definitions of switching time



[Inverter]
Collector current vs. Collector-Emitter voltage
Tj= 25℃ (typ.)



[Inverter]
Collector current vs. Collector-Emitter voltage
Tj= 125℃ (typ.)



[Inverter]
Collector current vs. Collector-Emitter voltage
VGE=15V (typ.)



[Inverter]
Collector-Emitter voltage vs. Gate-Emitter voltage
Tj= 25℃ (typ.)



[Inverter]
Capacitance vs. Collector-Emitter voltage (typ.)
VGE=0V, f= 1MHz, Tj= 25℃



[Inverter]
Dynamic Gate charge (typ.)
Vcc=300V, Ic=75A, Tj= 25℃



This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

[Inverter]
Switching time vs. Collector current (typ.)
Vcc=300V, VGE=± 15V, Rg=33Ω , Tj= 25℃



[Inverter]
Switching time vs. Collector current (typ.)
Vcc=300V, VGE=± 15V, Rg= 33Ω , Tj= 125℃



[Inverter]
Switching time vs. Gate resistance (typ.)
Vcc=300V, Ic=75A, VGE=± 15V, Tj= 25℃



[Inverter]
Switching loss vs. Collector current (typ.)
Vcc=300V, VGE=± 15V, Rg=33Ω



[Inverter]
Switching loss vs. Gate resistance (typ.)
Vcc=300V, Ic=75A, VGE=± 15V, Tj= 125℃



[Inverter]
Reverse bias safe operating area
+VGE=15V, -VGE≦ 15V, Rg≧ 33Ω , Tj≦ 125℃



This material and the information herein is the property of Fuji Electric Co.,Ltd They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd

[Inverter]
Forward current vs. Forward on voltage (typ.)



[Inverter]
Reverse recovery characteristics (typ.)
Vce=300V, VGE=± 15V, Rg=33 Ω



[Converter]
Forward current vs. Forward on voltage (typ.)



Transient thermal resistance



[Thermistor]
Temperature characteristic (typ.)



This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

[Brake]
Collector current vs. Collector-Emitter voltage
Tj= 25℃ (typ.)



[Brake]
Collector current vs. Collector-Emitter voltage
Tj= 125℃ (typ.)



[Brake]
Collector current vs. Collector-Emitter voltage
VGE=15V (typ.)



[Brake]
Collector-Emitter voltage vs. Gate-Emitter voltage
Tj= 25℃ (typ.)



[Brake]
Capacitance vs. Collector-Emitter voltage (typ.)
VGE=0V, f= 1MHz, Tj= 25℃



[Brake]
Dynamic Gate charge (typ.)
Vcc=300V, Ic=50A, Tj= 25℃



This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party, nor used for the manufacturing purposes without the express written consent of Fuji Electric Co. Ltd.

Littlediode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.