

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:

The **ASI AVF300** is Designed for Class C, IFF Applications up to 1090 MHz.

FEATURES:

- Internal Input/Output Matching Networks
- $P_G = 7.7$ dB at 300 W/1090 MHz
- **Omnigold™** Metalization System

MAXIMUM RATINGS

I_C	18.8 A
V_{CC}	55 V
P_{DISS}	625 W @ $T_C = 25^\circ C$
T_J	-65 °C to +250 °C
T_{STG}	-65 °C to +200 °C
θ_{JC}	0.3 °C/W

PACKAGE STYLE .400 2NL FLG

DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.020 / 0.51	.030 / 0.76
B	.100 / 2.54	
C	.376 / 9.55	.396 / 10.06
D	.110 / 2.79	.130 / 3.30
E	.395 / 10.03	.407 / 10.34
F	.193 / 4.90	
G	.450 / 11.43	
H	.125 / 3.18	
I	.640 / 16.26	.660 / 16.76
J	.890 / 22.61	.910 / 23.11
K	.395 / 10.03	.415 / 10.54
L	.004 / 0.10	.007 / 0.18
M	.052 / 1.32	.072 / 1.83
N	.118 / 3.00	.131 / 3.33
P		.230 / 5.84

ORDER CODE: ASI10572

CHARACTERISTICS $T_C = 25^\circ C$

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CBO}	$I_C = 10$ Ma	65			V
BV_{CER}	$I_C = 25$ mA $R_{BE} = 10 \Omega$	65			V
BV_{EBO}	$I_E = 1.0$ mA	3.5			V
I_{CES}	$V_{CE} = 50$ V			25	mA
h_{FE}	$V_{CE} = 5.0$ V $I_C = 1.0$ A	15		120	---
G_P	$V_{CC} = 50$ V $P_{OUT} = 300$ W $f = 1030 - 1090$ MHz	7.7			dB
η_C		40			%



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.