


MECHANICAL DATA

Dimensions in mm (inches)



I-PAK (TO-251)

Pin 1 – Base Pin 2 – Collector Pin 3 – Emitter

**ADVANCED
DISTRIBUTED BASE DESIGN
HIGH VOLTAGE
HIGH SPEED NPN
SILICON POWER TRANSISTOR**

Designed for use in
electronic ballast applications

- SEMEFAB DESIGNED AND DIFFUSED DIE
- HIGH VOLTAGE
- FAST SWITCHING
- HIGH ENERGY RATING

FEATURES

- Multi-base for efficient energy distribution across the chip resulting in significantly improved switching and energy ratings across full temperature range.
- Ion implant and high accuracy masking for tight control of characteristics from batch to batch.
- Triple Guard Rings for improved control of high voltages.

ABSOLUTE MAXIMUM RATINGS ($T_{case} = 25^{\circ}C$ unless otherwise stated)

V_{CBO}	Collector – Base Voltage	800V
V_{CEO}	Collector – Emitter Voltage ($I_B = 0$)	400V
V_{EBO}	Emitter – Base Voltage ($I_C = 0$)	10V
I_C	Continuous Collector Current	5A
$I_{C(PK)}$	Peak Collector Current	8A
I_B	Base Current	2A
P_{tot}	Total Dissipation at $T_{case} = 25^{\circ}C$	20W
T_{stg}	Operating and Storage Temperature Range	-55 to +150°C

ELECTRICAL CHARACTERISTICS ($T_{case} = 25^{\circ}C$ unless otherwise stated)

Parameter	Test Conditions	Min.	Typ.	Max.	Unit		
ELECTRICAL CHARACTERISTICS							
$V_{CEO(sus)}$	Collector – Emitter Sustaining Voltage	$I_C = 10mA$	400		V		
$V_{(BR)CBO}$	Collector – Base Breakdown Voltage	$I_C = 1mA$	800				
$V_{(BR)EBO}$	Emitter – Base Breakdown Voltage	$I_E = 1mA$	10				
I_{CBO}	Collector – Base Cut-Off Current	$V_{CB} = 800V$		10	μA		
			$T_C = 125^{\circ}C$	100			
I_{CEO}	Collector – Emitter Cut-Off Current	$I_B = 0$	$V_{CE} = 400V$	100	μA		
I_{EBO}	Emitter Cut-Off Current	$V_{EB} = 9V$	$I_C = 0$		10		
				$T_C = 125^{\circ}C$	100		
h_{FE}^*	DC Current Gain	$I_C = 0.1A$	$V_{CE} = 5V$	20	30	—	
		$I_C = 1A$	$V_{CE} = 5V$	15	45		
		$I_C = 2A$	$V_{CE} = 1V$	5	10		
$V_{CE(sat)}^*$	Collector – Emitter Saturation Voltage	$I_C = 100mA$	$I_B = 20mA$		0.05	0.1	V
		$I_C = 1A$	$I_B = 0.2A$		0.1	0.3	
		$I_C = 2A$	$I_B = 0.4A$		0.3	0.4	
$V_{BE(sat)}^*$	Base – Emitter Saturation Voltage	$I_C = 1A$	$I_B = 0.2A$		0.8	1.0	V
		$I_C = 2A$	$I_B = 0.4A$		0.9	1.1	
DYNAMIC CHARACTERISTICS							
f_t	Transition Frequency	$I_C = 0.2A$	$V_{CE} = 4V$		20	MHz	
C_{ob}	Output Capacitance	$V_{CB} = 20V$	$f = 1MHz$		40	pF	

* Pulse test $t_p = 300\mu s$, $\delta < 2\%$



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.