

PNP PRE-BIASED (R1=R2) SMALL SIGNAL SURFACE MOUNT TRANSISTOR

Features


- Epitaxial Planar Die Construction
- Ultra-Small Leadless Surface Mount Package
- Ideally Suited for Automated Assembly Processes
- "Lead Free", RoHS Compliant (Note 1)
- Halogen and Antimony Free "Green" Device (Note 2)
- Qualified to AEC-Q101 Standards for High Reliability

Part Number	R1 (NOM)	R2 (NOM)	Marking
DDTA144ELP	47K	47K	P2


Mechanical Data

- Case: DFN1006-3
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish — NiPdAu over Copper leadframe. Solderable per MIL-STD-202, Method 208
- Weight: 0.0009 grams (approximate)


DFN1006-3




Bottom View



Top View
Pin-Out



Device Symbol



Equivalent Inverter
Circuit


Ordering Information (Note 3)

Product	Marking	Reel size (inches)	Tape width (mm)	Quantity per reel
DDTA144ELP-7	P2	7	8	3,000
DDTA144ELP-7B	P2	7	8	10,000

- Notes:
1. No purposefully added lead.
 2. Diodes Inc's "Green" policy can be found on our website at <http://www.diodes.com>.
 3. For packaging details, go to our website at <http://www.diodes.com>.


Marking Information

DDTA144ELP-7



Top View
Dot Denotes
Collector Side

DDTA144ELP-7B



Top View
Bar Denotes Base
and Emitter Side

P2 = Product Type Marking Code

Maximum Ratings @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Characteristic	Symbol	Value	Unit
Supply Voltage	V_{CC}	-50	V
Input Voltage	V_{IN}	+10 to -40	V
Output Current (I_o)	$I_{C(MAX)}$	-200	mA

Thermal Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Characteristic	Symbol	Value	Unit
Power Dissipation (Note 4)	P_D	250	mW
Power Deration above 25°C	P_{der}	2	mW/ $^\circ\text{C}$
Thermal Resistance, Junction to Ambient Air (Note 4) (Equivalent to one heated junction of PNP)	$R_{\theta JA}$	500	$^\circ\text{C/W}$
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to +150	$^\circ\text{C}$

Electrical Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
Off Characteristics (Notes 5 & 6)						
Collector-Base Breakdown Voltage	BV_{CBO}	-50	—	—	V	$I_C = -10\mu\text{A}, I_E = 0$
Collector-Emitter Breakdown Voltage	BV_{CEO}	-50	—	—	V	$I_C = -1.0\text{mA}, I_B = 0$
Emitter-Base Breakdown Voltage	BV_{EBO}	-4.5	—	—	V	$I_E = -100\mu\text{A}, I_C = 0$
Collector Cutoff Current	I_{CEX}	—	—	-100	nA	$V_{CE} = -50\text{V}, V_{EB(OFF)} = 3.0\text{V}$
Base Cutoff Current (I_{BEX})	I_{BL}	—	—	-60	μA	$V_{CE} = -50\text{V}, V_{EB(OFF)} = 3.0\text{V}$
Collector-Base Cut Off Current	I_{CBO}	—	—	-100	nA	$V_{CB} = -50\text{V}, I_E = 0$
Collector-Emitter Cut Off Current, $I_{O(off)}$	I_{CEO}	—	—	-100	nA	$V_{CE} = -50\text{V}, I_B = 0$
Emitter-Base Cut Off Current	I_{EBO}	—	—	-100	μA	$V_{EB} = -4\text{V}, I_C = 0$
Input Off Voltage	$V_{I(off)}$	-300	—	—	mV	$V_{CC} = -5\text{V}, I_o = -100\mu\text{A}$
On Characteristics (Notes 5 & 6)						
Input-On Voltage	$V_{I(on)}$	—	—	-3.0	V	$V_O = -0.3\text{V}, I_o = -5\text{mA}$
Input Current	I_i	—	—	-7.2	mA	$V_i = -5\text{V}$
DC Current Gain	h_{FE}	90	—	—	—	$V_{CE} = -5\text{V}, I_C = -2.5\text{mA}$
		120	—	—	—	$V_{CE} = -5\text{V}, I_C = -5\text{mA}$
		150	—	—	—	$V_{CE} = -5\text{V}, I_C = -10\text{mA}$
		100	—	—	—	$V_{CE} = -5\text{V}, I_C = -100\text{mA}$
		180	—	—	—	$V_{CE} = -5\text{V}, I_C = -200\text{mA}$
Output On Voltage (Collector-Emitter Saturation Voltage)	$V_{O(on)}$	—	—	-150	mV	$I_i = -1\text{mA}, I_o = -10\text{mA}$
		—	—	-800750	mV	$I_i = -1\text{mA}, I_o = -450\text{mA}$
Input Resistance	R1	33	47	61	$\text{K}\Omega$	—
Resistance Ratio	(R2/R1)	0.8	1.0	1.2	—	—
Small Signal Characteristics						
Current Gain-Bandwidth Product	f_T	—	250	—	MHz	$V_{CE} = -10\text{V}, I_E = -5\text{mA}, f = 100\text{MHz}$

- Notes:
- Device mounted on FR-4 PCB, 1" x 0.85" x 0.062".
 - Short duration pulse test used to minimize self-heating effect. Pulse Test: Pulse width $t_p < 300\ \mu\text{s}$, Duty Cycle, $d_c \leq 2\%$.
 - Guaranteed by design.




Fig. 1 Power Dissipation vs. Ambient Temperature




Fig. 2 Typical DC Current Gain vs. Collector Current




Fig. 3 Typical Collector Emitter Saturation Voltage vs. Collector Current




Fig. 4 Typical Collector Emitter Voltage vs. Collector Current




Fig. 5 Typical Base Emitter Voltage vs. Collector Current




Fig. 6 Typical Input Voltage vs. Ambient Temperature






Fig. 7 Typical Base Emitter Saturation Voltage vs. Collector Current

Package Outline Dimensions



DFN1006-3			
Dim	Min	Max	Typ
A	0.47	0.53	0.50
A1	0	0.05	0.03
b1	0.10	0.20	0.15
b2	0.45	0.55	0.50
D	0.95	1.075	1.00
E	0.55	0.675	0.60
e	—	—	0.35
L1	0.20	0.30	0.25
L2	0.20	0.30	0.25
L3	—	—	0.40
All Dimensions in mm			

Suggested Pad Layout



Dimensions	Value (in mm)
Z	1.1
G1	0.3
G2	0.2
X	0.7
X1	0.25
Y	0.4
C	0.7

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2011, Diodes Incorporated

www.diodes.com



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.