

Inverter Grade SCRs

$I_{T(RMS)}$ T _c =65° C 50% Duty Cycle, Half Sine 1KHz (Amps)	I_{TSM} (Amps)		I_{DRM}/I_{RRM} @ Rated V_{DRM}/V_{RRM} and T _{J(Max)} (mA)	I^2t for Fusing @ 8.3 ms (A ² sec x 10 ⁴)	V_{DRM}/V_{RRM} Range (Volts)	V_{TM} @ I_{TM} T _J =25°C		Chip Size (mm)	Junction Temp. Range (°C)	R _{θJC} (°C/W)	$t_q(Max)$ @ T _{J(Max)} (μsec)
	50 Hz	60 Hz				I_{TM} (Amps)	V_{TM} (Volts)				
250	1500	1600	15-18	1.06	500-1400	500	3.5	18	-40 to 125	.135	40
240	3200	3500	25	5.1	100-1200	625	2.35	23	-40 to 125	.13	10 to 50
250	3200	3500	20	5.1	100-800	1500	2.85	22	-40 to 125	.15	20
250	3600	4000	25	6.6	100-1200	625	2.1	23	-40 to 125	.13	10 to 50
250	1700	1800	17	1.34	100-600	500	3	18	-40 to 125	.13	10
250	1700	1800	17	1.34	100-600	500	3	18	-40 to 125	.13	20
260	1700	1800	17	1.34	100-800	500	2.6	18	-40 to 125	.135	10
260	1700	1800	17	1.34	100-800	500	2.6	18	-40 to 125	.135	20
270	4150	4500	25	8.4	100-1200	625	1.85	23	-40 to 125	.13	10 to 50
300	6400	7000	30	20.5	100-1200	625	1.65	33	-40 to 125	.10	25 to 60
300	5400	6000	35	15	1400-1800	1500	3.15	33	-40 to 125	.06	40 to 60
325	5000	5500	45	12.6	500-1200	3000	4.2	30	-40 to 125	.06	40
325	5000	5500	45	12.6	500-1200	3000	4.2	30	-40 to 125	.06	30
345	3200	3500	25	5.1	100-1200	625	2.35	23	-40 to 125	.08	10 to 50
375	3600	4000	25	6.6	100-1200	625	2.1	23	-40 to 125	.08	10 to 50
400	6400	6800	35	19.2	1400-1800	1500	2.2	33	-40 to 125	.06	80 to 100
410	6500	7000	30	20.4	100-1000	625	1.5	33	-40 to 125	.10	10 to 50
410	7300	8000	30	26.6	100-1400	625	1.45	33	-40 to 125	.10	25 to 60

* = 25°C Value

x = ASCR, V_{RRM} = 10VDC Max.

$Q_{rr}(\text{Max})$ @ $T_J = 25^\circ\text{C}$ (μcoul)	Min dI/dt Repetitive on-State (A/ μsec)	Min Critical dV/dt @ $T_J(\text{Max})$ (V/ μsec)	Max VGT (V)	Max IGT (mA)	PACKAGE INFORMATION			
					Max Mounting Force or Torque	STYLE	Outline	TYPE NO.
25	500	200	5	500	$\frac{300 \text{ lb-in}}$ 348 kg-cm	$\frac{3}{4}$ -16 Stud	TO-93	C185
—	500	200	5	300	$\frac{800 \text{ lbs}}$ 3.56 KN	Press Pak	TO-200AB	C358
—	200	300	3*	150*	$\frac{300 \text{ lb-in}}$ 348 kg-cm	$\frac{3}{4}$ -16 Stud	TO-93	T607 __ _13
—	250	300	3*	150*	$\frac{300 \text{ lb-in}}$ 348 kg-cm	$\frac{3}{4}$ -16 Stud	TO-93	T607 __ _15
—	500	200	5	200	$\frac{800 \text{ lbs}}$ 3.56 KN	Press Pak	TO-200AB	C354
—	500	100	5	200	$\frac{800 \text{ lbs}}$ 3.56 KN	Press Pak	TO-200AB	C355
—	500	200	5	400	$\frac{800 \text{ lbs}}$ 3.56 KN	Press Pak	TO-200AB	C364
—	500	200	5	400	$\frac{800 \text{ lbs}}$ 3.56 KN	Press Pak	TO-200AB	C365
—	300	300	3*	150*	$\frac{300 \text{ lb-in}}$ 348 kg-cm	$\frac{3}{4}$ -16 Stud	TO-93	T607 __ _18
—	300	300	3*	150*	$\frac{360 \text{ lb-in}}$ 420 kg-cm	$\frac{3}{4}$ -16 Stud	T70	T707 __ _25
—	300	300	3*	150*	$\frac{2400 \text{ lbs}}$ 10.7 KN	Press Pak	T72	T72H __ _30
—	500	200	5	300	$\frac{2000 \text{ lbs}}$ 8.9 KN	Press Pak	TO-200AC	C387
—	500	200	5	300	$\frac{2000 \text{ lbs}}$ 8.9 KN	Press Pak	TO-200AC	C388
—	200	300	3*	150*	$\frac{1400 \text{ lbs}}$ 6.25 KN	Press Pak	T62	T627 __ _15
—	250	300	3*	150*	$\frac{1400 \text{ lbs}}$ 6.25 KN	Press Pak	T62	T627 __ _20
—	400	300	3*	150*	$\frac{2400 \text{ lbs}}$ 10.7 KN	Press Pak	T72	T72H __ _42
—	300	300	3*	150*	$\frac{360 \text{ lb-in}}$ 420 kg-cm	$\frac{3}{4}$ -16 Stud	T70	T707 __ _28
—	400	300	3*	150*	$\frac{360 \text{ lb-in}}$ 420 kg-cm	$\frac{3}{4}$ -16 Stud	T70	T707 __ _30



JEDEC TO-83

This datasheet has been downloaded from:

www.DatasheetCatalog.com

Datasheets for electronic components.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.