

N-CHANNEL J-FET

Qualified per MIL-PRF-19500/428

Devices

2N4416A


Qualified Level

JAN
JANTX
JANTXV

ABSOLUTE MAXIMUM RATINGS

Parameters / Test Conditions	Symbol	2N4416A	Unit
Gate-Source Voltage	V_{GS}	-35	Vdc
Drain-Source Voltage	V_{DS}	35	Vdc
Drain-Gate Voltage	V_{DG}	35	Vdc
Gate Current	I_G	10	mAdc
Power Dissipation $T_A = +25^{\circ}C$ ⁽¹⁾	P_T	300	mWdc
Operating Junction & Storage Temperature Range	T_{op}, T_{stg}	-65 to +200	$^{\circ}C$

(1) Derate linearly 1.7 mW/ $^{\circ}C$ for $T_A > +25^{\circ}C$.



*See appendix A for package outline

ELECTRICAL CHARACTERISTICS ($T_A = +25^{\circ}C$ unless otherwise noted)

Parameters / Test Conditions	Symbol	Min.	Max.	Units
Gate-Source Breakdown Voltage $V_{DS} = 0, I_G = 1.0 \mu\text{Adc}$	$V_{(BR)GSS}$	-35		Vdc
Gate Reverse Current $V_{DS} = 0, V_{GS} = 20 \text{ Vdc}$	I_{GSS}		-0.1	ηAdc
Drain Current $V_{DS} = 15 \text{ Vdc}$	I_{DSS}	5	15	mAdc
Gate-Source Voltage $V_{DS} = 15 \text{ Vdc}, I_D = 0.5 \text{ mAdc}$	V_{GS}	-1	-5.5	Vdc
Gate-Source Cutoff Voltage $V_{DS} = 15 \text{ Vdc}, I_D = 1.0 \eta\text{Adc}$	$V_{GS(off)}$	-2.5	-6.0	Vdc
Gate-Source Forward Voltage $V_{DS} = 0 \text{ Vdc}, I_G = 1.0 \text{ mAdc}$	V_{GSF}		1	Vdc

2N4416A JAN SERIES

ELECTRICAL CHARACTERISTICS ($T_A = +25^{\circ}\text{C}$ unless otherwise noted) (con't)

Parameters / Test Conditions	Symbol	Min.	Max.	Units
Magnitude of Small-Signal Common Source, Short-Circuit Forward Transfer Admittance ⁽²⁾ $V_{GS} = 0, V_{DS} = 15 \text{ Vdc}, f = 1.0 \text{ kHz}$	$ y_{fs} ^2$	4.5	7.5	ms
Small-Signal, Common-Source Short-Circuit Input Capacitance $V_{GS} = 0, V_{DS} = 15 \text{ Vdc}, 100 \text{ kHz} \leq f \leq 1.0 \text{ MHz}$	C_{iss}		4.0	pF
Small-Signal, Common-Source Short-Circuit Reverse Transfer Capacitance $V_{DS} = 15 \text{ Vdc}, V_{GS} = 0, 100 \text{ kHz} \leq f \leq 1.0 \text{ MHz}$	C_{rss}		0.8	pF
Small-Signal, Common-Source Short-Circuit Output Capacitance $V_{DS} = 15 \text{ Vdc}, V_{GS} = 0, 100 \text{ kHz} \leq f \leq 1.0 \text{ MHz}$	C_{oss}		2.0	pF

(2) Pulse Width = 100ms; Duty Cycle = 10%



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.