

DEVICE TYPE NO.	POLARITY	P_D @ $T_c=25^\circ\text{C}$	MAXIMUM RATINGS				ELECTRICAL CHARACTERISTICS				CASE
		WATTS	I_c AMPS	BV_{CBO}	BV_{CE}	BV_{EBO}	h_{FE} MIN.	I_c AMPS	V_{CE}	f MHZ *KHZ	
2N3713	NPN	150	10.0	80	60	7	25	.001	2	*30	T03
2N3714	NPN	150	10.0	100	80	7	25	.001	2	*30	T03
2N3715	NPN	150	10.0	80	60	7	50	1.00	2	*30	T03
2N3716	NPN	150	10.0	100	80	7	50	1.00	2	*30	T03
2N3734	NPN	1.00	1.50	50	30	5	30	1.00	1.5	300	T039
2N3735	NPN	1.00	1.50	75	50	5	20	1.00	1.5	250	T039
2N3740	PNP	25.0	1.00	60	60	7	30	.250	1	4	T066
2N3741	PNP	25.0	1.00	80	80	7	30	.250	1	4	T066
2N3742	NPN	1.00	.050	300	300	7	20	.030	10	30	T039
2N3743	PNP	1.00	.050	300	300	7	25	.030	10	30	T039
2N3762	PNP	1.00	1.50	40	40	5	30	1.00	1.5	180	T039
2N3763	PNP	1.00	1.50	60	60	5	20	1.00	1.5	150	T039
2N3766	NPN	20.0	1.00	80	60	6	40	.500	10	10	T066
2N3767	NPN	20.0	1.00	100	80	6	40	.500	10	10	T066
2N3771	NPN	150	30.0	50	40	5	15	.002	4	*200	T03
2N3772	NPN	150	20.0	100	60	7	10	.005	4	*200	T03
2N3773	NPN	150	30.0	160	140	7	15	8.00	4	*200	T03
2N3778	PNP	5.00	1.00	40	40	8	10	2.00	2	1	T039
2N3788	NPN	100	2.00	400	325	5	20	.005	5	*50	T03
2N3789	PNP	150	10.0	60	60	7	25	1.00	2	*30	T03
2N3790	PNP	150	10.0	80	80	7	25	1.00	2	*30	T03
2N3791	PNP	150	10.0	80	60	7	25	1.00	2	*30	T03
2N3792	PNP	150	10.0	80	80	7	50	1.00	2	*30	T03
2N3799	PNP	.350	.050	60	60	5	250	.010	5	100	T018
2N3830	NPN	1.00	1.20	80	50	5	30	5.00	1	200	T039
2N3831	NPN	1.00	1.20	70	40	5	35	5.00	1	200	T039
2N3839	NPN	.200	.040	30	15	2.5	30	.003	1	2000	T072
2N3863	NPN	117	7.50	70	50	7	30	3.00	2	*500	T03
2N3864	NPN	117	7.50	110	90	7	30	3.00	2	*500	T03
2N3865	NPN	117	7.50	160	150	7	30	3.00	2	*500	T03
2N3866	NPN	5.00	.400	55	30	3.5	10	.050	5	500	T039
2N3878	NPN	35.0	4.00	120	50	7	50	.500	5	40	T066
2N3879	NPN	35.0	7.00	120	75	7	12	4.00	2	40	T066
2N3880	NPN	.200	.030	30	15	2.5	50	.003	6	1200	T072
2N3902	NPN	100	3.5A	700	400	5	30	1.00	5	2.8	T03
2N3917	NPN	20.0	2.00	80	40	6	30	1.00	4	50	T03
2N3923	NPN	.800	.100	150	150	6	20	.025	10	40	T039
2N3931	PNP	.700	.100	180	180	6	100	.001	10	40	T039
2N3932	NPN	.200	.030	30	20	2.5	50	.002	8	750	T072
2N3933	NPN	.200	.030	40	30	2.5	60	.002	8	750	T072
2N3948	NPN	5.00	.400	36	20	3.5	15	.050	5	700	T039
2N3963	PNP	.360	.200	80	80	6	100	.001	5	40	T018
2N3964	PNP	.360	.200	45	45	6	250	.001	5	50	T018
2N3965	PNP	.360	.200	60	60	6	250	.001	5	50	T018
2N4000	NPN	1.00	1.00	100	80	8	30	.500	2	40	T039
2N4001	NPN	1.00	1.00	120	100	8	40	.500	2	40	T039
2N4030	PNP	.800	1.00	60	60	5	30	.100	5	100	T039
2N4031	PNP	.800	1.00	80	80	5	30	.100	5	100	T039
2N4032	PNP	.800	1.00	60	60	5	75	.100	5	150	T039
2N4033	PNP	.800	1.00	80	80	5	75	.100	5	150	T039
2N4036	PNP	.700	1.00	90	65	7	20	.150	2	60	T039
2N4037	PNP	1.00	1.00	60	40	7	50	.150	10	60	T039
2N4046	NPN	.800	.500	50	30	6	40	.100	1	250	T039
2N4047	NPN	.800	.500	80	50	6	40	.100	1	250	T039
2N4070	NPN	65.0	10.0	120	100	8	40	5.00	5	20	T03
2N4080	PNP	.300	.050	20	15	3	20	.003	1	1000	T072
2N4121	PNP	.200	.100	40	40	5	50	.001	10	400	T0106
2N4122	PNP	.200	.100	40	40	5	150	.001	10	450	T0106
2N4134	NPN	.200	.030	30	30	3	25	.004	5	350	T072
2N4135	NPN	.200	.030	30	30	3	25	.004	5	425	T072
2N4137	NPN	.360	.200	40	40	4.5	40	.010	.35	500	T018
2N4140	NPN	.300	.200	60	30	5	40	.150	10	250	T0106
2N4141	NPN	.300	.200	60	30	5	100	.150	10	250	T0106

This datasheet has been downloaded from:

www.DatasheetCatalog.com

Datasheets for electronic components.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.