

## NPN POWER SILICON TRANSISTOR

Qualified per MIL-PRF-19500/454

### Devices


2N5660      2N5661      2N5662      2N5663

### Qualified Level

JAN, JANTX  
JANTXV

### MAXIMUM RATINGS

Ratings	Symbol	2N5660 2N5662	2N5661 2N5663	Unit
Collector-Emitter Voltage	$V_{CEO}$	200	300	Vdc
Collector-Base Voltage	$V_{CBO}$	250	400	Vdc
Collector-Emitter Voltage	$V_{CER}$	250	400	Vdc
Emitter-Base Voltage	$V_{EBO}$	6.0		Vdc
Base Current	$I_B$	0.5		Adc
Collector Current	$I_C$	2.0		Adc
		<b>2N5660 2N5661</b>	<b>2N5662 2N5663</b>	
Total Power Dissipation @ $T_A = +25^{\circ}\text{C}$ @ $T_C = +100^{\circ}\text{C}$	$P_T$	2.0 <sup>(1)</sup>	1.0 <sup>(2)</sup>	W
		20 <sup>(3)</sup>	15 <sup>(4)</sup>	W
Operating & Storage Junction Temperature Range	$T_J, T_{stg}$	-65 to +200		$^{\circ}\text{C}$



TO-66\*  
(TO-213AA)  
2N5660, 2N5661



TO-5\*  
2N5662, 2N5663

### THERMAL CHARACTERISTICS

Characteristics	Symbol	2N5660 2N5661	2N5662 2N5663	Unit
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	5.0	6.67	$^{\circ}\text{C}/\text{W}$
Junction-to-Ambient	$R_{\theta JA}$	87.5	145.8	

- 1) Derate linearly 11.4 mW/ $^{\circ}\text{C}$  for  $T_A > +25^{\circ}\text{C}$
- 2) Derate linearly 5.7 mW/ $^{\circ}\text{C}$  for  $T_A > +25^{\circ}\text{C}$
- 3) Derate linearly 200 mW/ $^{\circ}\text{C}$  for  $T_C > +100^{\circ}\text{C}$
- 4) Derate linearly 150 mW/ $^{\circ}\text{C}$  for  $T_C > +100^{\circ}\text{C}$

\*See appendix A for package outline

### ELECTRICAL CHARACTERISTICS ( $T_C = 25^{\circ}\text{C}$ unless otherwise noted)

Characteristics	Symbol	Min.	Max.	Unit
-----------------	--------	------	------	------

### OFF CHARACTERISTICS

Collector-Emitter Breakdown Voltage $I_C = 10 \text{ mAdc}$	2N5660, 2N5662 2N5661, 2N5663	$V_{(BR)CEO}$	200 300	Vdc
Collector-Base Breakdown Voltage $I_C = 10 \text{ mAdc}, R_{BE} = 100\Omega$	2N5660, 2N5662 2N5661, 2N5663	$V_{(BR)CER}$	250 400	Vdc
Emitter-Base Breakdown Voltage $I_E = 10 \mu\text{Adc}$		$V_{(BR)EBO}$	6.0	Vdc

**ELECTRICAL CHARACTERISTICS (con't)**

Characteristics	Symbol	Min.	Max.	Unit
Collector-Emitter Cutoff Current V <sub>CE</sub> = 200 Vdc V <sub>CE</sub> = 300 Vdc	I <sub>CES</sub>		0.2	μAdc
2N5660, 2N5662 2N5661, 2N5663			0.2	μAdc
Collector-Base Cutoff Current V <sub>CB</sub> = 200 Vdc V <sub>CB</sub> = 250 Vdc V <sub>CB</sub> = 300 Vdc V <sub>CB</sub> = 400 Vdc	I <sub>CBO</sub>		0.1	μAdc
2N5660, 2N5662			1.0	mAdc
2N5660, 2N5662			0.1	μAdc
2N5661, 2N5663 2N5661, 2N5663			1.0	mAdc

**ON CHARACTERISTICS <sup>(5)</sup>**

Forward-Current Transfer Ratio I <sub>C</sub> = 50 mAdc, V <sub>CE</sub> = 2.0 Vdc I <sub>C</sub> = 0.5 Adc, V <sub>CE</sub> = 5.0 Vdc I <sub>C</sub> = 1.0 Adc, V <sub>CE</sub> = 5.0 Vdc I <sub>C</sub> = 2.0 Adc, V <sub>CE</sub> = 5.0 Vdc	h <sub>FE</sub>	2N5660, 2N5662 2N5661, 2N5663	40 25		
2N5660, 2N5662 2N5661, 2N5663		40 25	120 75		
All Types		15			
All Types		5.0			
Collector-Emitter Saturation Voltage I <sub>C</sub> = 1.0 Adc, I <sub>B</sub> = 0.1 Adc I <sub>C</sub> = 2.0 Adc, I <sub>B</sub> = 0.4 Adc	V <sub>CE(sat)</sub>		0.4 0.8		Vdc
Base-Emitter Saturation Voltage I <sub>C</sub> = 1.0 Adc, I <sub>B</sub> = 0.1 Adc I <sub>C</sub> = 2.0 Adc, I <sub>B</sub> = 0.4 Adc	V <sub>BE(sat)</sub>		1.2 1.5		Vdc

**DYNAMIC CHARACTERISTICS**

Magnitude of Common Emitter Small-Signal Short-Circuit Forward Current Transfer Ratio I <sub>C</sub> = 0.1 Adc, V <sub>CE</sub> = 5.0 Vdc, f = 10 MHz	h <sub>fe</sub>	2.0	7.0		
Output Capacitance V <sub>CB</sub> = 10 Vdc, I <sub>E</sub> = 0, 100 kHz ≤ f ≤ 1.0 MHz	C <sub>obo</sub>		45		pF

**SWITCHING CHARACTERISTICS**

Turn-On Time V <sub>CC</sub> = 100 Vdc; I <sub>C</sub> = 0.5 Adc; I <sub>B1</sub> = 15 Adc V <sub>CC</sub> = 100 Vdc; I <sub>C</sub> = 0.5 Adc; I <sub>B1</sub> = 25 Adc	t <sub>on</sub>	2N5660, 2N5662 2N5661, 2N5663	0.25 0.25		μs
Turn-Off Time V <sub>CC</sub> = 100 Vdc; I <sub>C</sub> = 0.5 Adc; I <sub>B1</sub> = -I <sub>B2</sub> = 15 Adc V <sub>CC</sub> = 100 Vdc; I <sub>C</sub> = 0.5 Adc; I <sub>B1</sub> = -I <sub>B2</sub> = 25 Adc		t <sub>off</sub>	2N5660, 2N5662 2N5661, 2N5663	0.85 1.2	

**SAFE OPERATING AREA**

<b>DC Tests</b> T <sub>C</sub> = +100°C, 1 Cycle, t ≥ 1.0 s					
<b>Test 1</b> V <sub>CE</sub> = 10 Vdc, I <sub>C</sub> = 2.0 Adc V <sub>CE</sub> = 7.5 Vdc, I <sub>C</sub> = 2.0 Adc					
<b>Test 2</b> V <sub>CE</sub> = 40 Vdc, I <sub>C</sub> = 500 mAdc V <sub>CE</sub> = 25 Vdc, I <sub>C</sub> = 600 mAdc					
<b>Test 3</b> V <sub>CE</sub> = 200 Vdc, I <sub>C</sub> = 36 mAdc V <sub>CE</sub> = 200 Vdc, I <sub>C</sub> = 27 mAdc					
<b>Test 4</b> V <sub>CE</sub> = 300 Vdc, I <sub>C</sub> = 19 mAdc V <sub>CE</sub> = 300 Vdc, I <sub>C</sub> = 14 mAdc					

(5) Pulse Test: Pulse Width = 300μs, Duty Cycle ≤ 2.0%.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.