


Central Semiconductor Corp.

Central Semiconductor Corp.

Central Semiconductor Corp.

Central Semiconductor Corp.

145 Adams Avenue  
Hauppauge, New York 11788



2N5632 2N5633 2N5634 NPN  
2N6229 2N6230 2N6231 PNP

COMPLEMENTARY SILICON POWER  
TRANSISTORS

JEDEC TO-3 CASE

## DESCRIPTION

The CENTRAL SEMICONDUCTOR 2N5632, 2N6229 series types are complementary silicon power transistors manufactured by the epitaxial base process mounted in a hermetically sealed metal case designed for high power amplifier and switching applications where high voltages are required.

MAXIMUM RATINGS ( $T_C=25^\circ\text{C}$  unless otherwise noted)

	SYMBOL	2N5632 2N6229	2N5633 2N6230	2N5634 2N6231	UNIT
Collector-Base Voltage	$V_{CB0}$	100	120	140	V
Collector-Emitter Voltage	$V_{CE0}$	100	120	140	V
Emitter-Base Voltage	$V_{EB0}$	7.0	7.0	7.0	V
Collector Current	$I_C$	10	10	10	A
Collector Current (Peak)	$I_{CM}$	15	15	15	A
Base Current	$I_B$	5.0	5.0	5.0	A
Power Dissipation	PD	150	150	150	W
Operating and Storage Junction Temperature	$T_J, T_{STG}$	-65 TO +200			$^\circ\text{C}$
Thermal Resistance	$\theta_{JC}$	1.17			$^\circ\text{C}/\text{W}$

ELECTRICAL CHARACTERISTICS ( $T_C=25^\circ\text{C}$  unless otherwise noted)

SYMBOL	TEST CONDITIONS	2N5632 2N6229		2N5633 2N6230		2N5634 2N6231		UNIT
		MIN	MAX	MIN	MAX	MIN	MAX	
$I_{CB0}$	$V_{CB}=\text{Rated } V_{CB0}$		1.0		1.0		1.0	mA
$I_{CEV}$	$V_{CE}=\text{Rated } V_{CB0}, V_{EB}(\text{OFF})=1.5\text{V}$		1.0		1.0		1.0	mA
$I_{CEV}$	$V_{CE}=\text{Rated } V_{CB0}, V_{EB}(\text{OFF})=1.5\text{V}, T_C=150^\circ\text{C}$		5.0		5.0		5.0	mA
$I_{CE0}$	$V_{CE}=\frac{1}{2} \text{ Rated } V_{CB0}$		1.0		1.0		1.0	mA
$I_{EB0}$	$V_{BE}=7.0\text{V}$		1.0		1.0		1.0	mA
$BV_{CE0}$	$I_C=200\text{mA}$	100		120		140		V
$V_{CE}(\text{SAT})$	$I_C=7.5\text{A}, I_B=0.75\text{A}$		1.0		1.0		1.0	V
$V_{CE}(\text{SAT})$	$I_C=10\text{A}, I_B=2.0\text{A}$		2.0		2.0		2.0	V
$V_{BE}(\text{SAT})$	$I_C=7.5\text{A}, I_B=0.75\text{A}$		2.0		2.0		2.0	V
$V_{BE}(\text{ON})$	$V_{CE}=2.0\text{V}, I_C=5.0\text{A}$		1.5		1.5		1.5	V
hFE	$V_{CE}=2.0\text{V}, I_C=5.0\text{A}$	25	100	20	80	15	60	
hFE	$V_{CE}=2.0\text{V}, I_C=10\text{A}$	5.0		5.0		5.0		
hfe	$V_{CE}=10\text{V}, I_C=2.0\text{A}, f=1.0\text{kHz}$	15		15		15		
$f_T$	$V_{CE}=20\text{V}, I_C=1.0\text{A}, f=0.5\text{MHz}$	1.0		1.0		1.0		MHz
$C_{ob}$	$V_{CB}=10\text{V}, I_E=0, f=0.1\text{MHz}$ (NPN types)		300		300		300	pF
$C_{ob}$	$V_{CB}=10\text{V}, I_E=0, f=0.1\text{MHz}$ (PNP types)		600		600		600	pF

**Central**<sup>TM</sup>  
Semiconductor Corp.

145 Adams Avenue  
Hauppauge, NY 11788 USA  
Tel: (631) 435-1110 • Fax: (631) 435-1824  
www.centrasemi.com



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.