

MICRO ELECTRONICS

BC351

**PNP
SILICON
TRANSISTOR**

DESCRIPTION

BC351 is PNP silicon planar transistor designed for AF small signal amplifier stages.

TO-92A



EBC

ABSOLUTE MAXIMUM RATINGS

Collector-Emitter Voltage	VCEO	30V
Collector-Base Voltage	VCBO	40V
Emitter-Base Voltage	VEBO	5V
Collector Current	IC	100mA
Continuous Power Dissipation	Pd	300mW
Operating & Storage Junction Temperature	Tj, Tstg	-55 to +150°C

ELECTRO-OPTICAL CHARACTERISTICS (Ta=25°C)

PARAMETER	SYMBOL	MIN	MAX	UNIT	CONDITIONS	
Collector-Emitter Breakdown Voltage	LVCEO	30		V	IC=1mA	IB=0
Collector-Base Breakdown Voltage	BVCBO	40		V	IC=100µA	IE=0
Emtter-Base Breakdown Voltage	BVEBO	5		V	IE=100µA	IC=0
Collector Cutoff Current	ICBO		100	nA	VCB=20V	IE=0
D.C. Current Gain	HFE	40	450		IC=2mA	VCE=5V
	Group L	40	120		IC=2mA	VCE=5V
	Group A	110	220		IC=2mA	VCE=5V
	Group B	200	450		IC=2mA	VCE=5V
Collector-Emitter Saturation Voltage	VCE(sat)		0.25	V	IC=10mA	IB=1mA
Output Capacitance	Cob		4	pF	VCB=10V	f=1MHz
Current Gain Bandwidth Product	fT	125		MHz	IC=5mA	VCE=10V
					f=100MHz	

* Pulse test : pulse width < 300µS, duty cycle < 2%.



MICRO ELECTRONICS LTD.

38, Hung To Road, Microtron Building, Kwun Tong, Kowloon, Hong Kong.
Kwun Tong P.O. Box 69477 Hong Kong. Fax No. 2341 0321 Telex: 43510 Micro Hx. Tel: 2343 0181-5

Aug-97



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.