

1N4728A through 1N4753A

Silicon Epitaxial Planar Zener Diodes

for Stabilized Power Supply

HITACHI

Preliminary

Rev. 0

Aug. 1993


Features

- Glass package DO-41 structure ensures high reliability.
- Wide spectrum from 3.3V through 36V of zener voltage provide flexible application.

Ordering Information

Type No.	Mark	Package Code
1N4728A through 1N4753A	Type No.	DO-41

Outline



Absolute Maximum Ratings (Ta = 25°C)

Item	Symbol	Value	Unit
Power dissipation	P_d	1.0	W
Surge power dissipation	$P_d(\text{surge})^*$	12	W
Junction temperature	T_j	175	°C
Storage temperature	T_{stg}	-55 to +175	°C

* $P_W=10\text{ms}$

Electrical Characteristics (Ta = 25°C)

	V_Z (V) *		I_R (μA)		Z_{ZT} (Ω)		Z_{ZK} (Ω)	
	Test Condition	Test Condition	Test Condition	Test Condition	Test Condition	Test Condition	Test Condition	Test Condition
	$I_Z(\text{mA})$	Max	$V_R(\text{V})$	Max	$I_{ZT}(\text{mA})$	Max	$I_{ZK}(\text{mA})$	Max
1N4728A	3.3 $\pm$ 5(%)	76	100	1.0	10	76	400	1.0
1N4729A	3.6 $\pm$ 5(%)	69	100	1.0	10	69	400	1.0
1N4730A	3.9 $\pm$ 5(%)	64	50	1.0	9	64	400	1.0
1N4731A	4.3 $\pm$ 5(%)	58	10	1.0	9	58	400	1.0
1N4732A	4.7 $\pm$ 5(%)	53	10	1.0	8	53	500	1.0

* Tested with DC.

1N4728A through 1N4753A

	V _Z (V) *		I _R (μA)		Z _{ZT} (Ω)		Z _{ZK} (Ω)	
	Test Condition	I _Z (mA)	Max	Test Condition	Max	I _{ZT} (mA)	Max	Test Condition
				V _R (V)				I _{ZK} (mA)
1N4733A	5.1±5(%)	49	10	1.0	7	49	550	1.0
1N4734A	5.6±5(%)	45	10	2.0	5	45	600	1.0
1N4735A	6.2±5(%)	41	10	3.0	2	41	700	1.0
1N4736A	6.8±5(%)	37	10	4.0	3.5	37	700	1.0
1N4737A	7.5±5(%)	34	10	5.0	4	34	700	0.5
1N4738A	8.2±5(%)	31	10	6.0	4.5	31	700	0.5
1N4739A	9.1±5(%)	28	10	7.0	5	28	700	0.5
1N4740A	10 ±5(%)	25	10	7.6	7	25	700	0.25
1N4741A	11 ±5(%)	23	5	8.4	8	23	700	0.25
1N4742A	12 ±5(%)	21	5	9.1	9	21	700	0.25
1N4743A	13 ±5(%)	19	5	9.9	10	19	700	0.25
1N4744A	15 ±5(%)	17	5	11.4	14	17	700	0.25
1N4745A	16 ±5(%)	15.5	5	12.2	16	15.5	700	0.25
1N4746A	18 ±5(%)	14.0	5	13.7	20	14.0	750	0.25
1N4747A	20 ±5(%)	12.5	5	15.2	22	12.5	750	0.25
1N4748A	22 ±5(%)	11.5	5	16.7	23	11.5	750	0.25
1N4749A	24 ±5(%)	10.5	5	18.2	25	10.5	750	0.25
1N4750A	27 ±5(%)	9.5	5	20.6	35	9.5	750	0.25
1N4751A	30 ±5(%)	8.5	5	22.8	40	8.5	1000	0.25
1N4752A	33 ±5(%)	7.5	5	25.1	45	7.5	1000	0.25
1N4753A	36 ±5(%)	7.0	5	27.4	50	7.0	1000	0.25

* Tested with DC.




Fig.1 Zener current Vs. Zener voltage




Fig.2 Temperature Coefficient Vs. Zener voltage




Fig.3 Power Dissipation Vs. Ambient Temperature

1N4728A through 1N4753A




Fig.4 Surge Reverse Power Ratings






Fig.5 Transient Thermal Impedance

1N4728A through 1N4753A

Package Dimensions

Unit: mm



- 1 Cathode
- 2 Anode

HITACHI Code	DO-41
JEDEC Code	DO-41
EIAJ Code	SC-47
Weight (g)	0.38

Expanded drawing of marking