

1SS382

Ultra High Speed Switching Application


Unit: mm

- Small package
- Composed of 2 independent diodes.
- Low forward voltage : $V_F(3) = 0.92V$ (typ.)
- Fast reverse recovery time: $T_{rr} = 1.6ns$ (typ.)

Maximum Ratings (Ta = 25°C)

Characteristic	Symbol	Rating	Unit
Maximum (peak) reverse Voltage	V_{RM}	85	V
Reverse voltage	V_R	80	V
Maximum (peak) forward current	I_{FM}	300 *	mA
Average forward current	I_O	100 *	mA
Surge current (10ms)	I_{FSM}	2	A
Power dissipation	P	100 *	mW
Junction temperature	T_j	125	°C
Storage temperature range	T_{stg}	-55~125	°C

*: Unit rating. Total rating = unit rating × 1.5




Weight: 0.006g


Electrical Characteristics (Ta = 25°C)

Characteristic	Symbol	Test Circuit	Test Condition	Min	Typ.	Max	Unit
Forward voltage	$V_F(1)$	—	$I_F = 1mA$	—	0.61	—	V
	$V_F(2)$	—	$I_F = 10mA$	—	0.74	—	V
	$V_F(3)$	—	$I_F = 100mA$	—	0.92	1.20	V
Reverse current	$I_R(1)$	—	$V_R = 30V$	—	—	0.1	μA
	$I_R(2)$	—	$V_R = 80V$	—	—	0.5	μA
Total capacitance	CT	—	$V_R = 0, f = 1MHz$	—	0.9	2.0	pF
Reverse recovery time	trr	—	$I_F = 10mA, Fig.1$	—	1.6	4.0	ns

Pin Assignment (Top View)



Marking



961001EAA2

● TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.









Fig.1 Reverse Recovery Time (t_{rr}) Test Circuit


INPUT WAVEFORM



PULSE GENERATOR
($R_{OUT} = 50\Omega$)



OUTPUT WAVEFORM



961001EAA2

- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.