

Medium Power Transistor (Motor or Relay drive)


(-80V, -4A)

2SB1616

●Features

- 1) Darlington connection for a high hFE.
- 2) Built-in resistor between base and emitter.
- 3) Built-in damper diode.
- 4) Complements the 2SC4574.

●Circuit schematic



●Electrical characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-emitter breakdown voltage	BV _{CEO}	-80	—	—	V	I _C = -1mA
Collector-base breakdown voltage	BV _{CBO}	-80	—	—	V	I _C = -50 μA
Emitter-base breakdown voltage	BV _{EB0}	-7	—	—	V	I _E = -50 μA
Collector cutoff current	I _{CBO}	—	—	-10	μA	V _{CB} = -80V
Emitter cutoff current	I _{EB0}	—	—	-10	μA	V _{EB} = -5V
Collector-emitter saturation voltage	V _{CE(sat)}	—	—	-1.5	V	I _C /I _B = -2A/-4mA
DC current transfer ratio	h _{FE}	1000	—	10000	—	V _{CE} /I _C = -3V/-2A
Transition frequency	f _T	—	20	—	MHz	V _{CE} = -5V, I _E = 0.5A, f = 10MHz
Output capacitance	C _{ob}	—	22	—	pF	V _{CB} = -10V, I _E = 0A, f = 1MHz

*1 Measured using pulse current. *2 Transition frequency of mounted transistor.

(SPEC-B426)


Power Transistor (80V, 4A)

2SD2478

●Features

- 1) Darlington connection for a high hFE.
- 2) Built-in resistor between base and emitter.
- 3) Built-in damper diode.
- 4) Complements the 2SC4574.

●Circuit schematic



●Absolute maximum ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit
Collector-base voltage	V _{CB0}	80	V
Collector-emitter voltage	V _{CE0}	80	V
Emitter-base voltage	V _{EB0}	7	V
Collector current	I _C	4	A (DC)
	I _{CP}	6	A (t=100ms)
Collector power dissipation	P _C	2	W
		30	W (T _C = 25°C)
Junction temperature	T _J	150	°C
Storage temperature	T _{stg}	-55~150	°C

●Packaging specifications and hFE

Type	2SC4574
Package	TO-220FP
hFE	1k~10k
Code	—
Basic ordering unit (pieces)	500

●Electrical characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	BV _{CBO}	80	—	—	V	I _C = 50 μA
Collector-emitter breakdown voltage	BV _{CEO}	80	—	—	V	I _C = -1mA
Collector cutoff current	I _{CBO}	—	—	100	μA	V _{CB} = 80V
Emitter cutoff current	I _{EB0}	—	—	10	μA	V _{EB} = 5V
Collector-emitter saturation voltage	V _{CE(sat)}	—	—	1.5	V	I _C /I _B = 2A/4mA
DC current transfer ratio	h _{FE}	1000	—	10000	—	V _{CE} /I _C = 3V/2A
Transition frequency	f _T	—	40	—	MHz	V _{CE} = 5V, I _E = -0.2A, f = 10MHz
Output capacitance	C _{ob}	—	35	—	pF	V _{CB} = 10V, I _E = 0A, f = 1MHz

*1 Measured using pulse current. *2 Transition frequency of mounted transistor.

Bi-polar transistors

Type	External dimensions (Units : mm)	Features
<p>UMT5 SC-88A type</p>	<p>All terminals have same dimensions</p>	<p>The UMT5 consists of two connected transistors or digital transistors in a UMT3 (SC-70) package. The mounting area can be reduced by 50% compared to the UMT3 and the internal circuitry is completed, making this package ideal for high density mounting at half the assembly cost.</p>
<p>UMT6 SC-88 type</p>	<p>All terminals have same dimensions</p>	<p>The UMT6 consists of two independent transistors or two independent digital transistors in a UMT (SC-70) package. The mounting area and mounting cost can be reduced by 50% compared to the UMT3, and the two transistors are independent to allow free configuration of a high density circuit.</p>

●Types and features of leaded packages

Type	External dimensions (Units : mm)	Features
<p>SPT (SC-72 type)</p>		<p>The SPT is a smaller version of the conventional TO-92 type. The body size (3×4×2 mm³) has been reduced to 1/4 that of the TO-92 (5×5×4 mm³). The SPT is available on tape for automatic insertion, and less space is occupied on the printed circuit board than the TO-92. Reliability is the same as the TO-92.</p>
<p>FTR</p>		<p>SIL type with a height of 3.4 mm and a lead pitch of 2.54 mm.</p>
<p>FTL</p>		<p>The FTL is a radial taping version of the highly popular FTR. This enables automatic high-density mounting with a radial insertion machine.</p>
<p>ATR (SC-71 type)</p>		<p>SC-71 type with a height of 4.4 mm and a P_c=1W type.</p>

EXPLANATION

Type	External dimensions (Units : mm)	Features
<p>ATV</p>		<p>The ATV is a radial tapping version of the highly popular ATR. This enables automatic high-density mounting with a radial insertion machine.</p>
<p>TO-92 (SC-43 type)</p>		<p>The SC-43 is for general purpose small signals.</p>
<p>TO-126FP</p>		<p>The TO-126FP is an isolation type package based on a TO-126 full mold. In addition to the features of the TO-126, molded heat sink fins allow easy isolation of the heat sink.</p>
<p>TO-220FP (SC-67 type)</p>		<p>The TO-220FP is an isolation type package based on a TO-220 full mold. In addition to the features of the TO-126 and TO-220, molded heat sink fins allow easy isolation of the heat sink.</p>

7828999 0016713 7T7

Type	External dimensions (Units : mm)	Features
TO-220FN		<p>The TO-220FN features the same performance as the TO-220FP with approximately 2 mm less height, allowing the design of slimmer devices. Furthermore, the elimination of support pins in the fin (collector electrode) solves short-circuiting problems with neighboring components and the chassis.</p> <p>To make the height to the installation hole the same as the TO-220FP, it can be replaced as is from the TO-220FP.</p>

EXPLANATION

■ 7828999 0016714 633 ■