


2SB566(K), 2SB566A(K)

Silicon PNP Triple Diffused
Low Frequency Power Amplifier Power Switching
Complementary Pair with 2SD476(K) and 2SD476A(K)

Absolute Maximum Ratings (Ta = 25°C)

Item	Symbol	2SB	2SB	Unit
		566(K)	566A(K)	
Collector to base voltage	V _{CBO}	-70	-70	V
Collector to emitter voltage	V _{CEO}	-50	-60	V
Emitter to base voltage	V _{EBO}	-5	-5	V
Collector current	I _C	-4	-4	A
Collector peak current	i _{C(peak)}	-8	-8	A
Collector power dissipation	P _C ^{*1}	40	40	W
Junction temperature	T _j	150	150	°C
Storage temperature	T _{stg}	-55 to +150	-55 to +150	°C

TO-220AB



1. Base
2. Collector (Flange)
3. Emitter

Note: 1. Value at T_C = 25°C.

Electrical Characteristics (Ta = 25°C)

Item	Symbol	2SB566(K)			2SB566A(K)			Unit	Test condition
		Min	Typ	Max	Min	Typ	Max		
Collector to base breakdown voltage	V _{(BR)CBO}	-70	—	—	-70	—	—	V	I _C = -10 μA, I _E = 0
Collector to emitter breakdown voltage	V _{(BR)CEO}	-50	—	—	-60	—	—	V	I _C = -50 mA, R _{BE} = ∞
Emitter to base breakdown voltage	V _{(BR)EBO}	-5	—	—	-5	—	—	V	I _E = -10 μA, I _C = 0
Collector cutoff current	I _{CBO}	—	—	-1	—	—	-1	μA	V _{CB} = -50 V, I _E = 0
DC current transfer ratio	h _{FE1} ^{*1}	60	—	200	60	—	200		V _{CE} = -4 V, I _C = -1 A
	h _{FE2}	35	—	—	35	—	—		V _{CE} = -4 V, I _C = -0.1 A
Collector to emitter saturation voltage	V _{CE(sat)}	—	—	-1.0	—	—	-1.0	V	I _C = -2 A, I _B = -0.2 A
Base to emitter saturation voltage	V _{BE(sat)}	—	—	-1.2	—	—	-1.2	V	I _C = -2 A, I _B = -0.2 A
Gain bandwidth product	f _T	—	7	—	—	7	—	MHz	V _{CE} = -4 V, I _C = -0.5 A


2SB566(K), 2SB566A(K)

Electrical Characteristics (Ta = 25°C) (cont)


Item	Symbol	2SB566(K)			2SB566A(K)			Unit	Test condition
		Min	Typ	Max	Min	Typ	Max		
Turn on time	t_{on}	—	0.3	—	—	0.3	—	μs	$V_{CC} = -10.5 V$ $I_C = 10I_{B1} = -10I_{B2} = -0.5 A$
Turn off time	t_{off}	—	3.0	—	—	3.0	—	μs	
Storage time	t_{stg}	—	2.5	—	—	2.5	—	μs	

Note: 1. The 2SB566(K) and 2SB566A(K) are grouped by h_{FE1} as follows.


B	C
60 to 120	100 to 200




Typical Output Characteristics



Typical Transfer Characteristics



DC Current Transfer Ratio vs. Collector Current



Collector to Emitter Saturation Voltage vs. Collector Current

