

TOSHIBA Transistor Silicon NPN Epitaxial Type


2SC5376F

Audio Frequency General Purpose Amplifier Applications
For Muting and Switching Applications


- Low Collector Saturation Voltage: $V_{CE(sat)}(1) = 15\text{ mV (typ.)}$
@ $I_C = 10\text{ mA}/I_B = 0.5\text{ mA}$
- High Collector Current: $I_C = 400\text{ mA (max)}$

Maximum Ratings (Ta = 25°C)


Characteristics	Symbol	Rating	Unit
Collector-base voltage	V_{CBO}	15	V
Collector-emitter voltage	V_{CEO}	12	V
Emitter-base voltage	V_{EBO}	5	V
Collector current	I_C	400	mA
Base current	I_B	50	mA
Collector power dissipation	P_C	100	mW
Junction temperature	T_j	125	°C
Storage temperature range	T_{stg}	-55 to 125	°C



Marking




Equivalent Circuit (top view)



961001EAA1

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

Electrical Characteristics (Ta = 25°C)

Characteristics		Symbol	Test Condition	Min	Typ.	Max	Unit
Collector cut-off current		I_{CBO}	$V_{CB} = 15 \text{ V}, I_E = 0$	—	—	0.1	μA
Emitter cut-off current		I_{EBO}	$V_{EB} = 5 \text{ V}, I_C = 0$	—	—	0.1	μA
DC current gain		h_{FE} (Note)	$V_{CE} = 2 \text{ V}, I_C = 10 \text{ mA}$	300	—	1000	
Collector-emitter saturation voltage		$V_{CE(sat)} (1)$	$I_C = 10 \text{ mA}, I_B = 0.5 \text{ mA}$	—	15	30	mV
		$V_{CE(sat)} (2)$	$I_C = 200 \text{ mA}, I_B = 10 \text{ mA}$	—	110	250	mV
Base-emitter voltage		$V_{BE(sat)}$	$I_C = 200 \text{ mA}, I_B = 10 \text{ mA}$	—	0.87	1.2	V
Transition frequency		f_T	$V_{CE} = 2 \text{ V}, I_C = 10 \text{ mA}$	80	130	—	MHz
Collector output capacitance		C_{ob}	$V_{CB} = 10 \text{ V}, I_E = 0, f = 1 \text{ MHz}$	—	4.2	—	pF
Collector-emitter on resistance		R_{on}	$I_B = 1 \text{ mA}, V_{in} = 1 \text{ V}_{rms}, f = 1 \text{ kHz}$	—	0.9	—	Ω
Switching time	Turn-on time	t_{on}	 Duty Cycle $\leq 2\%$ $I_{B1} = -I_{B2} = 5 \text{ mA}$	—	85	—	ns
	Storage time	t_{stg}		—	170	—	ns
	Fall time	t_f		—	40	—	ns

Note: h_{FE} Classification A: 300 to 600, B: 500 to 1000

