

2SK1867

Silicon N-Channel Power F-MOS FET

■ Features

- Avalanche energy capacity guaranteed: $EAS > 15\text{mJ}$
- $V_{GSS} = \pm 30\text{V}$ guaranteed
- High-speed switching: $t_f = 26\text{ns}$
- No secondary breakdown
- Allowing to supply by the radial taping

■ Applications

- Contactless relay
- Diving circuit for a solenoid
- Driving circuit for a motor
- Control equipment
- Switching power supply


■ Absolute Maximum Ratings ($T_C = 25^\circ\text{C}$)










Parameter		Symbol	Rated	Unit
Drain to Source breakdown voltage		V_{DSS}	900	V
Gate to Source voltage		V_{GSS}	± 30	V
Drain current	DC	I_D	± 2	A
	Pulse	I_{DP}	± 6	A
Avalanche energy capacity		EAS^*	15	mJ
Allowable power dissipation	$T_C = 25^\circ\text{C}$	P_D	15	W
	$T_a = 25^\circ\text{C}$		2	
Channel temperature		T_{ch}	150	$^\circ\text{C}$
Storage temperature		T_{stg}	-55 to +150	$^\circ\text{C}$

* $L = 7.5\text{mH}$, $I_L = 2\text{A}$, $V_{DD} = 50\text{V}$, 1 pulse


■ Electrical Characteristics ($T_C = 25^\circ\text{C}$)

Parameter	Symbol	Conditions	min	typ	max	Unit	
Drain to Source cut-off current	I_{DSS}	$V_{DS} = 900\text{V}$, $V_{GS} = 0$			0.1	mA	
Gate to Source leakage current	I_{GSS}	$V_{GS} = \pm 30\text{V}$, $V_{DS} = 0$			± 1	μA	
Drain to Source breakdown voltage	V_{DSS}	$I_D = 1\text{mA}$, $V_{GS} = 0$	900			V	
Gate threshold voltage	V_{th}	$V_{DS} = 25\text{V}$, $I_D = 1\text{mA}$	1		5	V	
Drain to Source ON-resistance	$R_{DS(on)}$	$V_{GS} = 10\text{V}$, $I_D = 2\text{A}$		3.8	4.85	Ω	
Forward transfer admittance	$ Y_{fs} $	$V_{DS} = 25\text{V}$, $I_D = 2\text{A}$	1.5	2		S	
Diode forward voltage	V_{DSF}	$I_{DR} = 2\text{A}$, $V_{GS} = 0$			-1.6	V	
Input capacitance (Common Source)	C_{iss}	$V_{DS} = 20\text{V}$, $V_{GS} = 0$, $f = 1\text{MHz}$		730		pF	
Output capacitance (Common Source)	C_{oss}				90		pF
Reverse transfer capacitance (Common Source)	C_{rss}				40		pF
Turn-on time	t_{on}	$V_{GS} = 10\text{V}$, $I_D = 2\text{A}$ $V_{DD} = 200\text{V}$, $R_L = 100\Omega$		40		ns	
Fall time	t_f				35		ns
Turn-off time (delay time)	$t_{d(off)}$				105		ns
Thermal resistance between channel and case	$R_{th(ch-c)}$				8.33	$^\circ\text{C/W}$	







$V_{th} - T_C$



$V_{DS}, V_{GS} - Q_g$



Switching measurement circuit



Avalanche energy capacity test circuit

