

2SK2322 **L**, 2SK2322 **S**

Silicon N Channel MOS FET

Application

High speed power switching

Features

- Low on-resistance
- High speed switching
- Low drive current
- 2.5 V gate drive device can be driven from 3 V source
- Suitable for Switching regulator, DC – DC converter
- Avalanche ratings




Table 1 Absolute Maximum Ratings (Ta = 25°C)

Item	Symbol	Ratings	Unit
Drain to source voltage	V _{DSS}	60	V
Gate to source voltage	V _{GSS}	±20	V
Drain current	I _D	15	A
Drain peak current	I _{D(pulse)} *	60	A
Body-drain diode reverse drain current	I _{DR}	15	A
Avalanche current	I _{AP} ***	15	A
Avalanche energy	E _{AR} ***	19	mJ
Channel dissipation	P _{ch} **	50	W
Channel temperature	T _{ch}	150	°C
Storage temperature	T _{stg}	–55 to +150	°C

* PW ≤ 10 μs, duty cycle ≤ 1 %





** Value at T_c = 25 °C





*** Value at T_{ch} = 25 °C, R_g ≥ 50 Ω





Table 2 Electrical Characteristics (Ta = 25°C)



Item	Symbol	Min	Typ	Max	Unit	Test conditions
Drain to source breakdown voltage	$V_{(BR)DSS}$	60	—	—	V	$I_D = 10 \text{ mA}$, $V_{GS} = 0$
Gate to source breakdown voltage	$V_{(BR)GSS}$	± 20	—	—	V	$I_G = \pm 100 \text{ }\mu\text{A}$, $V_{DS} = 0$
Gate to source leak current	I_{GSS}	—	—	± 10	μA	$V_{GS} = \pm 16 \text{ V}$, $V_{DS} = 0$
Zero gate voltage drain current	I_{DSS}	—	—	250	μA	$V_{DS} = 50 \text{ V}$, $V_{GS} = 0$
Gate to source cutoff voltage	$V_{GS(off)}$	0.5	—	1.5	V	$I_D = 1 \text{ mA}$, $V_{DS} = 10 \text{ V}$
Static drain to source on state resistance	$R_{DS(on)}$	—	0.04	0.05	Ω	$I_D = 8 \text{ A}$ $V_{GS} = 10 \text{ V}^*$
		—	0.08	0.15	Ω	$I_D = 3 \text{ A}$ $V_{GS} = 2.5 \text{ V}^*$
Forward transfer admittance	$ y_{fs} $	8	14	—	S	$I_D = 8 \text{ A}$ $V_{DS} = 10 \text{ V}^*$
Input capacitance	C_{iss}	—	1600	—	pF	$V_{DS} = 10 \text{ V}$
Output capacitance	C_{oss}	—	680	—	pF	$V_{GS} = 0$
Reverse transfer capacitance	C_{rss}	—	120	—	pF	$f = 1 \text{ MHz}$
Turn-on delay time	$t_{d(on)}$	—	30	—	ns	$I_D = 8 \text{ A}$
Rise time	t_r	—	190	—	ns	$V_{GS} = 10 \text{ V}$
Turn-off delay time	$t_{d(off)}$	—	130	—	ns	$R_L = 3.75 \text{ }\Omega$
Fall time	t_f	—	120	—	ns	
Body-drain diode forward voltage	V_{DF}	—	1.0	—	V	$I_F = 15 \text{ A}$, $V_{GS} = 0$
Body-drain diode reverse recovery time	t_{rr}	—	85	—	ns	$I_F = 15 \text{ A}$, $V_{GS} = 0$, $diF / dt = 50 \text{ A} / \mu\text{s}$

* Pulse Test













Avalanche Test Circuit and Waveform





Switching Time Test Circuit



Waveform

