

# SHINDENGEN

## VZ Series Power MOSFET

N-Channel Enhancement type

**2SK2489**  
(F10S18VZ)

**180V 10A**


### FEATURES

- Input capacitance (Ciss) is small.  
Especially, input capacitance at 0 bias is small.
- The static Rds(on) is small.
- The switching time is fast.

### APPLICATION

- DC/DC converters
- Power supplies of DC 12-24V input
- Product related to  
Integrated Service Digital Network

### OUTLINE DIMENSIONS



### RATINGS

#### ● Absolute Maximum Ratings (T<sub>c</sub> = 25°C)


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	T <sub>stg</sub>		-55~150	°C
Channel Temperature	T <sub>ch</sub>		150	
Drain-Source Voltage	V <sub>DSS</sub>		180	V
Gate-Source Voltage	V <sub>GSS</sub>		±30	
Continuous Drain Current (DC)	I <sub>D</sub>		10	
Continuous Drain Current (Peak)	I <sub>DP</sub>		20	A
Continuous Source Current (DC)	I <sub>S</sub>		10	
Total Power Dissipation	P <sub>T</sub>		45	W
Single Pulse Avalanche Current	I <sub>AS</sub>	T <sub>ch</sub> = 25°C	10	A

●Electrical Characteristics  $T_c = 25^\circ\text{C}$


Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$I_D = 1\text{mA}, V_{GS} = 0\text{V}$	180			V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = 180\text{V}, V_{GS} = 0\text{V}$			250	$\mu\text{A}$
Gate-Source Leakage Current	$I_{GSS}$	$V_{GS} = \pm 30\text{V}, V_{DS} = 0\text{V}$			$\pm 0.1$	
Forward Transconductance	$g_{fs}$	$I_D = 5\text{A}, V_{DS} = 10\text{V}$	3.0	7.0		S
Static Drain-Source On-state Resistance	$R_{DS(ON)}$	$I_D = 5\text{A}, V_{GS} = 10\text{V}$		0.17	0.25	$\Omega$
Gate Threshold Voltage	$V_{TH}$	$I_D = 1\text{mA}, V_{DS} = 10\text{V}$	2.0	3.0	4.0	V
Source-Drain Diode Forward Voltage	$V_{SD}$	$I_S = 5\text{A}, V_{GS} = 0\text{V}$			1.5	
Thermal Resistance	$\theta_{jc}$	junction to case			2.77	$^\circ\text{C}/\text{W}$
Total Gate Charge	$Q_g$	$V_{DD} = 150\text{V}, V_{GS} = 10\text{V}, I_D = 10\text{A}$		25		nC
Input Capacitance	$C_{iss}$	$V_{DS} = 10\text{V}, V_{GS} = 0\text{V}, f = 1\text{MHz}$		720		pF
Reverse Transfer Capacitance	$C_{rss}$			80		
Output Capacitance	$C_{oss}$			280		
Turn-On Time	$t_{on}$	$I_D = 5\text{A}, V_{GS} = 10\text{V}, R_L = 20\Omega$		50	100	ns
Turn-Off Time	$t_{off}$			140	280	

# 2SK2489


## Transfer Characteristics




## 2SK2489 Static Drain-Source On-state Resistance



**2SK2489** Gate Threshold Voltage




# 2SK2489 Safe Operating Area




2SK2489

Transient Thermal Impedance




# 2SK2489

# Capacitance



2SK2489

Power Derating



## 2SK2489 Gate Charge Characteristics

