

2SK2708

External dimensions 1 FM20

Absolute Maximum Ratings (Ta = 25°C)

Symbol	Rated	Unit
V _{DSS}	600	V
V _{GSS}	±30	V
I _D	±7	A
I _D (pulse) *1	±28	A
P _D	40 (T _c = 25°C)	W
E _{AS} *2	150	mJ
I _{AS}	7	A
T _{ch}	150	°C
T _{stg}	-55 to +150	°C

*1: P_w ≤ 100μs, duty cycle ≤ 1%

*2: V_{DD} = 30V, L = 6mH, I_L = 7A, unclamped, R_G = 50Ω, See Figure 1 on Page 5.

Electrical Characteristics (Ta = 25°C)

Symbol	Ratings			Unit	Conditions
	min	typ	max		
V _{(BR) DSS}	600			V	I _D = 100μA, V _{GS} = 0V
I _{GSS}			±100	nA	V _{GS} = ±30V
I _{DSS}			100	μA	V _{DS} = 600V, V _{GS} = 0V
V _{TH}	2.0	3.0	4.0	V	V _{DS} = 10V, I _D = 1mA
R _e (yfs)	4.0	6.0		S	V _{DS} = 20V, I _D = 3.5A
R _{DS} (on)		0.85	1.1	Ω	V _{GS} = 10V, I _D = 3.5A
C _{iss}		950		pF	V _{DS} = 10V, f = 1.0MHz, V _{GS} = 0V
C _{oss}		220		pF	
C _{rss}		120		pF	
t _d (on)		30		ns	I _D = 3.5A, V _{DD} = 250V, R _L = 71Ω, V _{GS} = 10V, See Figure 2 on Page 5.
t _r		27		ns	
t _d (off)		100		ns	
t _f		50		ns	
V _{SD}		0.9	1.5	V	I _{SD} = 7A, V _{GS} = 0V

