

# SPECIFICATION

(TENTATIVE)

DEVICE NAME : Power MOSFET

TYPE NAME : 2SK2755-01

SPEC. No. :

Fuji Electric Co.,Ltd.

This Specification is subject to change without notice.

	DATE	NAME	APPROVED	Fuji Electric Co.,Ltd.	
DRAWN				DWG.NO.	1/12
CHECKED					

1. Scope  
This specifies Fuji power MOSFET 2SK2755-01
2. Construction N-channel enhancement mode power MOSFET
3. Application for switching
4. Outview T0-3P Outview See to 5/12 page
5. Absolute maximum ratings at  $T_c=25^\circ\text{C}$  (unless otherwise specified)

Description	Symbol	Characteristics	Unit	Remarks
Drain-source voltage	$V_{DS}$	450	V	
Continuous Drain current	$I_D$	$\pm 18$	A	
Pulsed drain current	$I_{Dpulsec}$	$\pm 72$	A	
Gate-source voltage	$V_{GS}$	$\pm 30$	V	
Repetitive or non-repetitive	$I_{AR}$	18	A	$T_{ch} \leq 150^\circ\text{C}$
Avalanche energy	$E_{AS}$	185	mJ	See page 12/12 ※
Maximum power dissipation	$P_D$	125	W	
Operating and storage temperature range	$T_{ch}$ $T_{stg}$	150 -55 ~ +150	$^\circ\text{C}$ $^\circ\text{C}$	

※  $L=1.05\text{mH}$ ,  $V_{CC}=45\text{V}$

6. Electrical characteristics at  $T_c=25^\circ\text{C}$  (unless otherwise specified)
- Static ratings

Description	Symbol	Conditions	Characteristics			Unit
			Min.	Typ.	Max.	
Drain-source breakdown voltage	$B V_{DSS}$	$I_D = 1\text{mA}$ $V_{GS} = 0\text{V}$	450			V
Gate threshold voltage	$V_{GS(th)}$	$I_D = 1\text{mA}$ $V_{DS} = V_{GS}$	3.5	4.0	4.5	V
Zero gate voltage drain current	$I_{DSS}$	$V_{DS} = 450\text{V}$ $V_{GS} = 0\text{V}$	$T_{ch} = 25^\circ\text{C}$	10	500	$\mu\text{A}$
	$I_{DSS}$		$T_{ch} = 125^\circ\text{C}$	0.2	1.0	mA
Gate-source leakage current	$I_{GSS}$	$V_{GS} = \pm 30\text{V}$ $V_{DS} = 0\text{V}$		10	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	$I_D = 9\text{A}$ $V_{GS} = 10\text{V}$		0.40	0.45	$\Omega$

Fuji Electric Co., Ltd.

DWG.NO.

2/12

Y 0257-R-003a

Dynamic ratings

Description	Symbol	Conditions	Characteristics			Unit
			Min.	Typ.	Max.	
Forward transconductance	$g_{fs}$	$I_D = 9\text{ A}$ $V_{DS} = 25\text{ V}$	4.5	9.0		S
Input capacitance	$C_{iss}$	$V_{DS} = 25\text{ V}$ $V_{GS} = 0\text{ V}$ $f = 1\text{ MHz}$		1400	2100	pF
Output capacitance	$C_{oss}$			250	380	pF
Reverse transfer capacitance	$C_{rss}$			110	170	pF
Turn-on time	$t_{d(on)}$	$V_{CC} = 300\text{ V}$ $V_{GS} = 10\text{ V}$ $I_D = 18\text{ A}$ $R_{CS} = 10\ \Omega$		30	50	ns
	$t_r$			140	210	ns
Turn-off time	$t_{d(off)}$			80	120	ns
	$t_f$			60	90	ns

Reverse diode

Description	Symbol	Conditions	Characteristics			Unit
			Min.	Typ.	Max.	
Avalanche capability	$I_{AV}$	$L = 100\ \mu\text{H}$ , $T_{ch} = 25^\circ\text{C}$ * See Fig1 and 2	18			A
Diode forward on-voltage	$V_{SD}$	$I_F = 2 \times I_{DR}$ $V_{GS} = 0\text{ V}$ , $T_{ch} = 25^\circ\text{C}$		1.1	1.65	V
Reverse recovery time	$t_{rr}$	$I_F = I_{DR}$ $V_{GS} = 0\text{ V}$ $-di_F/dt = 100\text{ A}/\mu\text{s}$		500		ns
Reverse recovery charge	$Q_{rr}$	$T_{ch} = 25^\circ\text{C}$		6.5		$\mu\text{C}$

7. Thermal resistance

Description	Symbol	Conditions	Characteristics			Unit
			Min.	Typ.	Max.	
Thermal resistance	$R_{th_{ch-c}}$				1.0	$^\circ\text{C}/\text{W}$
	$R_{th_{ch-a}}$				35.0	$^\circ\text{C}/\text{W}$

Fuji Electric Co.,Ltd.

DWG.NO.

3/12

Y 0257-R-003a

Fig.1 Test circuit







Fig.2 Operating waveforms




FUJI POWER MOS FET

TYPE : 2SK2755-01



DIMENSIONS ARE IN MILLIMETERS.



CONNECTION

- ① GATE
- ② DRAIN
- ③ SOURCE

Note: 1. Guaranteed mark of avalanche ruggedness.


JEDEC : TO-247  
EIAJ : SC-65

Fuji Electric Co.,Ltd.


DWG. NO.

5/12


Power Dissipation  
 $PD=f(T_c)$




Safe operating area  
 $ID=f(V_{DS}) : D=0.01, T_c=25^\circ C$




Typical output characteristics  
 $I_D = f(V_{DS}) : 80 \mu s$  pulse test,  $T_c = 25^\circ C$




Typical transfer characteristic  
 $I_D = f(V_{GS}) : 80 \mu s$  pulse test,  $V_{DS} = 25V$ ,  $T_{ch} = 25^\circ C$




Typical forward transconductance  
 $g_{fs}=f(I_D)$ : 80  $\mu$ s pulse test,  $V_{DS}=25V$ ,  $T_{ch}=25^\circ C$




Typical drain-source on-state resistance  
 $R_{DS(on)}=f(I_D)$ : 80  $\mu$ s pulse test,  $T_c=25^\circ C$




Drain-source on-state resistance  
 $R_{DS(on)} = f(T_{ch}) : I_D = 9A, V_{GS} = 10V$




Gate threshold voltage  
 $V_{GS(th)} = f(T_{ch}) : I_D = 1mA, V_{DS} = V_{GS}$




Typical gate charge characteristic  
 $V_{GS} = f(Q_g) : I_D = 18A, T_c = 25^\circ C$




Typical capacitances  
 $C = f(V_{DS}) : V_{GS} = 0V, f = 1MHz$



Forward characteristic of reverse of diode  
 $I_F = f(V_{SD}) : 80 \mu s$  pulses test,  $V_{GS} = 0V$



Transient thermal impedande  
 $Z_{thch-c} = f(t)$  parameter:  $D = t/T$



Avalanche energy derating  
 $E_{as} = f(\text{starting } T_{ch}) : V_{CC} = 45V, I_{AV} = 18A$

