

6367254 MOTOROLA SC (XSTRS/R F)

96D-80721 D

T-33-13

MOTOROLA SEMICONDUCTOR TECHNICAL DATA

**BUS47
BUS47A**


**SWITCHMODE II^A SERIES
NPN SILICON POWER TRANSISTORS**

The BUS 47 and BUS 47A transistors are designed for high-voltage, high-speed, power switching in inductive circuits where fall time is critical. They are particularly suited for line-operated switch-mode applications such as:

- Switching Regulators
- Inverters
- Solenoid and Relay Drivers
- Motor Controls
- Deflection Circuits

Fast Turn-Off Times

60 ns Inductive Fall Time—25°C (Typ)
120 ns Inductive Crossover Time—25°C (Typ)




Operating Temperature Range -65 to +200°C
100°C Performance Specified for:
Reverse-Biased SOA with Inductive Loads
Switching Times with Inductive Loads
Saturation Voltages
Leakage Currents (125°C)

**9 AMPERES
NPN SILICON
POWER TRANSISTORS**
400 AND 450 VOLTS (BVCEO)
150 WATTS
850 - 1000 V (BVCE5)

**Designer's Data for
"Worst Case" Conditions**

The Designer's Data Sheet permits the design of most circuits entirely from the information presented. Limit data - representing device characteristics boundaries - are given to facilitate "worst case" design.




MAXIMUM RATINGS

Rating	Symbol	BUS 47	BUS 47A	Unit
Collector-Emitter Voltage	V _{CEO(sus)}	450	450	V _{dc}
Collector-Emitter Voltage	V _{CEV}	850	1000	V _{dc}
Emitter Base Voltage	V _{EB}	7		V _{dc}
Collector Current - Continuous	I _C	9		A _{dc}
Collector Current - Peak (1)	I _{CM}	18		
Collector Current - Overload	I _{OL}	36		
Base Current - Continuous	I _B	5		A _{dc}
Base Current - Peak (1)	I _{BM}	10		
Total Power Dissipation - T _C = 25°C	P _D	150		Watts
Derate above 25°C - T _C = 100°C		85.5		W/°C
Operating and Storage Junction Temperature Range	T _J , T _{stg}	-65 to +200		°C

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Case	R _{θJC}	1.17	°C/W
Maximum Lead Temperature for Soldering Purposes: 1/8" from Case for 5 Seconds	T _L	275	°C

(1) Pulse Test: Pulse Width = 5 ms, Duty Cycle ≤ 10%.



NOTES
1 DIMENSIONS Q AND V ARE DATUMS
2 [] IS SEATING PLANE AND DATUM
3 POSITIONAL TOLERANCE FOR MOUNTING HOLE Q
4 DIMENSIONS AND TOLERANCES PER AND Y14.5, 1975

MILLIMETERS		INCHES	
MIN	MAX	MIN	MAX
A	1.537	0.060	0.061
B	2.106	0.083	0.084
C	0.31	0.012	0.013
D	0.97	0.038	0.039
E	1.40	0.055	0.056
F	30.15 BSC	1.187 BSC	
G	10.92 BSC	0.430 BSC	
H	5.48 BSC	0.215 BSC	
J	18.25 BSC	0.718 BSC	
K	11.91	0.469	0.470
L	2.81	0.110	0.111
M	2.81	0.110	0.111
N	2.81	0.110	0.111
O	4.83	0.190	0.191
V	3.81	0.150	0.151

CASE 1-05 TO-3 TYPE

BUS47, BUS47A

T-33-13

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS (1)					
Collector-Emitter Sustaining Voltage (Table 1) (I _C = 200 mA, I _B = 0) L = 25 mH	BUS47 BUS47A V _{CEO(sus)}	400 450	-	-	V _{dc}
Collector Cutoff Current (V _{CEV} = Rated Value, V _{BE(off)} = 1.5 V _{dc}) (V _{CEV} = Rated Value, V _{BE(off)} = 1.5 V _{dc} , T _C = 125°C)	I _{CEV}	-	-	0.15 1.5	mAdc
Collector Cutoff Current (V _{CE} = Rated V _{CEV} , R _{BE} = 10 Ω)	T _C = 25°C T _C = 125°C I _{CER}	-	-	0.4 3.0	mAdc
Emitter Cutoff Current (V _{EB} = 5 V _{dc} , I _C = 0)	I _{EBO}	-	-	0.1	mAdc
Emitter-base breakdown Voltage (I _E = 50 mA - I _C = 0)	BVEBO	7.0	-	-	V _{dc}

SECOND BREAKDOWN

Second Breakdown Collector Current with Base Forward Biased	I _{S/b}	See Figure 12	
Clamped Inductive SOA with Base Reverse Biased	RBSOA	See Figure 13	

ON CHARACTERISTICS (1)

DC Current Gain (I _C = 6 Adc, V _{CE} = 5 V _{dc}) (I _C = 5 Adc, V _{CE} = 5 V)	BUS47 BUS47A h _{FE}	7	-	-	
Collector-Emitter Saturation Voltage (I _C = 6 Adc, I _B = 1.2 Adc) (I _C = 9 Adc, I _B = 1.8 Adc) (I _C = 6 Adc, I _B = 1.2 Adc, T _C = 100°C) (I _C = 5 Adc, I _B = 1 Adc) (I _C = 8 Adc, I _B = 1.8 Adc) (I _C = 5 Adc, I _B = 1 Adc, T _C = 100°C)	BUS47 BUS47A V _{CE(sat)}	-	-	1.5 5.0 2.5 1.5 5.0 2.5	V _{dc}
Base-Emitter Saturation Voltage (I _C = 6 Adc, I _B = 1.2 Adc) (I _C = 6 Adc, I _B = 1.2 Adc, T _C = 100°C) (I _C = 5 Adc, I _B = 1 Adc) (I _C = 5 Adc, I _B = 1 Adc, T _C = 100°C)	BUS47 BUS47A V _{BE(sat)}	-	-	1.6 1.6 1.6 1.6	V _{dc}

DYNAMIC CHARACTERISTICS

Output Capacitance (V _{CB} = 10 V _{dc} , I _E = 0, f _{test} = 100 KHz)	C _{ob}	-	-	300	pF
--	-----------------	---	---	-----	----

SWITCHING CHARACTERISTICS

Resistive Load (Table 1)

Delay Time	(V _{CC} = 250 V _{dc} , I _C = 6 A, I _{B1} = 1.2 A, t _D = 30 μs, Duty Cycle 2, V _{BE(off)} = 5 V)	t _d	-	0.05	0.2	μs
Rise Time		t _r	-	0.5	0.8	
Storage Time		t _s	-	1	2.0	
Fall Time		t _f	-	0.2	0.4	

Inductive Load, Clamped (Table 1)

Storage Time	(I _{C(pk)} = 6 A, I _{B1} = 1.2 A, V _{BE(off)} = 5 V, V _{CE(c1)} = 250 V)	BUS47	(T _C = 25°C)	t _{sv}	-	0.9	-	μs
Fall Time				t _{fi}	-	0.06	-	
Storage Time	(I _{C(pk)} = 5 A, I _{B1} = 1 A)	BUS47A	(T _C = 100°C)	t _{sv}	-	1.0	2.5	
Crossover Time				t _c	-	0.2	0.5	
Fall Time				t _{fi}	-	0.1	0.3	

(1) Pulse Test: PW = 300 μs, Duty Cycle ≤ 2%.