

DIODE MODULE

DWF(R)40A30/40

TOP





DWF(R)40A is a non-isolated diode module designed for 3 phase rectification.

- $I_{F(AV)}=40A$, $V_{RRM}=400V$
- Easy Construction with Joint-Cathode (F) Type and Joint-Anode (R) type.
- Non-isolated. (Mounting Base as terminals.)
- High Surge Capability

(Applications)

Welding Power Supply
3 Phase Rectifier



Maximum Ratings

($T_j=25^{\circ}C$ unless otherwise specified)

Symbol	Item	Ratings		Unit
		DWF(R)40A30	DWF(R)40A40	
V_{RRM}	Repetitive Peak Reverse Voltage	300	400	V
V_{RSM}	Non-Repetitive Peak Reverse Voltage	360	480	V
$V_{R(DC)}$	D.C. Reverse Voltage	240	320	V

Symbol	Item		Conditions	Ratings	Unit
$I_{F(AV)}$	Average Forward Current		Single phase, half wave, 180° conduction, $T_c: 122^{\circ}C$	40	A
$I_{F(RMS)}$	R.M.S. Forward Current		Single phase, half wave, 180° conduction, $T_c: 122^{\circ}C$	62	A
I_{FSM}	Surge Forward Current		$\frac{1}{2}$ cycle, 60Hz, peak value, non-repetitive	800	A
I^2t	I^2t		Value for one cycle of surge current	2700	A^2S
T_j	Operating Junction Temperature			-30 to $+150$	$^{\circ}C$
T_{stg}	Storage Temperature			-30 to $+125$	$^{\circ}C$
	Mounting Torque	Mounting (M5)	Recommended Value 1.5-2.5 (15-25)	2.7 (28)	$N \cdot m$ ($kgf \cdot cm$)
		Terminal (M5)	Recommended Value 1.5-2.5 (15-25)	2.7 (28)	
	Mass			170	g

Electrical Characteristics

Symbol	Item		Conditions	Ratings	Unit
I_{RRM}	Repetitive Peak Reverse Current, max.		at V_{DRM} , single phase, half wave, $T_j=150^{\circ}C$	8	mA
V_{FM}	Forward Voltage Drop, max.		Forward current 120A, $T_j=25^{\circ}C$, Inst. measurement	1.15	V
$R_{th(j-c)}$	Thermal Impedance, max.		Junction to case	0.60	$^{\circ}C/W$

