

Ultra Fast Recovery Diodes $V_{RM}: 100 \sim 600V$ $I_o: 5.0 \sim 20A$


FMG/FML

Rating/ Characteristics	Absolute Maximum Ratings						Electrical Characteristics (Ta = 25°C)						Others											
	V _{RSM} (V)	V _{RM} (V)	I _o (A)	I _{FSM} (A)	T _j (°C)	T _{stg} (°C)	V _F (V)	I _R (mA)	I _{R(H)} (mA)	t _{rr} (μs)	I _F /I _{RP} (mA)	Outline Drawing	Weight(g)	Taping	Note									
Type No.	per chip		With Fin	50Hz Sine Half Wave Single Pulse 10ms.			Max. per chip	I _F (A)	V _R = V _{RM} max (per chip)	V _R = V _{RM} , T _j = 150°C max (per chip)														
FMG-11S, R	100	100	5.0	35	-40 ~ +150		1.3	2.5	1.5	0.1	100/100	62	2.1		For High Frequency Rectification									
FMG-12S, R	200	200					1.8																	
FMG-13S, R	300	300					2.0																	
FMG-14S, R	400	400					1.3	5.0	2.5															
FMG-21S, R	100	100	10	65			1.8		62			2.1												
FMG-22S, R	200	200					2.0																	
FMG-23S, R	300	300					2.2	3.0								3.0								
FMG-24S, R	400	400	8.0				1.3																	
FMG-26S, R	600	600	6.0	50			1.8	10	5.0			63	5.5											
FMG-31S, R	100	100	20	150			2.0																	
FMG-32S, R	200	200					2.2																	
FMG-33S, R	300	300					2.5	0.5	3.0			64	2.1											
FMG-34S, R	400	400	16	100			0.98																	
FMG-36S, R	600	600	15	80			1.3					65	5.5											
FMG-G26S	600	600	4.0	50			1.8																	
FMG-G36S	600	600	8.0	80			2.0																	
FML-11S	100	100	5.0	35			0.98	2.5	0.15	0.5	0.04	62	2.1											
FML-12S	200	200					1.3																	
FML-13S	300	300		40			0.98		0.25	1.0	0.04													
FML-14S	400	400					1.3																	
FML-21S	100	100	10	65			0.98	5.0				63	5.5											
FML-22S	200	200					1.3																	
FML-23S	300	300		70			0.98	0.6	2.0	0.04														
FML-24S	400	400					1.3																	
FML-31S	100	100	20	150			0.98			10						64	2.1							
FML-32S	200	200					1.3																	
FML-33S	300	300		100			0.98			0.2	1.0	0.05												
FML-34S	400	400					1.3																	
FML-G12S	200	200	5.0	65			0.98	5.0				65	5.5											
FML-G13S	300	300					1.3																	
FML-G14S	400	400					1.5																	
FML-G16S	600	600					0.98																	
FML-G22S	200	200	10	150			0.98	10	0.5	2.0	0.04	64	2.1											


Thermal Resistance R_{th(j-c)} max: 4.2°C/W (FMG-G26S)

2.1°C/W (FMG-G36S)


Outline Drawing 62




Outline Drawing 63




Outline Drawing 64



Outline Drawing 65



62 ~ 65 Plastic Molded, Flammability: UL94V-0 or Equivalent




Taping Specifications

Designation	Dimension (in mm)	Packaging Dimension and Marking	Quantity
V1 Add Suffix [V1] to Type No.	Axial Taping 	Ammunition Pack 	2,000 pcs per box (2.7 ϕ body) 1,000 pcs per box (4.0 ϕ body)
VO Add Suffix [VO] to Type No.	Axial Taping 	Ammunition Pack 	2,000 pcs per box (2.7 ϕ body) (2.4 ϕ body)
V3 Add Suffix [V3] to Type No.	Axial Taping 	Reel 	1,500 pcs per reel (5.2 ϕ body)
V4 Add Suffix [V4] to Type No.	Axial Taping 	Ammunition Pack 	1,000 pcs per box (5.2 ϕ body)
W Add Suffix [W] to Type No.	Radial Taping 	Ammunition Pack 	4,000 pcs per box (2.7 ϕ body) (0.6 ϕ lead)
WS Add Suffix [WS] to Type No.	Radial Taping (Applicable to AO Series) 	Ammunition Pack 	2,500 pcs per box (2.4 ϕ body)
WK Add Suffix [WK] to Type No.	Radial Taping (Applicable to AO Series) 		


Marking Guide

1 Small TMD




- ① Type Designation (in abbreviation)
AM01 is abbreviated as M.
- ② Class Designation
Z: 200V, No Letter: 400V, A: 600V
- ③ A: Year (Last Number of AD Year)
B: Month (Jan. to Sept. are represented by numbers 1 to 9 respectively, and Oct., Nov., and Dec. are abbreviated as O, N and D respectively)
- ④ Cathode Band: Successive Band, however AU02 Type is Non-Successive Band.

2 E/EO Type TMD



- ① Type Designation (in abbreviation)
EM01 is abbreviated as MO, EM2 is abbreviated as M2.
- ② Class Designation
Z: 200V, No Letter: 400V, A: 600V
B: 800 V, C: 1000V, F: 1500V
However, EU02A to be marked 2A, and EU2YX to be marked Y.
- ③ Abbreviations Representing Production Period
A: Year (Last Number of AD Year)
B: Month (1~9, O, N, D)
- ④ Production Period Divided in 3 ten day terms
• : 1st 10days •• : 2nd 10days ••• : 3rd 10days


3 R Type TMD



- ① Type Designation: Mark in 2 sets
- ② Production Period: Mark in 4 sets
A: Year (Last Number of AD Year)
B: Month (1~9, O, N, D)
- ③ Production Period Divided in 3 ten day terms
• : 1st 10days •• : 2nd 10days ••• : 3rd 10days
- ④ Cathode Band Color: Silver: For Power Supply
Yellow: For Middle Speed
Red : For High Speed and Ultra-High Speed


4 RB40/60

(RB40 Series)




- ① Peak Reverse Voltage Designation
1, 2, 4, 6, C
Production Period
- ② Year (Last Number of AD Year)
- ③ Month (1~9, O, N, D)
- ④ Divided in 3 ten day terms
A: 1st 10days, B: 2nd 10days
C: 3rd 10days
Color Designation: Silver

(RB60 Series)




Dot Designation RB601 Violet
RB602 No Color
RB604 Blue
RB606 White

5 RBV/RBA




- ① Type Designation
- ② Lot Number
1st : Year (Last Number of AD Year)
2nd: Month (1~9, O, N, D)
3rd : Divided 1~3 ten day Terms
A: 1st 10 days B: 2nd 10 days
C: 3rd 10 days
- ③ In-Put Designation

6 TO220 Type (FM or CT Type)




- ① Type Designation
Show FMU-12S as FMU12S.
- ② Polarity: Rectifier Symbols
- ③ Lot Number (Laser Marking)
1st : Year (Last Number of AD Year)
2nd : Month (0~9, O, N, D)
3rd, 4th: Day

7 TO220 Type (FM or CT Type, single chip)




- ① Type Designation: Omit Last Letter
Show FML-G12S as FMLG12.
- ② Last Letter of Type Designation
- ③ Polarity: Rectifier Symbols
- ④ Lot Number (Laser Marking)
1st : Year (Last Number of AD Year)
2nd : Month (0~9, O, N, D)
3rd, 4th: Day

8 TO3P Type (FM or CT Type)




- ① Type shown in full designation
However, CTB-34/34S/34M are marked as CTB-34, CTU-G3DR is marked as CTUG3DR.
- ② Polarity: Rectifier Symbols
- ③ Lot Number:
1) M, U, G and L Types
First Number : Last Digit of AD Year
Second Number : Month
Third and Fourth Numbers: Day
Fifth Number : None
2) For types CTB-34/34S/34M, the fifth letter shows type designation. If no fifth number, the type is CTB-33 or CTB-34.
3) Marking Color: Silver

9 MI-10/15 Type



- ① MI-10/15 is die-stamped on the top of the case.
- ② Rectifier Symbols
- ③ Lot Number:
First Number : Peak Reverse Voltage:
(Letter) 0=50V, 1=100V, 2=200V,
4=400V, 6=600V, C=1000V
Second Number : Last Digit of AD Year
Third Number : Month
Fourth and Fifth Numbers: Day
Sixth Number : Production number and
U: Voltage Doubler Type

10 SFP Type



- ① Type Designation:
SFPB-64 is abbreviated at B64.
- ② Cathode Band