


SHINDENGEN

Sidac

K1V22(W)

OUTLINE DIMENSIONS



RATINGS

● Absolute Maximum Ratings

| Item | Symbol | Conditions | Ratings | Unit |
|---|-----------|--|---------|------------------|
| Storage Temperature | T_{stg} | | -40~125 | °C |
| Operating Junction Temperature | T_j | | 125 | °C |
| Maximum Off-state Voltage | V_{DRM} | | 180 | V |
| RMS On-state Current | I_T | $T_l = 91^{\circ}\text{C}$, 50Hz sine wave ($\theta = 180^{\circ}$) | 1 | A |
| Surge On-state Current | I_{TSM} | $T_j = 25^{\circ}\text{C}$, 50Hz sine wave ($\theta = 180^{\circ}$), non-repetitive 1-cycle peak value | 16 | A |
| Pulse On-state Current | I_{TRM} | $T_a = 25^{\circ}\text{C}$, pulse width $t_o = 10 \mu\text{s}$, sine wave, repetitive peak value $f = 1 \text{ kHz}$ | 17 | A |
| | | $T_a = 25^{\circ}\text{C}$, pulse width $t_o = 10 \mu\text{s}$, sine wave, repetitive peak value $f = 60 \text{ Hz}$ | 50 | |
| Critical Rate of Rise of On-state Current | di_T/dt | | 80 | A/ μs |


● Electrical Characteristics ($T_l=25^{\circ}\text{C}$)

| Item | Symbol | Conditions | Ratings | Unit |
|----------------------|---------------|----------------------------|---------|---------------|
| Breakover Voltage | V_{BO} | $I_B = 0$, 50Hz sine wave | 200~230 | V |
| Off-state Current | I_{DRM} | $V_D = V_{DRM}$ | Max 10 | μA |
| Breakover Current | I_{BO} | | Max 0.5 | mA |
| Holding Current | I_H | | TYP 50 | mA |
| On-state Voltage | V_T | $I_T = 1\text{A}$ | Max 3.0 | V |
| Switching Resistance | R_S | | Min 0.1 | k Ω |
| Thermal Resistance | θ_{jl} | Junction to lead | Max 15 | °C/W |

● Standard Design with P.C.B.

| Item | Symbol | Conditions | Standard | Unit |
|----------------------|--------|---|----------|------|
| RMS On-state Current | I_T | Assembled in P.C.B., $T_a = 25^{\circ}\text{C}$, soldering land 3mm ϕ | 0.55 | A |

K1V22(W)
K1V24(W)
K1V26(W) Typical On-State Voltage




K1V22(W)

K1V24(W)

K1V26(W)

Power Dissipation




K1V22(W)

K1V24(W)

K1V26(W)

Maximum Lead Temperature




K1V22(W)

K1V24(W)

K1V26(W)

Maximum Ambient Temperature




K1V22(W)

K1V24(W)


K1V26(W)

Maximum Surge On-State Current



K1V22(W)
K1V24(W)
K1V26(W)

Pulse On-State Current Rating




K1V22(W)

K1V24(W)


K1V26(W)

Pulse On-State Current Derating




K1V22(W)
K1V24(W)
K1V26(W)

Transient Thermal Resistance



K1V22(W)
K1V24(W)
K1V26(W)

Breakover Voltage - Junction Temperature



This datasheet has been downloaded from:

www.DatasheetCatalog.com

Datasheets for electronic components.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.