


# SHINDENGEN

Sidac

**K1V5**

## OUTLINE DIMENSIONS



## RATINGS

### ● Absolute Maximum Ratings

Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	$T_{stg}$		-40~125	°C
Operating Junction Temperature	$T_j$		125	°C
Maximum Off-state Voltage	$V_{DRM}$		40	V
RMS On-state Current	$I_T$	$T_l = 107^\circ\text{C}$ , 50Hz sine wave ( $\theta = 180^\circ$ )	1	A
Surge On-state Current	$I_{TSM}$	$T_j = 25^\circ\text{C}$ , 50Hz sine wave ( $\theta = 180^\circ$ ), non-repetitive 1-cycle peak value	13	A
Pulse On-state Current	$I_{TRM}$	$T_a = 25^\circ\text{C}$ , pulse width $t_o = 10 \mu\text{s}$ , sine wave, repetitive peak value $f = 1 \text{ kHz}$	25	A
		$T_a = 25^\circ\text{C}$ , pulse width $t_o = 10 \mu\text{s}$ , sine wave, repetitive peak value $f = 60 \text{ Hz}$	80	
Critical Rate of Rise of On-state Current	$di_T/dt$		80	A/ $\mu\text{s}$

### ● Electrical Characteristics ( $T_l=25^\circ\text{C}$ )


Item	Symbol	Conditions	Ratings	Unit
Breakover Voltage	$V_{BO}$	$I_B = 0$ , 50Hz sine wave	45~60	V
Off-state Current	$I_{DRM}$	$V_D = V_{DRM}$	Max 10	$\mu\text{A}$
Breakover Current	$I_{BO}$		Max 0.5	mA
Holding Current	$I_H$		TYP 50	mA
On-state Voltage	$V_T$	$I_T = 1\text{A}$	Max 1.5	V
Switching Resistance	$R_S$		Min 0.1	k $\Omega$
Thermal Resistance	$\theta_{jl}$	Junction to lead	Max 15	°C/W

### ● Standard Design with P.C.B.

Item	Symbol	Conditions	Standard	Unit
RMS On-state Current	$I_T$	Assembled in P.C.B., $T_a = 25^\circ\text{C}$ , soldering land $3\text{mm } \phi$	0.96	A


K1V5  
K1V6

Typical On-State Voltage




K1V5  
K1V6

Power Dissipation




K1V5  
K1V6

Maximum Lead Temperature




K1V5  
K1V6

Maximum Ambient Temperature




K1V5  
K1V6

Maximum Surge On-State Current




K1V5  
K1V6

Pulse On-State Current Rating



K1V5  
K1V6


Pulse On-State Current Derating



K1V5

K1V6

Transient Thermal Resistance



K1V5

K1V6

Breakover Voltage - Junction Temperature

