


**8 BIT BINARY COUNTER WITH INPUT REGISTER (3-STATE)**

- HIGH SPEED  
f<sub>MAX</sub> = 80 MHz (TYP.) AT V<sub>CC</sub> = 5 V
- LOW POWER DISSIPATION  
I<sub>CC</sub> = 4 μA (MAX.) AT T<sub>A</sub> = 25 °C
- OUTPUT DRIVE CAPABILITY  
10 LSTTL LOADS FOR RCO  
15 LSTTL LOADS FOR Q<sub>n</sub>
- BALANCED PROPAGATION DELAYS  
t<sub>PLH</sub> = t<sub>PHL</sub>
- SYMMETRICAL OUTPUT IMPEDANCE  
I<sub>OL</sub> = |I<sub>OH</sub>| = 6 mA (MIN.) for Q<sub>n</sub>  
I<sub>OL</sub> = |I<sub>OH</sub>| = 4 mA (MIN.) for RCO
- HIGH NOISE IMMUNITY  
V<sub>NIH</sub> = V<sub>NIL</sub> = 28 % V<sub>CC</sub> (MIN.)
- WIDE OPERATING VOLTAGE RANGE  
V<sub>CC</sub> (OPR) = 2 V TO 6 V
- PIN AND FUNCTION COMPATIBLE  
WITH 54/74LS593



**DESCRIPTION**



The M54/74HC593 is a high speed CMOS 8 BIT REGISTER COUNTER (3 STATE) fabricated with silicon gate C<sup>2</sup>MOS technology. It has the same high speed performance of LSTTL combined with true CMOS low power consumption.

The M54/74HC593 consists of a parallel input, 8 bit storage register feeding an 8 bit binary counter. Both the register and the counter have individual positive edge-triggered clock. In addition, the counter has direct load and clear functions. Expansion is easily accomplished by connecting RCO of first stage to the count enable CCKEN, of the second stage etc.

The M54/74HC593 comes in a 20 pin package and has 3 state I/O, which provides parallel counter outputs.

All inputs are equipped with protection circuits against static discharge and transient excess voltage.

**PIN CONNECTIONS (top view)**



NC =  
No Internal  
Connection

INPUT AND OUTPUT EQUIVALENT CIRCUIT



TRUTH TABLE


| INPUTS |                |                   |       |                    |              |                    |                    |              | FUNCTION   |
|--------|----------------|-------------------|-------|--------------------|--------------|--------------------|--------------------|--------------|--|
| G      | $\overline{G}$ | $\overline{CCLR}$ | CCKEN | $\overline{CCKEN}$ | CCK          | $\overline{CLOAD}$ | $\overline{RCKEN}$ | RCK          |  |
| L      | H              | X                 | X     | X                  | X            | X                  | X                  | X            | ALL Q BUS BECOME HIGH Z AND CAN BE APPLIED ANY DATA    |
| H      | X              | X                 | X     | X                  | X            | X                  | X                  | X            | THE OUTPUT DATA OF THE COUNTER IS ENABLE ON QA THRU QH |
| X      | L              | X                 | X     | X                  | X            | X                  | X                  | X            |  |
| X      | X              | L                 | X     | X                  | X            | H                  | X                  | X            | COUNTER IS CLEARED TO ZERO                             |
| X      | X              | H                 | X     | X                  | X            | L                  | X                  | X            | THE DATA OF Q BUS IS LOADED INTO COUNTER               |
| X      | X              | H                 | H     | X                  | $\uparrow$   | H                  | X                  | X            | COUNTER ADVANCES THE COUNT                             |
| X      | X              | H                 | X     | L                  | $\uparrow$   | H                  | X                  | X            |  |
| X      | X              | H                 | H     | X                  | $\downarrow$ | H                  | X                  | X            | NO COUNT   |
| X      | X              | H                 | X     | L                  | $\downarrow$ | H                  | X                  | X            |  |
| X      | X              | H                 | L     | H                  | X            | H                  | X                  | X            | NO COUNT   |
| X      | X              | X                 | X     | X                  | X            | X                  | H                  | X            | REGISTER DATA IS NOT CHANGED                           |
| X      | X              | X                 | X     | X                  | X            | X                  | L                  | $\downarrow$ | REGISTER DATA IS NOT CHANGED                           |
| X      | X              | X                 | X     | X                  | X            | X                  | L                  | $\uparrow$   | THE DATA OF Q BUS IS STORED INTO REGISTER              |

X: Don't Care

$$RCO = QA' \cdot QB' \cdot QC' \cdot QD' \cdot QE' \cdot QF' \cdot QG' \cdot QH'$$

(QA' to QH': Internal outputs of the counter)

LOGIC DIAGRAM




# M54/M74HC593

## PIN DESCRIPTION

| PIN No                    | SYMBOL                               | NAME AND FUNCTION           |
|---------------------------|--------------------------------------|-----------------------------|
| 1, 2, 3, 4,<br>5, 6, 7, 8 | A/QA to<br>H/QH                      | Binary Outputs              |
| 9                         | $\overline{\text{CLOAD}}$            | Counter Clock Load Input    |
| 11                        | $\overline{\text{RCO}}$              | Ripple Carry Output         |
| 12                        | $\overline{\text{CCLR}}$             | Counter Clear Input         |
| 13                        | CCK                                  | Counter Clock Input         |
| 14, 15                    | $\overline{\text{CCKEN}}$ ,<br>CCKEN | Counter Clock Enable Inputs |
| 16                        | RCK                                  | Register Clock Input        |
| 17                        | RCKEN                                | Register Clock Enable Input |
| 18, 19                    | $\overline{\text{G}}$ , G            | Output Enable               |
| 10                        | GND                                  | Ground (0V)                 |
| 20                        | V <sub>CC</sub>                      | Positive Supply Voltage     |

## IEC LOGIC SYMBOL



## ABSOLUTE MAXIMUM RATINGS

| Symbol                              | Parameter   | Value                         | Unit |
|-------------------------------------|---|-------------------------------|------|
| V <sub>CC</sub>                     | Supply Voltage  | -0.5 to +7                    | V    |
| V <sub>I</sub>                      | DC Input Voltage  | -0.5 to V <sub>CC</sub> + 0.5 | V    |
| V <sub>O</sub>                      | DC Output Voltage   | -0.5 to V <sub>CC</sub> + 0.5 | V    |
| I <sub>IK</sub>                     | DC Input Diode Current  | ± 20                          | mA   |
| I <sub>OK</sub>                     | DC Output Diode Current   | ± 20                          | mA   |
| I <sub>O</sub>                      | DC Output Source Sink Current Per Output Pin ( $\overline{\text{RCO}}$ )<br>(QA - QH) | ± 20<br>± 35                  | mA   |
| I <sub>CC</sub> or I <sub>GND</sub> | DC V <sub>CC</sub> or Ground Current  | ± 70                          | mA   |
| P <sub>D</sub>                      | Power Dissipation   | 500 (*)                       | mW   |
| T <sub>stg</sub>                    | Storage Temperature   | -65 to +150                   | °C   |
| T <sub>L</sub>                      | Lead Temperature (10 sec)   | 300                           | °C   |

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied.

(\*) 500 mW: ± 65 °C derate to 300 mW by 10mW/°C: 65 °C to 85 °C

## RECOMMENDED OPERATING CONDITIONS

| Symbol                          | Parameter   | Value   | Unit                              |    |
|---------------------------------|---|---|-----------------------------------|----|
| V <sub>CC</sub>                 | Supply Voltage  | 2 to 6  | V                                 |    |
| V <sub>I</sub>                  | Input Voltage   | 0 to V <sub>CC</sub>  | V                                 |    |
| V <sub>O</sub>                  | Output Voltage  | 0 to V <sub>CC</sub>  | V                                 |    |
| T <sub>op</sub>                 | Operating Temperature: <b>M54HC Series</b><br><b>M74HC Series</b> | -55 to +125<br>-40 to +85   | °C<br>°C                          |    |
| t <sub>r</sub> , t <sub>f</sub> | Input Rise and Fall Time  | V <sub>CC</sub> = 2 V<br>V <sub>CC</sub> = 4.5 V<br>V <sub>CC</sub> = 6 V | 0 to 1000<br>0 to 500<br>0 to 400 | ns |

## DC SPECIFICATIONS

| Symbol          | Parameter                           | Test Conditions        |  | Value                                   |      |      |                      |      |                       | Unit |      |   |
|-----------------|-------------------------------------|------------------------|--|---|------|------|----------------------|------|-----------------------|------|------|---|
|                 |                                     | V <sub>CC</sub><br>(V) |  | T <sub>A</sub> = 25 °C<br>54HC and 74HC |      |      | -40 to 85 °C<br>74HC |      | -55 to 125 °C<br>54HC |      |      |   |
|                 |                                     |                        |  | Min.                                    | Typ. | Max. | Min.                 | Max. | Min.                  |      | Max. |   |
| V <sub>IH</sub> | High Level Input Voltage            | 2.0                    |  | 1.5                                     |      |      | 1.5                  |      | 1.5                   |      | V    |   |
|                 |                                     | 4.5                    |  | 3.15                                    |      |      | 3.15                 |      | 3.15                  |      |      |   |
|                 |                                     | 6.0                    |  | 4.2                                     |      |      | 4.2                  |      | 4.2                   |      |      |   |
| V <sub>IL</sub> | Low Level Input Voltage             | 2.0                    |  |   |      | 0.5  |                      | 0.5  |                       | 0.5  | V    |   |
|                 |                                     | 4.5                    |  |   |      | 1.35 |                      | 1.35 |                       | 1.35 |      |   |
|                 |                                     | 6.0                    |  |   |      | 1.8  |                      | 1.8  |                       | 1.8  |      |   |
| V <sub>OH</sub> | High Level Output Voltage (RCO)     | 2.0                    | V <sub>I</sub> =<br>V <sub>IH</sub><br>or<br>V <sub>IL</sub>                                   | I <sub>O</sub> = -20 μA                 | 1.9  | 2.0  |                      | 1.9  |                       | 1.9  | V    |   |
|                 |                                     | 4.5                    |  |   | 4.4  | 4.5  |                      | 4.4  |                       | 4.4  |      |   |
|                 |                                     | 6.0                    |  |   | 5.9  | 6.0  |                      | 5.9  |                       | 5.9  |      |   |
|                 |                                     | 4.5                    |  | I <sub>O</sub> = -4.0 mA                | 4.18 | 4.31 |                      | 4.13 |                       | 4.10 |      |   |
|                 |                                     | 6.0                    |  | I <sub>O</sub> = -5.2 mA                | 5.68 | 5.8  |                      | 5.63 |                       | 5.60 |      |   |
| V <sub>OH</sub> | High Level Output Voltage (QA - QH) | 2.0                    | V <sub>I</sub> =<br>V <sub>IH</sub><br>or<br>V <sub>IL</sub>                                   | I <sub>O</sub> = -20 μA                 | 1.9  | 2.0  |                      | 1.9  |                       | 1.9  | V    |   |
|                 |                                     | 4.5                    |  |   | 4.4  | 4.5  |                      | 4.4  |                       | 4.4  |      |   |
|                 |                                     | 6.0                    |  |   | 5.9  | 6.0  |                      | 5.9  |                       | 5.9  |      |   |
|                 |                                     | 4.5                    |  | I <sub>O</sub> = -6.0 mA                | 4.18 | 4.31 |                      | 4.13 |                       | 4.10 |      |   |
|                 |                                     | 6.0                    |  | I <sub>O</sub> = -7.8 mA                | 5.68 | 5.8  |                      | 5.63 |                       | 5.60 |      |   |
| V <sub>OL</sub> | Low Level Output Voltage (RCO)      | 2.0                    | V <sub>I</sub> =<br>V <sub>IH</sub><br>or<br>V <sub>IL</sub>                                   | I <sub>O</sub> = 20 μA                  |      | 0.0  | 0.1                  |      | 0.1                   |      | 0.1  | V |
|                 |                                     | 4.5                    |  |   |      | 0.0  | 0.1                  |      | 0.1                   |      | 0.1  |   |
|                 |                                     | 6.0                    |  |   |      | 0.0  | 0.1                  |      | 0.1                   |      | 0.1  |   |
|                 |                                     | 4.5                    |  | I <sub>O</sub> = 4.0 mA                 |      | 0.17 | 0.26                 |      | 0.33                  |      | 0.40 |   |
|                 |                                     | 6.0                    |  | I <sub>O</sub> = 5.2 mA                 |      | 0.18 | 0.26                 |      | 0.33                  |      | 0.40 |   |
| V <sub>OL</sub> | Low Level Output Voltage (QA - QH)  | 2.0                    | V <sub>I</sub> =<br>V <sub>IH</sub><br>or<br>V <sub>IL</sub>                                   | I <sub>O</sub> = 20 μA                  |      | 0.0  | 0.1                  |      | 0.1                   |      | 0.1  | V |
|                 |                                     | 4.5                    |  |   |      | 0.0  | 0.1                  |      | 0.1                   |      | 0.1  |   |
|                 |                                     | 6.0                    |  |   |      | 0.0  | 0.1                  |      | 0.1                   |      | 0.1  |   |
|                 |                                     | 4.5                    |  | I <sub>O</sub> = 6.0 mA                 |      | 0.17 | 0.26                 |      | 0.33                  |      | 0.40 |   |
|                 |                                     | 6.0                    |  | I <sub>O</sub> = 7.8 mA                 |      | 0.18 | 0.26                 |      | 0.33                  |      | 0.40 |   |
| I <sub>I</sub>  | Input Leakage Current               | 6.0                    | V <sub>I</sub> = V <sub>CC</sub> or GND  |   |      | ±0.1 |                      | ±1   |                       | ±1   | μA   |   |
| I <sub>OZ</sub> | 3 State Output Off State Current    | 6.0                    | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>V <sub>O</sub> = V <sub>CC</sub> or GND |   |      | ±0.5 |                      | ±5.0 |                       | ±10  | μA   |   |
| I <sub>CC</sub> | Quiescent Supply Current            | 6.0                    | V <sub>I</sub> = V <sub>CC</sub> or GND  |   |      | 4    |                      | 40   |                       | 80   | μA   |   |

**AC ELECTRICAL CHARACTERISTICS** (Input  $t_r = t_f = 6$  ns)

| Symbol                               | Parameter                            | Test Conditions        |                        |                       | Value                                   |      |      |                      |      |                       | Unit |      |
|--------------------------------------|--------------------------------------|------------------------|------------------------|-----------------------|---|------|------|----------------------|------|-----------------------|------|------|
|                                      |                                      | V <sub>CC</sub><br>(V) | C <sub>L</sub><br>(pF) |                       | T <sub>A</sub> = 25 °C<br>54HC and 74HC |      |      | -40 to 85 °C<br>74HC |      | -55 to 125 °C<br>54HC |      |      |
|                                      |                                      |                        |                        |                       | Min.                                    | Typ. | Max. | Min.                 | Max. | Min.                  |      | Max. |
| t <sub>TLH</sub><br>t <sub>THL</sub> | Output Transition Time (RCO)         | 2.0                    | 50                     |                       |   | 30   | 75   |                      | 95   |                       | 110  | ns   |
|                                      |                                      | 4.5                    |                        |                       | 8                                       | 15   |      | 19                   |      | 22                    |      |      |
|                                      |                                      | 6.0                    |                        |                       | 7                                       | 13   |      | 16                   |      | 19                    |      |      |
| t <sub>TLH</sub><br>t <sub>THL</sub> | Output Transition Time (Qn)          | 2.0                    | 50                     |                       |   | 20   | 60   |                      | 75   |                       | 90   | ns   |
|                                      |                                      | 4.5                    |                        |                       | 7                                       | 12   |      | 15                   |      | 18                    |      |      |
|                                      |                                      | 6.0                    |                        |                       | 6                                       | 10   |      | 13                   |      | 15                    |      |      |
| t <sub>PLH</sub><br>t <sub>PHL</sub> | Propagation Delay Time (CCK - Qn)    | 2.0                    | 50                     |                       |   | 108  | 210  |                      | 265  |                       | 315  | ns   |
|                                      |                                      | 4.5                    |                        |                       | 27                                      | 42   |      | 53                   |      | 63                    |      |      |
|                                      |                                      | 6.0                    |                        |                       | 23                                      | 36   |      | 45                   |      | 54                    |      |      |
|                                      |                                      | 2.0                    | 150                    |                       |   | 124  | 240  |                      | 300  |                       | 360  | ns   |
|                                      |                                      | 4.5                    |                        |                       | 31                                      | 48   |      | 60                   |      | 72                    |      |      |
|                                      |                                      | 6.0                    |                        |                       | 26                                      | 41   |      | 51                   |      | 61                    |      |      |
| t <sub>PLH</sub><br>t <sub>PHL</sub> | Propagation Delay Time (CLOAD - Qn)  | 2.0                    | 50                     |                       |   | 108  | 210  |                      | 265  |                       | 315  | ns   |
|                                      |                                      | 4.5                    |                        |                       | 27                                      | 42   |      | 53                   |      | 63                    |      |      |
|                                      |                                      | 6.0                    |                        |                       | 23                                      | 36   |      | 45                   |      | 54                    |      |      |
|                                      |                                      | 2.0                    | 150                    |                       |   | 124  | 240  |                      | 300  |                       | 360  | ns   |
|                                      |                                      | 4.5                    |                        |                       | 31                                      | 48   |      | 60                   |      | 72                    |      |      |
|                                      |                                      | 6.0                    |                        |                       | 26                                      | 41   |      | 51                   |      | 61                    |      |      |
| t <sub>PHL</sub>                     | Propagation Delay Time (CCLR - Qn)   | 2.0                    | 50                     |                       |   | 112  | 220  |                      | 275  |                       | 330  | ns   |
|                                      |                                      | 4.5                    |                        |                       | 28                                      | 44   |      | 55                   |      | 66                    |      |      |
|                                      |                                      | 6.0                    |                        |                       | 24                                      | 37   |      | 47                   |      | 56                    |      |      |
|                                      |                                      | 2.0                    | 150                    |                       |   | 128  | 250  |                      | 315  |                       | 375  | ns   |
|                                      |                                      | 4.5                    |                        |                       | 32                                      | 50   |      | 63                   |      | 75                    |      |      |
|                                      |                                      | 6.0                    |                        |                       | 27                                      | 43   |      | 54                   |      | 64                    |      |      |
| t <sub>PLH</sub><br>t <sub>PHL</sub> | Propagation Delay Time (CCK - RCO)   | 2.0                    | 50                     |                       |   | 144  | 250  |                      | 315  |                       | 375  | ns   |
|                                      |                                      | 4.5                    |                        |                       | 36                                      | 50   |      | 63                   |      | 75                    |      |      |
|                                      |                                      | 6.0                    |                        |                       | 31                                      | 10   |      | 54                   |      | 64                    |      |      |
| t <sub>PLH</sub><br>t <sub>PHL</sub> | Propagation Delay Time (CLOAD - RCO) | 2.0                    | 50                     |                       |   | 152  | 295  |                      | 370  |                       | 445  | ns   |
|                                      |                                      | 4.5                    |                        |                       | 38                                      | 59   |      | 74                   |      | 89                    |      |      |
|                                      |                                      | 6.0                    |                        |                       | 32                                      | 50   |      | 63                   |      | 76                    |      |      |
| t <sub>PLH</sub><br>t <sub>PHL</sub> | Propagation Delay Time (CCLR - RCO)  | 2.0                    | 50                     |                       |   | 116  | 225  |                      | 280  |                       | 340  | ns   |
|                                      |                                      | 4.5                    |                        |                       | 29                                      | 45   |      | 56                   |      | 68                    |      |      |
|                                      |                                      | 6.0                    |                        |                       | 25                                      | 38   |      | 48                   |      | 58                    |      |      |
| t <sub>PLH</sub><br>t <sub>PHL</sub> | Propagation Delay Time (RCK - RCO)   | 2.0                    | 50                     |                       |   | 188  | 360  |                      | 450  |                       | 540  | ns   |
|                                      |                                      | 4.5                    |                        |                       | 47                                      | 72   |      | 90                   |      | 108                   |      |      |
|                                      |                                      | 6.0                    |                        |                       | 40                                      | 61   |      | 77                   |      | 93                    |      |      |
| t <sub>PZL</sub><br>t <sub>PZH</sub> | 3 State Output Enable Time           | 2.0                    | 50                     | R <sub>L</sub> = 1 KΩ |   | 72   | 145  |                      | 180  |                       | 220  | ns   |
|                                      |                                      | 4.5                    |                        |                       |   | 18   | 29   |                      | 36   |                       | 44   |      |
|                                      |                                      | 6.0                    |                        |                       |   | 15   | 25   |                      | 31   |                       | 38   |      |
|                                      |                                      | 2.0                    | 150                    | R <sub>L</sub> = 1 KΩ |   | 88   | 175  |                      | 220  |                       | 265  | ns   |
|                                      |                                      | 4.5                    |                        |                       |   | 22   | 35   |                      | 44   |                       | 53   |      |
|                                      |                                      | 6.0                    |                        |                       |   | 19   | 30   |                      | 37   |                       | 45   |      |


## AC ELECTRICAL CHARACTERISTICS (continued)

| Symbol                                 | Parameter                                      | Test Conditions        |                        |                       | Value                                   |      |      |                      |      |                       | Unit |      |
|--|--|------------------------|------------------------|-----------------------|---|------|------|----------------------|------|-----------------------|------|------|
|  |  | V <sub>CC</sub><br>(V) | C <sub>L</sub><br>(pF) | R <sub>L</sub> = 1 KΩ | T <sub>A</sub> = 25 °C<br>54HC and 74HC |      |      | -40 to 85 °C<br>74HC |      | -55 to 125 °C<br>54HC |      |      |
|  |  |                        |                        |                       | Min.                                    | Typ. | Max. | Min.                 | Max. | Min.                  |      | Max. |
| t <sub>PLZ</sub><br>t <sub>PHZ</sub>   | 3 State Output<br>Disable Time                 | 2.0                    | 50                     | R <sub>L</sub> = 1 KΩ |   | 80   | 140  |                      | 175  |                       | 210  | ns   |
|  |  | 4.5                    |                        |                       |   | 22   | 28   |                      | 35   |                       | 42   |      |
|  |  | 6.0                    |                        |                       |   | 17   | 24   |                      | 30   |                       | 36   |      |
| f <sub>MAX</sub>                       | Maximum Clock<br>Frequency                     | 2.0                    | 50                     |                       | 5.4                                     | 4    |      | 4.4                  |      | 3.6                   |      | MHz  |
|  |  | 4.5                    |                        |                       | 27                                      | 17   |      | 22                   |      | 18                    |      |      |
|  |  | 6.0                    |                        |                       | 32                                      | 20   |      | 26                   |      | 21                    |      |      |
| t <sub>W(H)</sub><br>t <sub>W(L)</sub> | Minimum Pulse<br>Width<br>(CCK, RCK)           | 2.0                    | 50                     |                       |   | 44   | 100  |                      | 125  |                       | 150  | ns   |
|  |  | 4.5                    |                        |                       |   | 11   | 20   |                      | 25   |                       | 30   |      |
|  |  | 6.0                    |                        |                       |   | 9    | 17   |                      | 21   |                       | 26   |      |
| t <sub>W(L)</sub>                      | Minimum Pulse<br>Width<br>(CCLR, CLOAD)        | 2.0                    | 50                     |                       |   | 40   | 100  |                      | 125  |                       | 150  | ns   |
|  |  | 4.5                    |                        |                       |   | 10   | 20   |                      | 25   |                       | 30   |      |
|  |  | 6.0                    |                        |                       |   | 9    | 17   |                      | 21   |                       | 26   |      |
| t <sub>s</sub>                         | Minimum Set-up<br>Time (CCKEN,<br>CCKEN, CCK)  | 2.0                    | 50                     |                       |   | 56   | 125  |                      | 160  |                       | 195  | ns   |
|  |  | 4.5                    |                        |                       |   | 14   | 25   |                      | 32   |                       | 39   |      |
|  |  | 6.0                    |                        |                       |   | 12   | 21   |                      | 27   |                       | 33   |      |
| t <sub>s</sub>                         | Minimum Set-up<br>Time<br>(RCKEN - RCK)        | 2.0                    | 50                     |                       |   | 32   | 75   |                      | 95   |                       | 110  | ns   |
|  |  | 4.5                    |                        |                       |   | 8    | 15   |                      | 19   |                       | 22   |      |
|  |  | 6.0                    |                        |                       |   | 7    | 13   |                      | 16   |                       | 19   |      |
| t <sub>s(H)</sub>                      | Minimum Set-up<br>Time<br>(RCK - CLOAD)        | 2.0                    | 50                     |                       |   | 56   | 125  |                      | 160  |                       | 195  | ns   |
|  |  | 4.5                    |                        |                       |   | 14   | 25   |                      | 32   |                       | 39   |      |
|  |  | 6.0                    |                        |                       |   | 12   | 21   |                      | 27   |                       | 33   |      |
| t <sub>s</sub>                         | Minimum Set-up<br>Time<br>(A to H - RCK)       | 2.0                    | 50                     |                       |   | 16   | 50   |                      | 60   |                       | 70   | ns   |
|  |  | 4.5                    |                        |                       |   | 4    | 10   |                      | 12   |                       | 14   |      |
|  |  | 6.0                    |                        |                       |   | 3    | 9    |                      | 11   |                       | 12   |      |
| t <sub>h</sub>                         | Minimum Hold<br>Time                           | 2.0                    | 50                     |                       |   | 0    | 0    |                      | 0    |                       | 0    | ns   |
|  |  | 4.5                    |                        |                       |   | 0    | 0    |                      | 0    |                       | 0    |      |
|  |  | 6.0                    |                        |                       |   | 0    | 0    |                      | 0    |                       | 0    |      |
| t <sub>REM</sub>                       | Minimum Clear<br>Removal Time<br>(CCLR, CLOAD) | 2.0                    | 50                     |                       |   |      | 5    |                      |      |                       | 5    | ns   |
|  |  | 4.5                    |                        |                       |   |      |      | 5                    |      |                       | 5    |      |
|  |  | 6.0                    |                        |                       |   |      |      | 5                    |      |                       | 5    |      |
| C <sub>IN</sub>                        | Input Capacitance                              |                        |                        |                       |   | 5    | 10   |                      | 10   |                       | 10   | pF   |
| C <sub>PD</sub> (*)                    | Power Dissipation<br>Capacitance               |                        |                        |                       |   | 19   |      |                      |      |                       |      | pF   |

(\*) C<sub>PD</sub> is defined as the value of the IC's internal equivalent capacitance which is calculated from the operating current consumption without load. (Refer to Test Circuit). Average operating current can be obtained by the following equation. I<sub>CC(opr)</sub> = C<sub>PD</sub> • V<sub>CC</sub> • f<sub>IN</sub> + I<sub>CC</sub>

**Plastic DIP20 (0.25) MECHANICAL DATA**


| DIM. | mm    |       |      | inch  |       |       |
|------|-------|-------|------|-------|-------|-------|
|      | MIN.  | TYP.  | MAX. | MIN.  | TYP.  | MAX.  |
| a1   | 0.254 |       |      | 0.010 |       |       |
| B    | 1.39  |       | 1.65 | 0.055 |       | 0.065 |
| b    |       | 0.45  |      |       | 0.018 |       |
| b1   |       | 0.25  |      |       | 0.010 |       |
| D    |       |       | 25.4 |       |       | 1.000 |
| E    |       | 8.5   |      |       | 0.335 |       |
| e    |       | 2.54  |      |       | 0.100 |       |
| e3   |       | 22.86 |      |       | 0.900 |       |
| F    |       |       | 7.1  |       |       | 0.280 |
| I    |       |       | 3.93 |       |       | 0.155 |
| L    |       | 3.3   |      |       | 0.130 |       |
| Z    |       |       | 1.34 |       |       | 0.053 |



P001J


## Ceramic DIP20 MECHANICAL DATA

| DIM. | mm                    |       |      | inch  |       |       |
|------|-----------------------|-------|------|-------|-------|-------|
|      | MIN.                  | TYP.  | MAX. | MIN.  | TYP.  | MAX.  |
| A    |                       |       | 25   |       |       | 0.984 |
| B    |                       |       | 7.8  |       |       | 0.307 |
| D    |                       | 3.3   |      |       | 0.130 |       |
| E    | 0.5                   |       | 1.78 | 0.020 |       | 0.070 |
| e3   |                       | 22.86 |      |       | 0.900 |       |
| F    | 2.29                  |       | 2.79 | 0.090 |       | 0.110 |
| G    | 0.4                   |       | 0.55 | 0.016 |       | 0.022 |
| I    | 1.27                  |       | 1.52 | 0.050 |       | 0.060 |
| L    | 0.22                  |       | 0.31 | 0.009 |       | 0.012 |
| M    | 0.51                  |       | 1.27 | 0.020 |       | 0.050 |
| N1   | 4° (min.), 15° (max.) |       |      |       |       |       |
| P    | 7.9                   |       | 8.13 | 0.311 |       | 0.320 |
| Q    |                       |       | 5.71 |       |       | 0.225 |



**SO20 MECHANICAL DATA**


| DIM. | mm         |       |       | inch  |       |       |
|------|------------|-------|-------|-------|-------|-------|
|      | MIN.       | TYP.  | MAX.  | MIN.  | TYP.  | MAX.  |
| A    |            |       | 2.65  |       |       | 0.104 |
| a1   | 0.10       |       | 0.20  | 0.004 |       | 0.007 |
| a2   |            |       | 2.45  |       |       | 0.096 |
| b    | 0.35       |       | 0.49  | 0.013 |       | 0.019 |
| b1   | 0.23       |       | 0.32  | 0.009 |       | 0.012 |
| C    |            | 0.50  |       |       | 0.020 |       |
| c1   | 45° (typ.) |       |       |       |       |       |
| D    | 12.60      |       | 13.00 | 0.496 |       | 0.512 |
| E    | 10.00      |       | 10.65 | 0.393 |       | 0.419 |
| e    |            | 1.27  |       |       | 0.050 |       |
| e3   |            | 11.43 |       |       | 0.450 |       |
| F    | 7.40       |       | 7.60  | 0.291 |       | 0.299 |
| L    | 0.50       |       | 1.27  | 0.19  |       | 0.050 |
| M    |            |       | 0.75  |       |       | 0.029 |
| S    | 8° (max.)  |       |       |       |       |       |



P013L

## PLCC20 MECHANICAL DATA

| DIM. | mm   |      |       | inch  |       |       |
|------|------|------|-------|-------|-------|-------|
|      | MIN. | TYP. | MAX.  | MIN.  | TYP.  | MAX.  |
| A    | 9.78 |      | 10.03 | 0.385 |       | 0.395 |
| B    | 8.89 |      | 9.04  | 0.350 |       | 0.356 |
| D    | 4.2  |      | 4.57  | 0.165 |       | 0.180 |
| d1   |      | 2.54 |       |       | 0.100 |       |
| d2   |      | 0.56 |       |       | 0.022 |       |
| E    | 7.37 |      | 8.38  | 0.290 |       | 0.330 |
| e    |      | 1.27 |       |       | 0.050 |       |
| e3   |      | 5.08 |       |       | 0.200 |       |
| F    |      | 0.38 |       |       | 0.015 |       |
| G    |      |      | 0.101 |       |       | 0.004 |
| M    |      | 1.27 |       |       | 0.050 |       |
| M1   |      | 1.14 |       |       | 0.045 |       |



Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics - All Rights Reserved

SGS-THOMSON Microelectronics GROUP OF COMPANIES  
Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands -  
Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A