

PF08107BP

MOS FET Power Amplifier Module
for E-GSM and DCS1800 Dual Band Handy Phone

HITACHI

ADE-208-1399B (Z)
3rd Edition
Feb. 2001

Application


- Dual band amplifier for E-GSM (880 MHz to 915 MHz) and DCS1800 (1710 MHz to 1785 MHz).
- For 3.5 V nominal operation

Features

- 2 in / 2 out dual band amplifier
- Simple external circuit including output matching circuit
- One power control pin with one band switch
- High gain 3stage amplifier : 0 dBm input Typ
- Lead less thin & Small package : $8 \times 13.75 \times 1.6$ mm Typ
- High efficiency : 46 % Typ at 35.0 dBm for E-GSM
40 % Typ at 32.0 dBm for DCS1800

Pin Arrangement

- RF-K-8



- 1: Pin_{GSM}
- 2: Vapc
- 3: Vdd1
- 4: Pout_{GSM}
- 5: Pout_{DCS}
- 6: Vdd2
- 7: Vctl
- 8: Pin_{DCS}
- G: GND

Absolute Maximum Ratings ($T_c = 25^\circ\text{C}$)

Item	Symbol	Rating	Unit
Supply voltage	Vdd	8	V
Supply current	I _{dd} _{GSM}	3.5	A
	I _{dd} _{DCS}	2	A
Vctl voltage	Vctl	4	V
Vapc voltage	Vapc	4	V
Input power	Pin	10	dBm
Operating case temperature	T _c (op)	-30 to +100	°C
Storage temperature	T _{stg}	-30 to +100	°C
Output power	P _{out} _{GSM}	37	dBm
	P _{out} _{DCS}	34.8	dBm

Note: The maximum ratings shall be valid over both the E-GSM-band (880 to 915 MHz), and the DCS1800-band (1710 to 1785 MHz).

Electrical Characteristics for DC ($T_c = 25^\circ\text{C}$)

Item	Symbol	Min	Typ	Max	Unit	Test Condition
Drain cutoff current	I _{ds}	—	—	20	μA	Vdd = 4.7 V, Vapc = 0 V, Vctl = 0.2 V
		—	—	300	μA	Vdd = 8 V, Vapc = 0 V, Vctl = 0.2 V, T _c = -20 to +70°C
Vapc control current	I _{apc}	—	—	3	mA	Vapc = 2.2 V
Vctl control current	I _{ctl}	—	—	2	μA	Vctl = 3 V

Electrical Characteristics for E-GSM mode (Tc = 25°C)

Test conditions unless otherwise noted:

f = 880 to 915 MHz, Vdd1 = Vdd2 = 3.5 V, Pin = 0 dBm, Vctl = 2.0 V, Rg = Rl = 50 Ω, Tc = 25°C, Pulse operation with pulse width 577 μs and duty cycle 1:8 shall be used.

Item	Symbol	Min	Typ	Max	Unit	Test Condition
Frequency range	F	880	—	915	MHz	
Band select (GSM active)	Vctl	2.0	—	2.8	V	
Input power	Pin	-2	0	2	dBm	
Control voltage range	Vapc	0.2	—	2.2	V	
Supply voltage	Vdd	3.0	3.5	4.5	V	
Total efficiency	η_T	41	46	—	%	Pout _{GSM} = 35 dBm,
2nd harmonic distortion	2nd H.D.	—	-45	-35	dBc	Vapc = controlled
3rd harmonic distortion	3rd H.D.	—	-45	-35	dBc	
4th~8th harmonic distortion	4th~8th H.D.	—	—	-35	dBc	
Input VSWR	VSWR (in)	—	1.5	3	—	
Output power (1)	Pout (1)	35.0	36.0	—	dBm	Vapc = 2.2 V
Output power (2)	Pout (2)	34.0	35.0	—	dBm	Vdd = 3.1 V, Vapc = 2.2 V, Tc = +70°C
Isolation	—	—	-42	-37	dBm	Vapc = 0.2 V, Pin = 2 dBm
Isolation at DCS RF-output when GSM is active	—	—	-30	-20	dBm	Pout _{GSM} = 35 dBm, Measured at f = 1760 to 1830 MHz
Switching time	t _r , t _f	—	1	2	μs	Pout _{GSM} = 0 to 35.0 dBm
Stability	—	No parasitic oscillation			—	Vdd = 3.1 to 4.5 V, Pout ≤ 35 dBm, Vapc _{GSM} ≤ 2.2 V, Rg = 50 Ω, Tc = 25°C, Output VSWR = 6 : 1 All phases
Load VSWR tolerance	—	No degradation			—	Vdd = 3.1 to 4.5 V, Pout _{GSM} ≤ 35 dBm, Vapc _{GSM} ≤ 2.2 V, Rg = 50 Ω, t = 20 sec., Tc = 25°C, Output VSWR = 10 : 1 All phases


Electrical Characteristics for DCS1800 mode ($T_c = 25^\circ\text{C}$)

Test conditions unless otherwise noted:



$f = 1710$ to 1785 MHz, $V_{dd1} = V_{dd2} = 3.5$ V, $P_{in} = 0$ dBm, $V_{ctl} = 0$ V, $R_g = R_l = 50 \Omega$, $T_c = 25^\circ\text{C}$,
Pulse operation with pulse width $577 \mu\text{s}$ and duty cycle 1:8 shall be used.


Item	Symbol	Min	Typ	Max	Unit	Test Condition
Frequency range	F	1710	—	1785	MHz	DCS1800 (1710 to 1785)
Band select (DCS active)	V_{ctl}	0	—	0.1	V	
Input power	P_{in}	-2	0	2	dBm	
Control voltage range	V_{apc}	0.2	—	2.2	V	
Supply voltage	V_{dd}	3.0	3.5	4.5	V	
Total efficiency	η_T	34	40	—	%	$P_{out_{DCS}} = 32$ dBm,
2nd harmonic distortion	2nd H.D.	—	-45	-35	dBc	$V_{apc} =$ controlled
3rd harmonic distortion	3rd H.D.	—	-45	-35	dBc	
4th~8th harmonic distortion	4th~8th H.D.	—	—	-35	dBc	
Input VSWR	VSWR (in)	—	1.5	3	—	
Output power (1)	P_{out} (1)	32.5	33.5	—	dBm	$V_{apc} = 2.2$ V
Output power (2)	P_{out} (2)	31.0	32.0	—	dBm	$V_{dd} = 3.1$ V, $V_{apc} = 2.2$ V, $T_c = +70^\circ\text{C}$
Isolation	—	—	-42	-37	dBm	$V_{apc} = 0.2$ V, $P_{in_{DCS}} = 2$ dBm
Switching time	t_r, t_f	—	1	2	μs	$P_{out_{DCS}} = 0$ to 32 dBm
Stability	—	No parasitic oscillation			—	$V_{dd} = 3.1$ to 4.5 V, $P_{out_{DCS}} \leq 32$ dBm, $V_{apc} \leq 2.2$ V, $R_g = 50 \Omega$, Output VSWR = 6 : 1 All phases
Load VSWR tolerance	—	No degradation			—	$V_{dd} = 3.1$ to 4.5 V, $P_{out_{DCS}} \leq 32$ dBm, $V_{apc} \leq 2.2$ V, $R_g = 50 \Omega$, $t = 20$ sec., Output VSWR = 10 : 1 All phases



Internal Diagram and External Circuit





Characteristic Curves








































Package Dimensions

Unit: mm



- 1: Pin_{GSM}
- 2: V_{apc}
- 3: V_{dd1}
- 4: P_{out GSM}
- 5: P_{out DCS}
- 6: V_{dd2}
- 7: V_{ctl}
- 8: Pin_{DCS}
- G: GND

Remark:
Coplanarity of bottom side of terminals are less than 0 ± 0.1 mm.

Hitachi Code	RF-K-8
JEDEC	—
EIAJ	—
Mass (reference value)	—

Cautions

1. Hitachi neither warrants nor grants licenses of any rights of Hitachi's or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document. Hitachi bears no responsibility for problems that may arise with third party's rights, including intellectual property rights, in connection with use of the information contained in this document.
2. Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.
3. Hitachi makes every attempt to ensure that its products are of high quality and reliability. However, contact Hitachi's sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic, safety equipment or medical equipment for life support.
4. Design your application so that the product is used within the ranges guaranteed by Hitachi particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. Hitachi bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating Hitachi product does not cause bodily injury, fire or other consequential damage due to operation of the Hitachi product.
5. This product is not designed to be radiation resistant.
6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from Hitachi.
7. Contact Hitachi's sales office for any questions regarding this document or Hitachi semiconductor products.

HITACHI

Hitachi, Ltd.

Semiconductor & Integrated Circuits.

Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan
Tel: Tokyo (03) 3270-2111 Fax: (03) 3270-5109

URL NorthAmerica : <http://semiconductor.hitachi.com/>
 Europe : <http://www.hitachi-eu.com/hel/ecg>
 Asia : <http://sicapac.hitachi-asia.com>
 Japan : <http://www.hitachi.co.jp/Sicd/indx.htm>

For further information write to:

Hitachi Semiconductor
(America) Inc.
179 East Tasman Drive,
San Jose, CA 95134
Tel: <1> (408) 433-1990
Fax: <1>(408) 433-0223

Hitachi Europe GmbH
Electronic Components Group
Dornacher StraÙe 3
D-85622 Feldkirchen, Munich
Germany
Tel: <49> (89) 9 9180-0
Fax: <49> (89) 9 29 30 00

Hitachi Europe Ltd.
Electronic Components Group.
Whitebrook Park
Lower Cookham Road
Maidenhead
Berkshire SL6 8YA, United Kingdom
Tel: <44> (1628) 585000
Fax: <44> (1628) 585160

Hitachi Asia Ltd.
Hitachi Tower
16 Collyer Quay #20-00,
Singapore 049318
Tel : <65>-538-6533/538-8577
Fax : <65>-538-6933/538-3877
URL : <http://www.hitachi.com.sg>

Hitachi Asia Ltd.
(Taipei Branch Office)
4/F, No. 167, Tun Hwa North Road,
Hung-Kuo Building,
Taipei (105), Taiwan
Tel : <886>-(2)-2718-3666
Fax : <886>-(2)-2718-8180
Telex : 23222 HAS-TP
URL : <http://www.hitachi.com.tw>

Hitachi Asia (Hong Kong) Ltd.
Group III (Electronic Components)
7/F., North Tower,
World Finance Centre,
Harbour City, Canton Road
Tsim Sha Tsui, Kowloon,
Hong Kong
Tel : <852>-(2)-735-9218
Fax : <852>-(2)-730-0281
URL : <http://www.hitachi.com.hk>

Copyright © Hitachi, Ltd., 2001. All rights reserved. Printed in Japan.
Colophon 2.0

HITACHI