

TRANSISTOR MODULE (Hi-β)

QCA200BA60

TOP





UL;E76102 (M)

QCA200BA60 is a dual Darlington power transistor module which has series-connected ULTRA HIGH h_{FE} , high speed, high power Darlington transistors. Each transistor has a reverse paralleled fast recovery diode (t_{rr} : 200ns). The mounting base of the module is electrically isolated from Semiconductor elements for simple heatsink construction,

- $I_C=200A$, $V_{CEX}=600V$
- Low saturation voltage for higher efficiency.
- ULTRA HIGH DC current gain h_{FE} . $h_{FE} \geq 750$
- Isolated mounting base
- V_{EBO} 10V for faster switching speed.

(Applications)

Motor Control (VVVF), AC/DC Servo, UPS, Switching Power Supply, Ultrasonic Application



Maximum Ratings

($T_j=25^\circ\text{C}$ unless otherwise specified)

Symbol	Item	Conditions	Ratings		Unit
			QCA200BA60		
V_{CBO}	Collector-Base Voltage		600		V
V_{CEX}	Collector-Emitter Voltage	$V_{BE}=-2V$	600		V
V_{EBO}	Emitter-Base Voltage		10		V
I_C	Collector Current	() $p_w \leq 1ms$	200 (400)		A
$-I_C$	Reverse Collector Current		200		A
I_B	Base Current		12		A
P_T	Total power dissipation	$T_C=25^\circ\text{C}$	1250		W
T_j	Junction Temperature		-40 to +150		$^\circ\text{C}$
T_{stg}	Storage Temperature		-40 to +125		$^\circ\text{C}$
V_{ISO}	Isolation Voltage	A.C.1minute	2500		
	Mounting Torque	Mounting (M6)	Recommended Value 2.5-3.9 (25-40)		N·m (kgf·cm)
		Terminal (M6)	Recommended Value 2.5-3.9 (25-40)		
	Mass	Typical Value	470		g

Electrical Characteristics

Symbol	Item	Conditions	Ratings			Unit
			Min.	Typ.	Max.	
I_{CBO}	Collector Cut-off Current	$V_{CB}=V_{CBO}$			2.0	mA
I_{EBO}	Emitter Cut-off Current	$V_{EB}=V_{EBO}$			800	mA
$V_{CEO(SUS)}$	Collector Emitter Sustaining Voltage	$I_C=1A$	450			V
$V_{CEX(SUS)}$		$I_C=40A$, $I_{B2}=-8A$	600			
h_{FE}	D.C. Current Gain	$I_C=200A$, $V_{CE}=2.5V$	750			
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=200A$, $I_B=0.26A$			2.5	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	$I_C=200A$, $I_B=0.26A$			3.0	V
t_{on}	Switching Time	On Time			2.0	μs
t_s		Storage Time	$V_{CC}=300V$, $I_C=200A$ $I_{B1}=0.4A$, $I_{B2}=-4A$		8.0	
t_f		Fall Time			2.0	
V_{ECO}	Collector-Emitter Reverse Voltage	$I_C=-200A$			1.8	V
t_{rr}	Reverse Recovery time	$V_{CC}=300V$, $I_C=-200A$, $-di/dt=200A/\mu s$, $V_{BE}=-5V$		200		ns
$R_{th(j-c)}$	Thermal Impedance (junction to case)	Transistor part			0.1	$^\circ\text{C}/\text{W}$
		Diode part			0.3	

