


TOSHIBA Transistor Silicon NPN Epitaxial Type (PCT Process)

RN5006


Motor Drive Circuit Applications
 Power Amplifier Applications
 Power Switching Applications

- With built-in bias resistors
- Simplify circuit design
- Reduce a quantity of parts and manufacturing process
- Small flat package
- $P_C = 1\sim 2W$ (mounted on ceramic substrate)
- Complementary to RN6006

Equivalent Circuit



Unit in mm



Weight: 0.05g


Maximum Ratings ($T_a = 25^\circ C$)

Characteristic	Symbol	Rating	Unit
Collector-base voltage	V_{CBO}	10	V
Collector-emitter voltage	V_{CEO}	10	V
Emitter-base voltage	V_{EBO}	6	V
Collector current	DC	I_C	2
	Pulse (Note1)	I_{CP}	4
Base current	I_B	0.4	A
Collector power dissipation	P_C	500	mW
Collector power dissipation	P_C^*	1000	mW
Junction temperature	T_j	150	$^\circ C$
Storage temperature range	T_{stg}	-55~150	$^\circ C$

Note: Pulse width $\leq 10ms$, duty cycle $\leq 30\%$

* : Mounted on ceramic substrate ($250mm^2 \times 0.8t$)

Marking



961001EAA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

Electrical Characteristics (Ta = 25°C)

Characteristic	Symbol	Test Circuit	Test Condition	Min	Typ.	Max	Unit
Collector cut-off current	I_{CBO}	—	$V_{CB} = 10V, I_E = 0$	—	—	0.1	μA
Emitter cut-off current	I_{EBO}	—	$V_{EB} = 6V, I_C = 0$	0.462	0.60	0.857	mA
Collector-emitter breakdown voltage	$V_{(BR)CES}$	—	$I_C = 1mA$	10	—	—	V
DC current gain	$h_{FE} (1)$	—	$V_{CE} = 1V, I_C = 0.5A$	160	—	600	—
	$h_{FE} (2)$		$V_{CE} = 1V, I_C = 4.0A$	60	—	—	
Collector-emitter saturation voltage	$V_{CE} (sat)$	—	$I_C = 2A, I_B = 0.05A$	—	—	0.5	V
Transition frequency	f_T	—	$V_{CE} = 1V, I_C = 0.5A$	—	140	—	MHz
Collector output capacitance	C_{ob}	—	$V_{CB} = 10V, I_E = 0, f = 1 MHz$	—	30	—	pF
Resistor	R	—	—	7	10	13	k Ω