

SF8L60

600V 8A


FEATURES

- High Voltage
- trr70ns
- Fully Isolated Molding
- Dielectric strength 2kV guaranteed

APPLICATION

- PFC
- Switching power supply
- Free Wheel
- CTV+B output, lighting

OUTLINE DIMENSIONS



RATINGS

●Absolute Maximum Ratings (If not specified Tc=25°C)


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	Tstg		-55~150	°C
Operating Junction Temperature	Tj		150	°C
Maximum Reverse Voltage	VRM		600	V
Average Rectified Forward Current	Io	50Hz sine wave, R-load, Tc=118°C	8	A
Peak Surge Forward Current	IFSM	50Hz sine wave, Non-repetitive 1 cycle peak value, Tj=25°C	170	A
Dielectric Strength	Vdis	Terminals to case, AC 1 minute	2	kV
Mounting Torque	TOR	(Recommended torque:0.3N·m)	0.5	N·m

●Electrical Characteristics (If not specified Tc=25°C)

Item	Symbol	Conditions	Ratings	Unit
Forward Voltage	VF	IF=8A, Pulse measurement	Max.1.5	V
Reverse Current	IR	VR=VRM, Pulse measurement	Max.25	μA
Reverse Recovery Time	trr	IF=0.5A, IR=1A	Max.70	ns
Thermal Resistance	θjc	junction to case	Max.2.5	°C/W


SF8L60

Forward Voltage




SF8L60

Forward Power Dissipation




$T_j = T_{jmax}$




SF8L60

Derating Curve




$$V_R = V_{RM}$$



SF8L60

Peak Surge Forward Capability



SF8L60 Junction Capacitance

