

Rectifier Diodes


■ $V_{RM}: 100 \sim 1500V$ ■ $I_o: 0.5 \sim 3.0A$

SFPM/AM/EM/RM/RO


Rating / Characteristics	Absolute Maximum Ratings						Electrical Characteristics ($T_a = 25^\circ C$)				Others			
	V_{RSM} (V)	V_{RM} (V)	I_o (A)	I_{FSM} (A)	T_J ($^\circ C$)	T_{stg} ($^\circ C$)	V_F (V)	I_R (μA)	I_{RH} (μA)		Outline Drawing	Weight(g)	Taping	Note
Type No.			() = with Fin	50Hz Half Sine Wave Single Pulse			max	I_F (A)	$V_R = V_{RM}$ max	$V_R = V_{RM}$ $T_a = 100^\circ C$ max				
SFPM-52	250	200	0.9	30	$-40 \sim +150$		1.0				①	0.072		Surface Mount
SFPM-54	450	400												
SFPM-62	250	200												
SFPM-64	450	400												
AM01Z	250	200	1.0	35	$-40 \sim +140$		0.98	1.0	10		②	0.13		
AM01	450	400												
AM01A	650	600												
EM01Z	250	200												
EM01	450	400	1.2	45	$-40 \sim +140$		0.97				③	0.2		
EM01A	650	600												
EM 1Y	150	100												
EM 1Z	250	200												
EM 1	450	400	1.0	35	$-40 \sim +130$		1.2	1.0	5		④	0.3		
EM 1A	650	600												
EM 1B	850	800												
EM 1C	1050	1000												
EM 2	450	400	1.2	80	$-40 \sim +140$		0.92	1.2			⑤	0.44	○	
EM 2A	650	600												
EM 2B	850	800												
RM 1Z	250	200												
RM 1	450	400	1.0	50	$-40 \sim +130$		0.95	1.0	5		⑥	0.6		
RM 1A	650	600												
RM 1B	850	800												
RM 1C	1050	1000												
RM 1D	1250	1200	0.6	25	$-40 \sim +130$		1.4				⑦	1.2	—	
RM 1E	1450	1400												
RM 1F	1550	1500												
RM 11A	—	600												
RM 11B	—	800	1.2	100	$-40 \sim +140$		0.92	1.5			⑧	1.0		
RM 11C	—	1000												
RM 10Z	—	200												
RM 10	—	400												
RM 10A	—	600	1.2	100	$-40 \sim +130$		0.91				⑨	0.6		
RM 10B	—	800												
RM 2Z	250	200												
RM 2	450	400												
RM 2A	650	600	2.5	150	$-40 \sim +150$		0.95	3.0			⑩	1.2		
RM 2B	850	800												
RM 2C	1050	1000												
RM 3	400	400												
RM 4Y	150	100	1.7	200	$-40 \sim +150$		0.97	3.5			⑪	0.61	○	
RM 4Z	250	200												
RM 4	450	400												
RM 4A	650	600												
RM 4B	850	800	1.8(3.0)	350	$-40 \sim +130$		0.92	1.5			⑫	0.61	○	
RM 4C	1050	1000												
RM 4AM	650	600												
RO 2Z	250	200												
RO 2	450	400	1.2	80	$-40 \sim +130$		0.92	1.5			⑬	0.61	○	
RO 2A	650	600												
RO 2B	850	800												
RO 2C	1050	1000												

○ : Available


Outline Drawing ①




Outline Drawing ②




Outline Drawing ③




Outline Drawing ④



Outline Drawing ⑤




Outline Drawing ⑥



①~⑥. Plastic Molding : UL94V-0 or Equivalent


SFFPM-52,54 SFFPM-62,64

Io-Ta Deratings




AMO1 Series

Io-Ta Deratings




EM01, EM 2 Series

Io-Ta Deratings




EM 1 Series

If-Vf Characteristics (Typical Value)




RM 1 Series


If-Vf Characteristics (Typical Value)




IFSM Characteristics




Io-Ta Deratings



IFSM Characteristics




Io-Ta Deratings




RM 11 Series

Io-Ta Deratings




RM 10 Series

Io-Ta Deratings




RM 2 Series


If-Vf Characteristics (Typical Value)



IFSM Characteristics




Io-Ta Deratings




RM 4 Series


Ir-Vr Characteristics (Typical Value)




If-Vf Characteristics (Typical Value)



IFSM Characteristics




Io-Ta Deratings




RM 4AM


Io-Ta Deratings



Outline Drawing ⑦




Outline Drawing ⑧




RO 2 Series


If-Vf Characteristics (Typical Value)



IFSM Characteristics



Io-Ta Deratings




Symbols/trr Measurement Circuit

Symbols

V_{RSM}	Peak Reverse Surge Voltage	I_{RSM}	Peak Reverse Surge Current	T_{stg}	Storage Temperature
V_{RM}	Peak Reverse Voltage	I_R	Reverse Current	t_{rr}	Reverse Recovery Time
V_{P-P}	Reverse Voltage (Peak to Peak)	I_{RP}	Peak Reverse Current	C_t	Total Capacitance Between Terminals
V_R	Reverse Voltage	$I_{R(H)}$	Reverse Current (High Temperature)	$R_{th(j-c)}$	Thermal Resistance, Junction to Case
V_F	Forward Voltage	I_Z	Avalanche Current	r_z	Temperature Coefficient of Breakdown Voltage
V_B	Breakdown Voltage	I_{ZSM}	Allowable Avalanche Current	R_z	Equivalent Resistance of Breakdown Region
I_o	Average Rectified Forward Current	T_a	Ambient Temperature	$P_{F(AV)}$	Average Forward Power Dissipation
I_F	Forward Current	T_j	Junction Temperature	I_t^2	I_t^2 limiting Value
$I_{F(AV)}$	Average Forward Current	T_{opr}	Operating Ambient Temperature		
I_{FSM}	Peak Forward Surge Current	T_c	Case Temperature		

Reverse Recovery Time Measurement Circuit



Taping Specifications

Excluding High Voltage Diodes


Designation	Dimension (in mm)	Packaging Dimension and Marking	Quantity
V Add Suffix [V] to Type No.	Tape Carrier Method (1) Right side of taping direction is cathode. (2) Place electrode side down when casing. (3) Provide leader tape of 150~200mm at beginning of tape. (4) Provide space of more than 10 pitches each for beginning and end of tape.	Reel Marking of Type No., Lot No. and Quantity 	1,800 pcs per reel
V Add Suffix [V] to type No.	Axial Taping 	Reel Markings of Type No. Lot No. and Quantity Core Flange 	5,000 pcs per reel (2.7 φ body) 3,000 pcs per reel (4.0 φ body)

Taping Specifications

Designation	Dimension (in mm)	Packaging Dimension and Marking	Quantity
V1 Add Suffix [V1] to Type No.	Axial Taping 	Ammunition Pack 	2,000 pcs per box (2.7 ϕ body) 1,000 pcs per box (4.0 ϕ body)
VO Add Suffix [VO] to Type No.	Axial Taping 	Ammunition Pack 	2,000 pcs per box (2.7 ϕ body) (2.4 ϕ body)
V3 Add Suffix [V3] to Type No.	Axial Taping 	Reel 	1,500 pcs per reel (5.2 ϕ body)
V4 Add Suffix [V4] to Type No.	Axial Taping 	Ammunition Pack 	1,000 pcs per box (5.2 ϕ body)
W Add Suffix [W] to Type No.	Radial Taping 	Ammunition Pack 	4,000 pcs per box (2.7 ϕ body) (0.6 ϕ lead)
WS Add Suffix [WS] to Type No.	Radial Taping (Applicable to AO Series) 	Ammunition Pack 	2,500 pcs per box (2.4 ϕ body)
WK Add Suffix [WK] to Type No.	Radial Taping (Applicable to AO Series) 		


Marking Guide

1 Small TMD




- ① Type Designation (in abbreviation)
AM01 is abbreviated as M.
- ② Class Designation
Z: 200V, No Letter: 400V, A: 600V
- ③ A: Year (Last Number of AD Year)
B: Month (Jan. to Sept. are represented by numbers 1 to 9 respectively, and Oct., Nov., and Dec. are abbreviated as O, N and D respectively)
- ④ Cathode Band: Successive Band, however AU02 Type is Non-Successive Band.

2 E/EO Type TMD



- ① Type Designation (in abbreviation)
EM01 is abbreviated as MO, EM2 is abbreviated as M2.
- ② Class Designation
Z: 200V, No Letter: 400V, A: 600V
B: 800 V, C: 1000V, F: 1500V
However, EU02A to be marked 2A, and EU2YX to be marked Y.
- ③ Abbreviations Representing Production Period
A: Year (Last Number of AD Year)
B: Month (1~9, O, N, D)
- ④ Production Period Divided in 3 ten day terms
• : 1st 10days •• : 2nd 10days ••• : 3rd 10days


3 R Type TMD



- ① Type Designation: Mark in 2 sets
- ② Production Period: Mark in 4 sets
A: Year (Last Number of AD Year)
B: Month (1~9, O, N, D)
- ③ Production Period Divided in 3 ten day terms
• : 1st 10days •• : 2nd 10days ••• : 3rd 10days
- ④ Cathode Band Color: Silver: For Power Supply
Yellow: For Middle Speed
Red : For High Speed and Ultra-High Speed


4 RB40/60

(RB40 Series)




- ① Peak Reverse Voltage Designation
1, 2, 4, 6, C
Production Period
- ② Year (Last Number of AD Year)
- ③ Month (1~9, O, N, D)
- ④ Divided in 3 ten day terms
A: 1st 10days, B: 2nd 10days
C: 3rd 10days
Color Designation: Silver

(RB60 Series)




Dot Designation RB601 Violet
RB602 No Color
RB604 Blue
RB606 White

5 RBV/RBA




- ① Type Designation
- ② Lot Number
1st : Year (Last Number of AD Year)
2nd: Month (1~9, O, N, D)
3rd : Divided 1~3 ten day Terms
A: 1st 10 days B: 2nd 10 days
C: 3rd 10 days
- ③ In-Put Designation

6 TO220 Type (FM or CT Type)




- ① Type Designation
Show FMU-12S as FMU12S.
- ② Polarity: Rectifier Symbols
- ③ Lot Number (Laser Marking)
1st : Year (Last Number of AD Year)
2nd : Month (0~9, O, N, D)
3rd, 4th: Day

7 TO220 Type (FM or CT Type, single chip)




- ① Type Designation: Omit Last Letter
Show FML-G12S as FMLG12.
- ② Last Letter of Type Designation
- ③ Polarity: Rectifier Symbols
- ④ Lot Number (Laser Marking)
1st : Year (Last Number of AD Year)
2nd : Month (0~9, O, N, D)
3rd, 4th: Day

8 TO3P Type (FM or CT Type)




- ① Type shown in full designation
However, CTB-34/34S/34M are marked as CTB-34, CTU-G3DR is marked as CTUG3DR.
- ② Polarity: Rectifier Symbols
- ③ Lot Number:
1) M, U, G and L Types
First Number : Last Digit of AD Year
Second Number : Month
Third and Fourth Numbers: Day
Fifth Number : None
2) For types CTB-34/34S/34M, the fifth letter shows type designation. If no fifth number, the type is CTB-33 or CTB-34.
3) Marking Color: Silver

9 MI-10/15 Type



- ① MI-10/15 is die-stamped on the top of the case.
- ② Rectifier Symbols
- ③ Lot Number:
First Number : Peak Reverse Voltage:
(Letter) 0=50V, 1=100V, 2=200V,
4=400V, 6=600V, C=1000V
Second Number : Last Digit of AD Year
Third Number : Month
Fourth and Fifth Numbers: Day
Sixth Number : Production number and
U: Voltage Doubler Type

10 SFP Type



- ① Type Designation:
SFPB-64 is abbreviated at B64.
- ② Cathode Band