

SI-8200L/8300L Series


Self Oscillating Switching Type with Coil

■Features

- Integrated switching IC and coil construction
- Requires 2 external components only
- Low switching noise
- Heatsink not required

■Applications

- Telephone power supplies
- Onboard local power supplies



■Lineup

Part Number	SI-8201L	SI-8203L	SI-8211L	SI-8213L	SI-8301L
Vo(V)	5	12	5	12	5
Io(A)	0.4	0.35	0.3	0.28	1.0

■Absolute Maximum Ratings

Parameter	Symbol	Ratings			Unit
		SI-8201L/8203L	SI-8211L/8213L	SI-8301L	
DC Input Voltage	V_{IN}	45	60	45	V
Power Dissipation	P_D	1.5	1.17	3.0	W
Junction Temperature	T_j	+100			°C
Storage Temperature	T_{stg}	-25 to +85			°C

■Recommended Operating Conditions

Parameter	Symbol	Ratings					Unit
		SI-8201L	SI-8203L	SI-8211L	SI-8213L	SI-8301L	
DC Input Voltage Range	V_{IN}	10 to 40	16 to 40	15 to 55	22 to 55	8 to 40	V
Output Current Range	I_o	0 to 0.4	0 to 0.35	0 to 0.3	0 to 0.28	0 to 1.0	A
Operating Temperature Range	T_{op}	-10 to +65			-10 to +85		°C


■Electrical Characteristics

(Ta=25°C)


Parameter	Symbol	Ratings															Unit
		SI-8201L			SI-8203L			SI-8211L			SI-8213L			SI-8301L			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Output Voltage	V _O	4.9	5.0	5.1	11.8	12.0	12.2	4.9	5.0	5.1	11.8	12.0	12.2	5.0	5.1	5.2	V
	Conditions	V _{IN} =15V, I _O =0.2A			V _{IN} =25V, I _O =0.2A			V _{IN} =35V, I _O =0.2A			V _{IN} =38V, I _O =0.2A			V _{IN} =15V, I _O =0.5A			
Efficiency	η		73			79			63			78			73		%
	Conditions	V _{IN} =15V, I _O =0.2A			V _{IN} =25V, I _O =0.2A			V _{IN} =35V, I _O =0.2A			V _{IN} =38V, I _O =0.2A			V _{IN} =15V, I _O =0.5A			
Switching Frequency	f	25			25			25			25				25		kHz
Line Regulation	ΔV _O LINE		15	60		15	60			60			60			50	mV
	Conditions	V _{IN} =10 to 20V, I _O =0.2A			V _{IN} =16 to 34V, I _O =0.2A			V _{IN} =20 to 50V, I _O =0.2A			V _{IN} =22 to 50V, I _O =0.2A			V _{IN} =10 to 20V, I _O =0.5A			
Load Regulation	ΔV _O LOAD		15	60		60	100			60			60			80	mV
	Conditions	V _{IN} =15V, I _O =0.02 to 0.25A			V _{IN} =25V, I _O =0.02 to 0.3A			V _{IN} =35V, I _O =0.02 to 0.3A			V _{IN} =38V, I _O =0.02 to 0.28A			V _{IN} =15V, I _O =0.3 to 0.7A			
Temperature Coefficient of Output Voltage	ΔV _O /ΔT _a			±1.5			±1.5			±1.5			±1.5			±1.5	mV/°C
Switching Ripple	ΔV _r		30	60		60	100		30	60		50	100		45		mV _{p-p}
Voltage (C2=470μF)	Conditions	V _{IN} =25V, I _O =0.3A			V _{IN} =40V, I _O =0.35A			V _{IN} =48V, I _O =0.3A			V _{IN} =48V, I _O =0.28A			V _{IN} =15V, I _O =0.5A			

■Outline Drawing


(unit: mm)




■Block Diagram



■Standard External Circuit



■Ta-PD Characteristics



■Caution


1. A low-impedance capacitor suitable for switching applications must be used for the external capacitor and must be connected as close to the IC as possible in order to assure low ripple voltage and stable switching operation.
2. The SI-8200L and 8300L series do not have a built-in overcurrent protection circuit. Thus, avoid short-circuit conditions that may cause an overcurrent.
3. The SI-8300L series may not start up if the input voltage rises too rapidly.
Do not use the SI-8300L series in applications where the input terminal, pin6, is opened and closed directly in a state where the input voltage is already applied.
4. Terminals LIN and NC in the connection diagram must be left unconnected to other circuits.
5. The IC's metallic heatsink is electrically floating. Do not connect it to GND or any other circuit.
6. Since the SI-8200L and 8300L series have an open-package construction, they can only be used in specific environments. Verify the operating environment and use the IC within the conditions indicated in the reliability data.

■Typical Characteristics


($T_a=25^\circ\text{C}$)

SI-8201L

Rise Characteristics




Efficiency Characteristics




SI-8203L

Rise Characteristics




Efficiency Characteristics




SI-8211L

Rise Characteristics




Efficiency Characteristics




SI-8213L

Rise Characteristics




Efficiency Characteristics



SI-8301L

Rise Characteristics



Efficiency Characteristics

