

Absolute maximum ratings

(Ta=25°C)

Symbol	Ratings	Unit
V _{DSS}	250	V
V _{GSS}	±20	V
I _D	7	A
I _{D(pulse)}	15 (PW≤1ms, Du≤1%)	A
E _{AS} *	55	mJ
I _{AS}	7	A
P _T	5 (Ta=25°C, with all circuits operating, without heatsink)	W
	40 (Tc=25°C, with all circuits operating, with infinite heatsink)	
θ _{J-a}	25 (Junction-Air, Ta=25°C, with all circuits operating)	°C/W
θ _{J-c}	3.125 (Junction-Case, Tc=25°C, with all circuits operating)	°C/W
T _{ch}	150	°C
T _{stg}	-40 to +150	°C


* : V_{DD}=25V, L=2mH, I_D=7A, unclamped, R_G=50Ω, see Fig. E on page 15.

Electrical characteristics








(Ta=25°C)

Symbol	Specification			Unit	Conditions
	min	typ	max		
V _{(BR)DSS}	250			V	I _D =100μA, V _{GS} =0V
I _{GSS}			±100	nA	V _{GS} =±20V
I _{DSS}			100	μA	V _{DS} =250V, V _{GS} =0V
V _{TH}	2.0		4.0	V	V _{DS} =10V, I _D =1mA
Re _(yfs)	2.5	5.0		S	V _{DS} =10V, I _D =3.5A
R _{DS(ON)}		400	500	mΩ	V _{GS} =10V, I _D =3.5A
C _{iss}		450		pF	V _{DS} =10V, f=1.0MHz, V _{GS} =0V
C _{oss}		280		pF	
td(on)		20		ns	I _D =3.5A, V _{DD} =100V, R _L =28.6Ω, V _{GS} =10V, see Fig. 3 on page 16.
tr		30		ns	
td(off)		55		ns	
tr		75		ns	
V _{SD}		1.0	1.5	V	I _{SD} =7A, V _{GS} =0V
trr		75		ns	I _{SD} =3.5A, V _{GS} =0V, di/dt=100A/μs


Equivalent circuit diagram



Characteristic curves

I_D-V_{DS} Characteristics (Typical)I_D-V_{GS} Characteristics (Typical)R_{DS(ON)}-I_D Characteristics (Typical)Re_(yfs)-I_D Characteristics (Typical)R_{DS(ON)}-T_C Characteristics (Typical)Capacitance-V_{DS} Characteristics (Typical)I_{DR}-V_{SD} Characteristics (Typical)

Safe Operating Area (SOA)

P_T-T_a Characteristics