

TOSHIBA PHOTOCOUPLER GaAs IRED & PHOTO-MOS FET

TLP3110

MEASUREMENT INSTRUMENTS


LOGIC IC TESTERS/MEMORY TESTERS

BOARD TESTERS/SCANNERS

Unit in mm


The TOSHIBA MINI FLAT PHOTO RELAY TLP3110 is a small outline photo relay, suitable for surface mount assembly. The TLP3110 consists of a GaAs infrared emitting diode optically coupled to a photo-MOSFET in a 4 pin lead package (MFSOP6), and has characteristics of small off-state current and small output terminal capacitance, which enable the TLP3110 to be applied to measurement instruments.

- 1-Form-A
- Peak Off-State Voltage : 60 V (MIN.)
- Trigger LED Current : 4 mA (MAX.)
- On-State Current : 350 mA (MAX.)
- On-State Resistance : 1.2 Ω (MAX.)
- Isolation Voltage : 1500 V_{rms} (MIN.)



Weight : 0.1 g

PIN CONFIGURATION (TOP VIEW)



- 1 : ANODE
 3 : CATHODE
 4 : DRAIN
 6 : DRAIN

980910EBC1

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- Gallium arsenide (GaAs) is a substance used in the products described in this document. GaAs dust and fumes are toxic. Do not break, cut or pulverize the product, or use chemicals to dissolve them. When disposing of the products, follow the appropriate regulations. Do not dispose of the products with other industrial waste or with domestic garbage.
- The products described in this document are subject to the foreign exchange and foreign trade laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
LED	Forward Current	I _F	50	mA
	Reverse Voltage	V _R	6	V
	Junction Temperature	T _j	125	°C
DETECTOR	Off-State Output Voltage	V _{OFF}	60	V
	On-State Current	I _{ON}	350	mA
	Junction Temperature	T _j	125	°C
Storage Temperature		T _{stg}	−40~125	°C
Operating Temperature		T _{opr}	−20~85	°C
Lead Soldering Temperature (10 s)		T _{sol}	260	°C
Isolation Voltage (AC, 1 min., R.H. ≤ 60%) (Note 1)		BV _S	1500	V _{rms}

(Note 1) : Device considered a two-terminal device : Pins 1 and 3 shorted together, and pins 4 and 6 shorted together.

RECOMMENDED OPERATING CONDITIONS

CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNIT
Supply Voltage	V _{OFF}	—	—	48	V
Forward Current	I _F	10	—	30	mA
On-State Current	I _{ON}	—	—	350	mA
Operating Temperature	T _{opr}	25	—	50	°C

INDIVIDUAL ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
LED	Forward Voltage	V _F	I _F = 20 mA	1.0	1.2	1.4	V
	Reverse Voltage	I _R	V _R = 6 V	—	—	10	μA
	Capacitance	C _T	V = 0, f = 1 MHz	—	15	—	pF
DETECTOR	Off-State Current	I _{OFF}	V _{OFF} = 30 V, Ta = 50°C	—	0.4	1	nA
	Capacitance	C _{OFF}	V = 0, f = 1 MHz	—	100	150	pF

COUPLED ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Trigger LED Current	I _{FT}	I _{ON} = 350 mA	—	—	4	mA
ON-State Resistance	R _{ON}	I _{ON} = 350 mA, I _F = 5 mA	—	0.9	1.2	Ω

ISOLATION CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Capacitance Input to Output	CS	VS = 0 V, f = 1 MHz	—	0.8	—	pF
Isolation Resistance	RS	VS = 500 V, R.H. ≤ 60%	5×10^{10}	10^{14}	—	Ω
Isolation Voltage	BVS	AC, 1 minute	1500	—	—	Vrms
		AC, 1 second (in oil)	—	3000	—	
		DC, 1 minute (in oil)	—	3000	—	Vdc

SWITCHING CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Turn-ON Time	tON	RL = 200 Ω (Note 2)	—	—	1	ms
Turn-OFF Time	tOFF	VDD = 20 V, IF = 10 mA	—	—	1	

(Note 2) : SWITCHING TIME TEST CIRCUIT

