

Description

The μ PD4464 is a high-speed 8,192-word by 8-bit static RAM fabricated with advanced silicon-gate technology. Full CMOS storage cells with six transistors make the μ PD4464 a very low-power device that requires no clock or refreshing to operate.

Two chip enable pins are provided for battery backup application, and an output enable pin is included for easy interface. Data retention is guaranteed at a power supply voltage as low as 2 volts.

The μ PD4464 is available in standard 28-pin plastic DIP or miniflat packaging.

Features


- Operating temperature range: -40 to 85°C
- Single $+5$ -volt power supply
- Fully static operation — no clock or refreshing required
- TTL-compatible inputs and outputs
- Common I/O using three-state output
- One output enable pin and two chip enable pins for easy application
- Data retention voltage: 2 V minimum
- Standard 28-pin plastic DIP or miniflat packaging

Ordering Information

Part Number	Access Time (max)	Active Current (max)	Standby Current (max)	Package
μ PD4464C-12	120 ns	40 mA	10 μA	28-pin plastic DIP
C-15	150 ns	40 mA		
C-20	200 ns	35 mA		
μ PD4464C-12L	120 ns	40 mA	1 μA (at $T_A = 60^{\circ}\text{C}$)	28-pin plastic DIP
C-15L	150 ns	40 mA		
C-20L	200 ns	35 mA		
μ PD4464G-12	120 ns	40 mA	10 μA	28-pin plastic miniflat
G-15	150 ns	40 mA		
G-20	200 ns	35 mA		
μ PD4464G-12L	120 ns	40 mA	1 μA (at $T_A = 60^{\circ}\text{C}$)	28-pin plastic miniflat
G-15L	150 ns	40 mA		
G-20L	200 ns	35 mA		

Pin Configuration

28-Pin Plastic DIP or Miniflat



Pin Identification

Symbol	Function
A_0 - A_{12}	Address inputs
I/O ₁ -I/O ₈	Data inputs/outputs
CE ₁	Chip enable (active low)
CE ₂	Chip enable (active high)
OE	Output enable
WE	Write enable
GND	Ground
VCC	+5-volt power supply
NC	No connection

Absolute Maximum Ratings


Power supply voltage, V_{CC} (Note 1)	-0.5 to $+7.0$ V
Input voltage, V_{IN} (Note 1)	-0.5 to $V_{CC} + 0.5$ V
Output voltage, V_{OUT} (Note 1)	-0.5 to $V_{CC} + 0.5$ V
Operating temperature, T_{OPR}	-40 to 85°C
Storage temperature, T_{STG}	-55 to 125°C
Power dissipation, P_D	1.0 W

Notes:

(1) -3.0 V minimum (pulse width = 50 ns maximum)

Comment: Exposure to Absolute Maximum Ratings for extended periods may affect device reliability; exceeding the ratings could cause permanent damage. The device should be operated within the limits specified under DC and AC Characteristics.

Block Diagram



Recommended DC Operating Conditions

T_A = -40 to 85°C

Parameter	Symbol	Limits			Unit
		Min	Typ	Max	
Supply voltage	V _{CC}	4.5	5.0	5.5	V
Input voltage, low (Note 1)	V _{IL}	-0.3		0.8	V
Input voltage, high	V _{IH}	2.2		V _{CC} + 0.5	V

Notes:

(1) -3.0 V minimum (pulse width = 50 ns maximum)

Capacitance

T_A = 25°C; f = 1.0 MHz

Parameter	Symbol	Limits			Unit	Test Conditions
		Min	Typ	Max		
Input capacitance	C _{IN}		6		pF	V _{IN} = 0 V
I/O capacitance	C _{I/O}		8		pF	V _{I/O} = 0 V

DC Characteristics

T_A = -40 to 85°C; V_{CC} = +5.0 V ±10%

Parameter	Symbol	Limits			Unit	Test Conditions
		Min	Typ	Max		
Input leakage current	I _{LI}			1	μA	V _{IN} = 0 V to V _{CC}
I/O leakage current	I _{LO}			1	μA	V _{I/O} = 0 V to V _{CC} CE ₁ = V _{IH} or CE ₂ = V _{IL} or OE = V _{IH} or WE = V _{IL}
Operating supply current	I _{CCA1}			40	mA	CE = V _{IL} ; CE ₂ = V _{IH} ; I _{I/O} = 0 (min cycle)
	I _{CCA2}		5	10	mA	CE = V _{IL} ; CE ₂ = V _{IH} ; I _{I/O} = 0 (dc current)
Standby supply current	I _{CCS1}		0.004	10	μA	CE ≥ V _{CC} - 0.2 V; CE ₂ ≥ V _{CC} - 0.2 V
	I _{CCS2}		0.004	10	μA	CE ₂ ≤ 0.2 V
Output voltage, low	V _{OL}			0.4	V	I _{OL} = 2.1 mA
Output voltage, high	V _{OH}	2.4			V	I _{OH} = -1.0 mA

Notes:

(1) μPD4464-20/-20L: 35 mA max

(2) μPD4464-12L/-15L/-20L: 1.0 μA max (-40 to 60°C)
0.2 μA max (-40 to 25°C)

Truth Table

CE ₁	CE ₂	OE	WE	Mode	I/O	I _{CC}
H	X	X	X	Not selected	High-Z	Standby
X	L	X	X	Not selected	High-Z	Standby
L	H	H	H	D _{OUT} disabled	High-Z	Active
L	H	L	H	Read	D _{OUT}	Active
L	H	X	L	Write	D _{IN}	Active

Notes:

(1) X = don't care

AC Characteristics

$T_A = -40$ to 85 °C; $V_{CC} = +5.0$ V $\pm 10\%$

Parameter	Symbol	Limits						Unit	Test Conditions (Note 1)
		μPD4464-12		μPD4464-15		μPD4464-20			
		Min	Max	Min	Max	Min	Max		
Read Cycle									
Read cycle time	t_{RC}	120		150		200		ns	
Address access time	t_{AA}		120		150		200	ns	
\overline{CE}_1 access time	t_{C01}		120		150		200	ns	
CE_2 access time	t_{C02}		120		150		200	ns	
Output enable to output valid	t_{OE}		60		75		100	ns	
Output hold from address change	t_{OH}	10		10		10		ns	
Chip enable (\overline{CE}_1) to output in low-Z	t_{LZ1}	10		10		100		ns	
Chip enable (CE_2) to output in low-Z	t_{LZ2}	10		10		10		ns	
Output enable to output in low-Z	t_{OLZ}	5		5		5		ns	
Chip enable (\overline{CE}_1) to output in high-Z	t_{HZ1}		40		75		100	ns	
Chip enable (CE_2) to output in high-Z	t_{HZ2}		40		75		100	ns	
Output enable to output in high-Z	t_{OHZ}		40		60		80	ns	
Write Cycle									
Write cycle time	t_{WC}	120		150		200		ns	
Chip enable (\overline{CE}_1) to end of write	t_{CW1}	85		130		180		ns	
Chip enable (CE_2) to end of write	t_{CW2}	85		130		180		ns	
Address valid to end of write	t_{AW}	85		130		180		ns	
Address setup time	t_{AS}	0		0		0		ns	
Write pulse width	t_{WP}	70		100		140		ns	
Write recovery time	t_{WR}	5		5		5		ns	
Data valid to end of write	t_{DW}	50		70		80		ns	
Data hold time	t_{DH}	5		5		5		ns	
Write enable to output in high-Z	t_{WHZ}		40		75		100	ns	
Output active from end of write	t_{OW}	5		10		10		ns	

Notes:

- (1) Input pulse levels = 0.8 V to 2.4 V; input pulse rise and fall times = 5 ns; timing reference levels = 1.5 V; output load = 1 TTL gate and $C_L = 100$ pF.

6