





## ■ Dimensions

D×L(mm)

Cap.(μF)	Code	V(Code)		6.3 (0J)		10 (1A)		16(1C)		25(1E)		35(1V)	
		Size code		—	6	—	6	—	6	—	6	—	6
22	220												5×11
27	270												5×11
33	330										5×11		6.3×11
39	390										5×11		6.3×11
47	470								5×11		6.3×11		6.3×11
56	560								5×11		6.3×11		6.3×11
68	680						5×11		6.3×11		6.3×11		6.3×15
82	820						5×11		6.3×11		6.3×11		6.3×15
100	101		5×11				6.3×11		6.3×11		6.3×15		8×11.5
120	121		5×11				6.3×11		6.3×11		6.3×15		8×15
150	151		6.3×11				6.3×11		6.3×15		8×11.5		8×15
180	181		6.3×11				6.3×11		6.3×15		8×15	10×12.5	8×20
220	221		6.3×11				6.3×15		8×11.5		8×15	10×12.5	8×20
270	271		6.3×15				6.3×15		8×15	10×12.5	8×20	10×15	10×20
330	331		6.3×15				8×11.5		8×15	10×12.5	8×20	10×15	10×20
390	391		8×11.5				8×15	10×12.5	8×20	10×15	10×20	12.5×15	10×25
470	471		8×15	10×12.5			8×15	10×12.5	8×20	10×15	10×20	12.5×15	10×31.5
560	561		8×15	10×12.5			8×20	10×15	10×20	12.5×15	10×25	12.5×15	12.5×20
680	681		8×20	10×15			8×20	10×15	10×20	12.5×15	10×31.5	16×15	12.5×25
820	821		8×20	10×15			10×20	12.5×15	10×25	12.5×15	12.5×20	16×15	12.5×25
1000	102		10×20	12.5×15			10×20	12.5×15	10×31.5	16×15	12.5×25	18×15	12.5×31.5
1200	122		10×20	12.5×15			10×25	12.5×15	12.5×20	16×15	12.5×25	18×15	12.5×35.5
1500	152		10×25	12.5×15			10×31.5	16×15	12.5×25	18×15	12.5×31.5	16×20	12.5×40
1800	182		10×31.5	16×15			12.5×20	16×15	12.5×31.5	16×20	12.5×35.5	16×25	16×31.5
2200	222		10×31.5	16×15			12.5×25	18×15	12.5×31.5	16×20	12.5×40	18×20	16×35.5
2700	272		12.5×25	18×15			12.5×31.5	16×20	12.5×35.5	16×25	16×31.5	18×25	16×40
3300	332		12.5×25	18×15			12.5×35.5	16×20	12.5×40	18×20	16×35.5	18×31.5	18×40
3900	392		12.5×31.5	16×20			12.5×40	18×20	16×31.5	18×25	16×40	18×35.5	
4700	472		12.5×35.5	18×20			16×31.5	18×25	16×35.5	18×31.5	18×40		
5600	562		12.5×40	18×20			16×35.5	18×25	16×40	18×35.5			
6800	682		16×31.5	18×25			16×35.5	18×31.5	18×35.5				
8200	822		16×35.5	18×31.5			16×40		18×40				
10000	103		16×40	18×31.5			18×40						
12000	123		18×35.5										
15000	153		18×40										

Cap.(μF)	Code	V(Code)		50 (1H)		63 (1J)		80 (1K)		100 (2A)	
		Size code		—	6	—	6	—	6	—	6
0.47	R47		5×11								5×11
0.68	R68		5×11								5×11
1	O10		5×11								5×11
1.5	1R5		5×11								5×11
2.2	2R2		5×11								5×11
3.3	3R3		5×11								5×11
4.7	4R7		5×11						5×11		6.3×11
6.8	6R8		5×11						5×11		6.3×11
10	100		5×11				5×11		6.3×11		6.3×11
12	120		5×11				5×11		6.3×11		6.3×11
15	150		5×11				6.3×11		6.3×11		6.3×15
18	180		5×11				6.3×11		6.3×11		6.3×15
22	220		6.3×11				6.3×11		6.3×15		8×11.5
27	270		6.3×11				6.3×11		6.3×15		8×15
33	330		6.3×11				6.3×15		8×11.5		8×15
39	390		6.3×11				6.3×15		8×15	10×12.5	8×20
47	470		6.3×15				8×11.5		8×15	10×12.5	10×20
56	560		6.3×15				8×15	10×12.5	8×20	10×15	10×20
68	680		8×11.5				8×15	10×12.5	10×20	12.5×15	10×25
82	820		8×15	10×12.5			8×20	10×15	10×20	12.5×15	10×31.5
100	101		8×20	10×15			10×20	12.5×15	10×25	12.5×15	10×31.5
120	121		8×20	10×15			10×20	12.5×15	10×31.5	16×15	12.5×25
150	151		10×20	12.5×15			10×25	12.5×15	10×31.5	16×15	12.5×25
180	181		10×20	12.5×15			10×31.5	16×15	12.5×25	16×15	12.5×31.5
220	221		10×25	12.5×15			12.5×20	16×15	12.5×31.5	18×15	12.5×35.5
270	271		10×31.5	16×15			12.5×25	18×15	12.5×31.5	16×20	12.5×40
330	331		10×31.5	16×15			12.5×25	18×15	12.5×35.5	16×25	16×31.5
390	391		12.5×25	16×15			12.5×31.5	16×20	12.5×40	18×20	16×35.5
470	471		12.5×25	18×15			12.5×35.5	16×25	16×31.5	18×25	16×40
560	561		12.5×31.5	16×20			12.5×40	18×20	16×35.5	18×31.5	18×35.5
680	681		12.5×35.5	16×20			16×31.5	18×25	16×40	18×31.5	18×40
820	821		12.5×40	18×20			16×35.5	18×31.5	18×35.5		
1000	102		16×31.5	18×25			16×40	18×35.5	18×40		
1200	122		16×35.5	18×31.5			18×40				
1500	152		16×40	18×31.5							
1800	182		18×35.5								
2200	222		18×40								

※In case of low profile type, [6] will be put at 12th digit of type numbering system.

Dimension table for 160-450V products are shown in 92 page.

## Standard ratings

V(Code) Size code		6.3(0J)										
		Item	Case size φD×L (mm)	—				6				
				Impedance(ΩMAX)		Rated ripple(mA rms)		Case size φD×L (mm)	Impedance(ΩMAX)		Rated ripple(mA rms)	
				20°C/100kHz	-10°C/100kHz	105°C/10kHz~ 200kHz	105°C/120Hz		20°C/100kHz	-10°C/100kHz	105°C/10kHz~ 200kHz	105°C/120Hz
100	101	5×11	0.85	1.70	150	99						
120	121	5×11	0.65	1.30	175	115						
150	151	6.3×11	0.49	0.98	225	155						
180	181	6.3×11	0.39	0.78	250	175						
220	221	6.3×11	0.30	0.60	285	205						
270	271	6.3×15	0.24	0.48	370	275						
330	331	6.3×15	0.20	0.40	405	310						
390	391	8×11.5	0.17	0.34	445	345						
470	471	8×15	0.14	0.28	550	435	10×12.5	0.14	0.28	575	455	
560	561	8×15	0.12	0.24	595	480	10×12.5	0.13	0.26	600	485	
680	681	8×20	0.10	0.20	730	605	10×15	0.11	0.22	700	580	
820	821	8×20	0.085	0.17	795	670	10×15	0.095	0.19	750	635	
1000	102	10×20	0.075	0.15	950	820	12.5×15	0.085	0.17	890	765	
1200	122	10×20	0.065	0.13	1020	895	12.5×15	0.075	0.15	950	835	
1500	152	10×25	0.055	0.11	1220	1090	12.5×15	0.065	0.13	1020	915	
1800	182	10×31.5	0.050	0.10	1370	1230	16×15	0.055	0.11	1270	1140	
2200	222	10×31.5	0.043	0.086	1470	1320	16×15	0.049	0.098	1340	1200	
2700	272	12.5×25	0.038	0.076	1590	1430	18×15	0.044	0.088	1500	1350	
3300	332	12.5×25	0.034	0.068	1710	1530	18×15	0.039	0.078	1600	1440	
3900	392	12.5×31.5	0.031	0.062	1910	1710	16×20	0.036	0.072	1720	1540	
4700	472	12.5×35.5	0.028	0.056	2100	1890	18×20	0.032	0.064	1920	1720	
5600	562	12.5×40	0.026	0.052	2270	2040	18×20	0.030	0.060	1980	1780	
6800	682	16×31.5	0.024	0.048	2370	2130	18×25	0.027	0.054	2210	1980	
8200	822	16×35.5	0.022	0.044	2550	2290	18×31.5	0.025	0.050	2390	2150	
10000	103	16×40	0.020	0.040	2750	2470	18×31.5	0.023	0.046	2490	2240	
12000	123	18×35.5	0.019	0.038	2820	2530						
15000	153	18×40	0.018	0.036	2960	2660						

V(Code) Size code		10(1A)										
		Item	Case size φD×L (mm)	—				6				
				Impedance(ΩMAX)		Rated ripple(mA rms)		Case size φD×L (mm)	Impedance(ΩMAX)		Rated ripple(mA rms)	
				20°C/100kHz	-10°C/100kHz	105°C/10kHz~ 200kHz	105°C/120Hz		20°C/100kHz	-10°C/100kHz	105°C/10kHz~ 200kHz	105°C/120Hz
68	680	5×11	0.80	1.60	155	97						
82	820	5×11	0.65	1.30	175	110						
100	101	6.3×11	0.55	1.10	210	135						
120	121	6.3×11	0.44	0.88	235	160						
150	151	6.3×11	0.35	0.70	265	185						
180	181	6.3×11	0.29	0.58	290	205						
220	221	6.3×15	0.24	0.48	370	270						
270	271	6.3×15	0.20	0.40	405	300						
330	331	8×11.5	0.16	0.32	460	350						
390	391	8×15	0.14	0.28	550	430	10×12.5	0.15	0.30	555	430	
470	471	8×15	0.12	0.24	595	475	10×12.5	0.13	0.26	600	475	
560	561	8×20	0.10	0.20	730	590	10×15	0.11	0.22	700	565	
680	681	8×20	0.085	0.17	795	660	10×15	0.090	0.18	770	635	
820	821	10×20	0.070	0.14	985	835	12.5×15	0.080	0.16	920	780	
1000	102	10×20	0.060	0.12	1060	915	12.5×15	0.065	0.13	1040	895	
1200	122	10×25	0.050	0.10	1280	1120	12.5×15	0.060	0.12	1060	930	
1500	152	10×31.5	0.045	0.090	1440	1290	16×15	0.050	0.10	1330	1190	
1800	182	12.5×20	0.039	0.078	1470	1320	16×15	0.044	0.088	1420	1270	
2200	222	12.5×25	0.034	0.068	1710	1530	18×15	0.039	0.078	1600	1440	
2700	272	12.5×31.5	0.030	0.060	1940	1740	16×20	0.035	0.070	1740	1560	
3300	332	12.5×35.5	0.026	0.052	2180	1960	16×20	0.031	0.062	1850	1660	
3900	392	12.5×40	0.024	0.048	2360	2120	18×20	0.028	0.056	2050	1840	
4700	472	16×31.5	0.023	0.046	2420	2170	18×25	0.026	0.052	2250	2020	
5600	562	16×35.5	0.021	0.042	2610	2340	18×25	0.024	0.048	2340	2100	
6800	682	16×35.5	0.020	0.040	2680	2410	18×31.5	0.022	0.044	2540	2280	
8200	822	16×40	0.019	0.038	2820	2530	18×35.5	0.021	0.042	2690	2420	
10000	103	18×40	0.017	0.034	3040	2730						

※ In case of low profile type, [6] will be put at 12th digit of type numbering system.

■ Standard ratings

V(Code) Size Code Item Cap.(μF) Code		16(1C)									
		—					6				
		Case size ΦD×L (mm)	Impedance(ΩMAX)		Rated ripple(mA rms)		Case size ΦD×L (mm)	Impedance(ΩMAX)		Rated ripple(mA rms)	
20°C/100kHz	−10°C/100kHz		105°C/100kHz	105°C/120Hz	20°C/100kHz	−10°C/100kHz		105°C/100kHz	105°C/120Hz		
47	470	5×11	0.80	1.60	155	92					
56	560	5×11	0.65	1.30	175	105					
68	680	6.3×11	0.50	1.00	220	135					
82	820	6.3×11	0.42	0.84	240	155					
100	101	6.3×11	0.35	0.70	265	175					
120	121	6.3×11	0.29	0.58	290	195					
150	151	6.3×15	0.23	0.46	375	260					
180	181	6.3×15	0.20	0.40	405	285					
220	221	8×11.5	0.16	0.32	460	335					
270	271	8×15	0.14	0.28	550	410	10×12.5	0.14	0.28	575	430
330	331	8×15	0.12	0.24	595	455	10×12.5	0.12	0.24	625	480
390	391	8×20	0.10	0.20	730	570	10×15	0.10	0.20	730	570
470	471	8×20	0.090	0.18	770	615	10×15	0.090	0.18	770	615
560	561	10×20	0.075	0.15	950	770	12.5×15	0.080	0.16	920	745
680	681	10×20	0.065	0.13	1020	845	12.5×15	0.070	0.14	985	815
820	821	10×25	0.055	0.11	1220	1030	12.5×15	0.060	0.12	1060	895
1000	102	10×31.5	0.047	0.094	1410	1210	16×15	0.055	0.11	1270	1090
1200	122	12.5×20	0.041	0.082	1430	1250	16×15	0.046	0.092	1390	1220
1500	152	12.5×25	0.036	0.072	1660	1490	18×15	0.041	0.082	1560	1400
1800	182	12.5×31.5	0.032	0.064	1880	1690	16×20	0.037	0.074	1700	1530
2200	222	12.5×31.5	0.028	0.056	2010	1800	16×20	0.033	0.066	1800	1620
2700	272	12.5×35.5	0.025	0.050	2220	1990	16×25	0.030	0.060	2010	1800
3300	332	12.5×40	0.023	0.046	2410	2160	18×20	0.027	0.054	2090	1880
3900	392	16×31.5	0.022	0.044	2470	2220	18×25	0.025	0.050	2290	2060
4700	472	16×35.5	0.020	0.040	2680	2410	18×31.5	0.023	0.046	2490	2240
5600	562	16×40	0.019	0.038	2820	2530	18×35.5	0.022	0.044	2620	2350
6800	682	18×35.5	0.018	0.036	2900	2610					
8200	822	18×40	0.017	0.034	3040	2730					

V(Code) Size Code Item Cap.(μF) Code		25(1E)									
		—					6				
		Case size ΦD×L (mm)	Impedance(ΩMAX)		Rated ripple(mA rms)		Case size ΦD×L (mm)	Impedance(ΩMAX)		Rated ripple(mA rms)	
20°C/100kHz	−10°C/100kHz		105°C/100kHz	105°C/120Hz	20°C/100kHz	−10°C/100kHz		105°C/100kHz	105°C/120Hz		
33	330	5×11	0.80	1.60	155	88					
39	390	5×11	0.65	1.30	175	100					
47	470	6.3×11	0.55	1.10	210	125					
56	560	6.3×11	0.44	0.88	235	140					
68	680	6.3×11	0.36	0.72	260	160					
82	820	6.3×11	0.30	0.60	285	180					
100	101	6.3×15	0.24	0.48	370	245					
120	121	6.3×15	0.20	0.40	405	275					
150	151	8×11.5	0.16	0.32	460	320					
180	181	8×15	0.14	0.28	550	390	10×12.5	0.15	0.30	555	395
220	221	8×15	0.11	0.22	625	455	10×12.5	0.13	0.26	600	435
270	271	8×20	0.095	0.19	750	560	10×15	0.11	0.22	700	525
330	331	8×20	0.085	0.17	795	610	10×15	0.095	0.19	750	575
390	391	10×20	0.070	0.14	985	770	12.5×15	0.080	0.16	920	720
470	471	10×20	0.065	0.13	1020	810	12.5×15	0.070	0.14	985	785
560	561	10×25	0.055	0.11	1220	990	12.5×15	0.060	0.12	1060	860
680	681	10×31.5	0.046	0.092	1420	1180	16×15	0.055	0.11	1270	1050
820	821	12.5×20	0.041	0.082	1430	1210	16×15	0.049	0.098	1340	1130
1000	102	12.5×25	0.036	0.072	1660	1430	18×15	0.043	0.086	1520	1310
1200	122	12.5×25	0.032	0.064	1760	1550	18×15	0.039	0.078	1600	1400
1500	152	12.5×31.5	0.029	0.058	1980	1780	16×20	0.034	0.068	1770	1590
1800	182	12.5×35.5	0.026	0.052	2180	1960	16×25	0.031	0.062	1980	1780
2200	222	12.5×40	0.024	0.048	2360	2120	18×20	0.028	0.056	2050	1840
2700	272	16×31.5	0.022	0.044	2470	2220	18×25	0.025	0.050	2290	2060
3300	332	16×35.5	0.020	0.040	2680	2410	18×31.5	0.023	0.046	2490	2240
3900	392	16×40	0.019	0.038	2820	2530	18×35.5	0.021	0.042	2690	2420
4700	472	18×40	0.018	0.036	2960	2660					

※ In case of low profile type, 6 will be put at 12th digit of type numbering system.

**PM** series

■ Standard ratings

V(Code) Size code		35(1V)										
		Item	Case size ΦD×L (mm)	Impedance(Ω MAX.)		Rated ripple(mA rms)		Case size ΦD×L (mm)	Impedance(Ω MAX.)		Rated ripple(mA rms)	
				20°C/100kHz	-10°C/100kHz	105°C/100kHz 10kHZ~200kHz	105°C/120Hz		20°C/100kHz	-10°C/100kHz	105°C/100kHz 10kHZ~200kHz	105°C/120Hz
22	220	5×11	0.75	1.50	160	85						
27	270	5×11	0.60	1.20	180	99						
33	330	6.3×11	0.49	0.98	225	125						
39	390	6.3×11	0.41	0.82	245	140						
47	470	6.3×11	0.34	0.68	270	160						
56	560	6.3×11	0.28	0.56	295	180						
68	680	6.3×15	0.24	0.48	370	230						
82	820	6.3×15	0.19	0.38	415	265						
100	101	8×11.5	0.16	0.32	460	305						
120	121	8×15	0.14	0.28	550	370	10×12.5	0.15	0.30	555	375	
150	151	8×15	0.12	0.24	595	415	10×12.5	0.12	0.24	625	435	
180	181	8×20	0.10	0.20	730	520	10×15	0.11	0.22	700	500	
220	221	8×20	0.085	0.17	795	580	10×15	0.090	0.18	770	560	
270	271	10×20	0.070	0.14	985	735	12.5×15	0.080	0.16	920	690	
330	331	10×20	0.060	0.12	1060	810	12.5×15	0.065	0.13	1020	780	
390	391	10×25	0.055	0.11	1220	955	12.5×15	0.060	0.12	1060	825	
470	471	10×31.5	0.046	0.092	1420	1130	16×15	0.055	0.11	1270	1010	
560	561	12.5×20	0.041	0.082	1430	1160	16×15	0.048	0.096	1360	1100	
680	681	12.5×25	0.036	0.072	1660	1370	18×15	0.042	0.084	1540	1270	
820	821	12.5×25	0.032	0.064	1760	1490	18×15	0.038	0.076	1620	1370	
1000	102	12.5×31.5	0.029	0.058	1980	1710	16×20	0.034	0.068	1770	1530	
1200	122	12.5×35.5	0.026	0.052	2180	1920	16×25	0.031	0.062	1980	1740	
1500	152	12.5×40	0.024	0.048	2360	2120	18×20	0.028	0.056	2050	1840	
1800	182	16×31.5	0.022	0.044	2470	2220	18×25	0.025	0.050	2290	2060	
2200	222	16×35.5	0.020	0.040	2680	2410	18×31.5	0.023	0.046	2490	2240	
2700	272	16×40	0.018	0.036	2900	2610	18×35.5	0.021	0.042	2690	2420	
3300	332	18×40	0.017	0.034	3040	2730						

V(Code) Size code		50(1H)										
		Item	Case size ΦD×L (mm)	Impedance(Ω MAX.)		Rated ripple(mA rms)		Case size ΦD×L (mm)	Impedance(Ω MAX.)		Rated ripple(mA rms)	
				20°C/100kHz	-10°C/100kHz	105°C/100kHz 10kHZ~200kHz	105°C/120Hz		20°C/100kHz	-10°C/100kHz	105°C/100kHz 10kHZ~200kHz	105°C/120Hz
0.47	R47	5×11	23.0	46.0	22	11						
0.68	R68	5×11	16.0	32.0	28	14						
1	010	5×11	11.0	22.0	36	18						
1.5	1R5	5×11	7.50	15.0	45	22						
2.2	2R2	5×11	5.00	10.0	54	27						
3.3	3R3	5×11	3.30	6.60	66	33						
4.7	4R7	5×11	2.20	4.40	81	40						
6.8	6R8	5×11	1.80	3.60	91	45						
10	100	5×11	1.40	2.80	115	57						
12	120	5×11	1.20	2.40	125	62						
15	150	5×11	0.93	1.86	145	72						
18	180	5×11	0.80	1.60	155	79						
22	220	6.3×11	0.65	1.30	195	100						
27	270	6.3×11	0.53	1.06	215	115						
33	330	6.3×11	0.43	0.86	240	135						
39	390	6.3×11	0.36	0.72	260	150						
47	470	6.3×15	0.30	0.60	330	195						
56	560	6.3×15	0.25	0.50	360	220						
68	680	8×11.5	0.20	0.40	410	255						
82	820	8×15	0.17	0.34	500	320	10×12.5	0.18	0.36	510	330	
100	101	8×20	0.14	0.28	620	410	10×15	0.16	0.32	580	385	
120	121	8×20	0.12	0.24	670	455	10×15	0.13	0.26	640	435	
150	151	10×20	0.10	0.20	820	570	12.5×15	0.11	0.22	785	545	
180	181	10×20	0.085	0.17	890	635	12.5×15	0.095	0.19	845	605	
220	221	10×25	0.075	0.15	1040	760	12.5×15	0.080	0.16	920	670	
270	271	10×31.5	0.065	0.13	1200	900	16×15	0.070	0.14	1120	840	
330	331	10×31.5	0.055	0.11	1300	995	16×15	0.060	0.12	1210	925	
390	391	12.5×25	0.048	0.096	1440	1120	16×15	0.055	0.11	1270	990	
470	471	12.5×25	0.044	0.088	1500	1190	18×15	0.046	0.092	1470	1170	
560	561	12.5×31.5	0.040	0.080	1680	1360	16×20	0.044	0.088	1550	1260	
680	681	12.5×35.5	0.036	0.072	1850	1530	16×20	0.040	0.080	1630	1350	
820	821	12.5×40	0.033	0.066	2010	1700	18×20	0.036	0.072	1810	1530	
1000	102	16×31.5	0.030	0.060	2120	1830	18×25	0.033	0.066	2000	1730	
1200	122	16×35.5	0.028	0.056	2260	1990	18×31.5	0.031	0.062	2140	1880	
1500	152	16×40	0.026	0.052	2410	2170	18×31.5	0.029	0.058	2220	1990	
1800	182	18×35.5	0.025	0.050	2460	2210						
2200	222	18×40	0.024	0.048	2560	2300						

※ In case of low profile type, [6] will be put at 12th digit of type numbering system.

■ Standard ratings

V(Code) Size code		63(1J)									
		—					6				
		Item Case size φD×L (mm)	Impedance(Ω MAX.)		Rated ripple (mA rms)		Item Case size φD×L (mm)	Impedance(Ω MAX.)		Rated ripple (mA rms)	
20°C/100kHz	—10°C/100kHz		105°C/10kHz~ 200kHz	105°C/120Hz	20°C/100kHz	—10°C/100kHz		105°C/10kHz~ 200kHz	105°C/120Hz		
10	100	5×11	1.06	2.12	135	67					
12	120	5×11	0.93	1.86	145	72					
15	150	6.3×11	0.73	1.46	185	92					
18	180	6.3×11	0.63	1.26	195	100					
22	220	6.3×11	0.52	1.04	215	110					
27	270	6.3×11	0.43	0.86	240	130					
33	330	6.3×15	0.35	0.70	305	170					
39	390	6.3×15	0.30	0.60	330	190					
47	470	8×11.5	0.25	0.50	365	215					
56	560	8×15	0.21	0.42	450	275	10×12.5	0.23	0.46	450	275
68	680	8×15	0.17	0.34	500	315	10×12.5	0.19	0.38	495	310
82	820	8×20	0.15	0.30	600	385	10×15	0.16	0.32	580	375
100	101	10×20	0.12	0.24	750	495	12.5×15	0.14	0.28	695	460
120	121	10×20	0.10	0.20	820	555	12.5×15	0.12	0.24	750	510
150	151	10×25	0.090	0.18	950	665	12.5×15	0.095	0.19	845	590
180	181	10×31.5	0.075	0.15	1110	790	16×15	0.080	0.16	1050	750
220	221	12.5×20	0.065	0.13	1140	835	16×15	0.070	0.14	1120	820
270	271	12.5×25	0.055	0.11	1340	1000	18×15	0.060	0.12	1290	965
330	331	12.5×25	0.049	0.098	1420	1090	18×15	0.050	0.10	1410	1080
390	391	12.5×31.5	0.043	0.086	1620	1260	16×20	0.047	0.094	1500	1170
470	471	12.5×35.5	0.039	0.078	1780	1420	16×25	0.042	0.084	1700	1350
560	561	12.5×40	0.035	0.070	1950	1580	18×20	0.039	0.078	1730	1400
680	681	16×31.5	0.032	0.064	2050	1700	18×25	0.035	0.070	1940	1610
820	821	16×35.5	0.029	0.058	2220	1880	18×31.5	0.032	0.064	2110	1780
1000	102	16×40	0.027	0.054	2370	2050	18×35.5	0.029	0.058	2280	1970
1200	122	18×40	0.025	0.050	2510	2210					

V(Code) Size code		80(1K)									
		—					6				
		Item Case size φD×L (mm)	Impedance(Ω MAX.)		Rated ripple (mA rms)		Item Case size φD×L (mm)	Impedance(Ω MAX.)		Rated ripple (mA rms)	
20°C/100kHz	—10°C/100kHz		105°C/10kHz~ 200kHz	105°C/120Hz	20°C/100kHz	—10°C/100kHz		105°C/10kHz~ 200kHz	105°C/120Hz		
4.7	4R7	5×11	4.20	11.00	53	26					
6.8	6R8	5×11	2.60	7.00	68	34					
10	100	6.3×11	1.70	4.60	87	43					
12	120	6.3×11	1.40	3.80	96	48					
15	150	6.3×11	1.20	3.20	104	52					
18	180	6.3×11	1.00	2.70	114	58					
22	220	6.3×15	0.77	2.10	135	71					
27	270	6.3×15	0.63	1.70	149	80					
33	330	8×11.5	0.53	1.40	234	132					
39	390	8×15	0.46	1.20	272	156	10×12.5	0.49	1.30	271	155
47	470	8×15	0.39	1.10	295	175	10×12.5	0.42	1.10	293	174
56	560	8×20	0.34	0.92	347	208	10×15	0.36	0.97	337	202
68	680	10×20	0.28	0.76	426	264	12.5×15	0.31	0.84	402	249
82	820	10×20	0.25	0.68	447	284	12.5×15	0.27	0.73	430	273
100	101	10×25	0.21	0.57	526	347	12.5×15	0.23	0.62	466	308
120	121	10×31.5	0.18	0.49	606	406	16×15	0.20	0.54	663	444
150	151	10×31.5	0.15	0.41	663	459	16×15	0.18	0.47	699	484
180	181	12.5×25	0.13	0.35	734	520	16×15	0.15	0.41	766	543
220	221	12.5×31.5	0.12	0.32	816	595	18×15	0.13	0.35	881	643
270	271	12.5×31.5	0.10	0.27	894	667	16×20	0.11	0.30	995	742
330	331	12.5×35.5	0.088	0.24	1000	767	16×25	0.099	0.27	1140	874
390	391	12.5×40	0.078	0.21	1060	822	18×20	0.089	0.24	1170	908
470	471	16×31.5	0.069	0.19	1450	1150	18×25	0.080	0.22	1330	1060
560	561	16×35.5	0.062	0.17	1600	1300	18×31.5	0.072	0.19	1490	1210
680	681	16×40	0.055	0.15	1770	1470	18×31.5	0.065	0.18	1560	1300
820	821	18×35.5	0.049	0.13	1890	1590					
1000	102	18×40	0.044	0.12	2080	1790					

※ In case of low profile type, [6] will be put at 12th digit of type numbering system.

## Standard ratings

Cap.(μF)	V(Code)	Size code	100 (2A)										
			Item	—					6				
				Case size φD×L (mm)	Impedance(Ω MAX.)		Rated ripple (mA rms)		Case size φD×L (mm)	Impedance(Ω MAX.)		Rated ripple (mA rms)	
					20°C/100kHz	—10°C/100kHz	105°C/10kHz ~ 200kHz	105°C/120Hz		20°C/100kHz	—10°C/100kHz	105°C/10kHz ~ 200kHz	105°C/120Hz
0.47	R47	5×11	43.0	116.0	17	8							
0.68	R68	5×11	23.0	62.0	23	11							
1	010	5×11	17.0	46.0	27	13							
1.5	1R5	5×11	10.0	27.0	35	17							
2.2	2R2	5×11	6.60	18.0	43	21							
3.3	3R3	5×11	4.10	11.0	54	27							
4.7	4R7	6.3×11	2.80	7.60	68	34							
6.8	6R8	6.3×11	1.90	5.10	83	41							
10	100	6.3×11	1.20	3.20	104	52							
12	120	6.3×11	1.00	2.70	114	57							
15	150	6.3×15	0.81	2.20	131	65							
18	180	6.3×15	0.67	1.80	155	73							
22	220	8×11.5	0.55	1.50	230	122							
27	270	8×15	0.47	1.30	269	146	10×12.5	0.50	1.40	268	145		
33	330	8×15	0.38	1.00	299	169	10×12.5	0.42	1.10	293	166		
39	390	8×20	0.33	0.89	352	202	10×15	0.36	0.97	337	193		
47	470	10×20	0.28	0.76	423	252	12.5×15	0.31	0.84	402	239		
56	560	10×20	0.24	0.65	456	274	12.5×15	0.27	0.73	430	258		
68	680	10×25	0.21	0.57	526	326	12.5×15	0.23	0.62	466	289		
82	820	10×31.5	0.18	0.49	606	386	16×15	0.19	0.51	681	433		
100	101	10×31.5	0.15	0.41	663	438	16×15	0.17	0.46	719	475		
120	121	12.5×25	0.13	0.35	774	519	16×15	0.14	0.38	793	531		
150	151	12.5×25	0.11	0.30	798	553	18×15	0.12	0.32	917	635		
180	181	12.5×31.5	0.098	0.26	904	641	16×20	0.11	0.30	995	706		
220	221	12.5×35.5	0.087	0.23	1000	730	16×25	0.093	0.25	1170	854		
270	271	12.5×40	0.072	0.19	1130	843	18×20	0.080	0.22	1230	918		
330	331	16×31.5	0.062	0.17	1520	1160	18×25	0.070	0.19	1420	1080		
390	391	16×35.5	0.053	0.14	1730	1340	18×31.5	0.062	0.17	1600	1240		
470	471	16×40	0.047	0.13	1920	1530	18×35.5	0.056	0.15	1770	1410		
560	561	18×35.5	0.041	0.11	2070	1680							
680	681	18×40	0.036	0.097	2300	1910							

※ In case of low profile type, [6] will be put at 12th digit of type numbering system.

Cap.(μF)	V(Code)	160		200		250		315		350		400		450	
		2C	2D	2E	2F	2V	2G	2W							
1	010	8×11.5	19	8×11.5	19	8×11.5	19	8×11.5	19	10×12.5	21	10×12.5	17	10×15	17
2.2	2R2	8×11.5	30	8×11.5	30	10×12.5	32	10×12.5	32	10×15	34	10×15	28	10×20	28
3.3	3R3	10×12.5	50	10×12.5	50	10×15	52	10×15	52	10×20	54	10×20	47	12.5×20	48
4.7	4R7	10×12.5	57	10×15	60	10×15	60	10×20	65	10×20	65	12.5×20	55	12.5×25	55
10	100	10×15	90	10×20	95	12.5×20	98	12.5×20	98	12.5×25	100	12.5×25	85	16×25	90
22	220	12.5×20	140	12.5×25	145	16×25	150	16×25	150	16×25	150	16×31.5	130	16×35.5	135
33	330	12.5×25	175	16×25	180	16×25	180	16×31.5	185	16×35.5	190	18×35.5	170	18×40	170
47	470	16×25	220	16×25	220	16×31.5	225	18×35.5	235	18×40	240				
100	101	16×35.5	330	18×40	345	18×40	345							Case size	※

※ Rated Ripple(mA rms)at 105°C 120Hz