

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

1N3062
1N3063
1N3064

SILICON SWITCHING DIODE

JEDEC DO-35 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR 1N3062 Series types are very high speed Silicon Switching Diodes designed for computer and general purpose applications.

MAXIMUM RATINGS (T_A=25°C)

	SYMBOL	1N3062	1N3063	1N3064	UNIT
Peak Repetitive Voltage	V _{RRM}	75	75	75	V
Peak Working Reverse Voltage	V _{RWM}	50	50	50	V
Average Forward Current	I _O	75	75	75	mA
Forward Steady-State Current	I _F	115	115	115	mA
Peak Forward Current (Recurrent)	I _{FM}	225	225	225	mA
Peak Forward Surge Current (1.0μs)	I _{FSM}	2000	2000	2000	mA
Power Dissipation	P _D	250	250	250	mW
Operating and Storage Junction Temperature	T _J , T _{stg}	-65 TO +200			°C

ELECTRICAL CHARACTERISTICS (T_A=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNIT
I _R	V _R =50V		0.1	μA
I _R	V _R =50V, T _A =150°C		100	μA
BV _R	I _R =5.0μA	75		V
V _F	I _F =250μA	0.505	0.575	V
V _F	I _F =1.0mA	0.55	0.65	V
V _F	I _F =2.0mA	0.61	0.71	V
V _F	I _F =10mA (1N3064)	-	1.0	V
V _F	I _F =10mA (1N3063)	0.7	0.85	V
V _F	I _F =20mA (1N3062)	-	1.0	V
C _T	V _R =0V, f=1.0MHz (1N3062)		1.0	pF
C _T	V _R =0V, f=1.0MHz (1N3063, 1N3064)		2.0	pF
t _{rr}	V _r =6.0V, I _f =10mA, R _L =100Ω (1N3062)		2.0	ns
t _{rr}	V _r =1.0V, I _f =10mA, R _L =100Ω (1N3063, 1N3064)		4.0	ns
RE	f=1.0MHz	45		%
ΔV _F /°C			1.8	mV/°C



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.