



**MILITARY DATA SHEET**

**MN54F374-X REV 1A0**

Original Creation Date: 05/31/96  
 Last Update Date: 07/30/96  
 Last Major Revision Date: 05/31/96

**OCTAL D-TYPE FLIP-FLOP WITH 3-STATE OUTPUTS**

**General Description**

The F374 is a high-speed, low power octal D-type flip flop featuring separate D-type inputs for each flip-flop and 3-state outputs for bus-oriented applications. A buffered Clock (CP) and Output Enable ( $\overline{OE}$ ) are common to all flip-flops.

**Industry Part Number**

54F374

**NS Part Numbers**

54F374DMQB  
 54F374FMQB  
 54F374LMQB

**Prime Die**

M374

**Processing**

MIL-STD-883, Method 5004

**Quality Conformance Inspection**

MIL-STD-883, Method 5005

Subgrp	Description	Temp ( °C)
1	Static tests at	+25
2	Static tests at	+125
3	Static tests at	-55
4	Dynamic tests at	+25
5	Dynamic tests at	+125
6	Dynamic tests at	-55
7	Functional tests at	+25
8A	Functional tests at	+125
8B	Functional tests at	-55
9	Switching tests at	+25
10	Switching tests at	+125
11	Switching tests at	-55

**Features**

- Edge-triggered D-Type Inputs
- Buffered Positive Edge-Triggered Clock
- 3-State Outputs for Bus-Oriented Applications

**(Absolute Maximum Ratings)**

(Note 1)

Storage Temperature	-65 C to +150 C
Ambient Temperature under Bias	-55 C to +125 C
Junction Temperature under Bias	-55 C to +175 C
Vcc Pin Potential to Ground Pin	-0.5V to +7.0V
Input Voltage (Note 2)	-0.5V to +7.0V
Input Current (Note 2)	-30mA to +5.0mA
Voltage Applied to Output in HIGH State (with Vcc=0V)	
Standard Output	-0.5V to Vcc
TRI-STATE Output	-0.5V to +5.5V
Current Applied to Output in LOW State (Max)	twice the rated I <sub>ol</sub> (mA)
ESD Last Passing Voltage (Min)	4000V

Note 1: Absolute Maximum ratings are those values beyond which the device may be damaged or have its useful life impaired.

Note 2: Either voltage limit or current limit is sufficient to protect inputs.

**Recommended Operating Conditions**

Free Air Ambient Temperature	
Commercial	0 C to +70 C
Military	-55 C to +125 C
Supply Voltage	
Military	+4.5V to +5.5V
Commercial	+4.5V to +5.5V

## Electrical Characteristics

### DC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)  
DC: VCC 4.5V to 5.5V, Temp range: -55C to 125C

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
IIH	Input High Current	VCC=5.5V, VM=2.7V, VINH=4.5V	1, 3	INPUTS		20	uA	1, 2, 3
IBVI	Input High Current	VCC=5.5V, VM=7.0V, VINH=5.5V	1, 3	INPUTS		100	uA	1, 2, 3
IIL	Input LOW Current	VCC=5.5V, VM=0.5V, VINH=5.5V	1, 3	INPUTS		-0.6	mA	1, 2, 3
VOL	Output LOW Voltage	VCC=4.5V, VIL=0.8V, IOL=20mA	1, 3	OUTPUTS		0.5	V	1, 2, 3
VOH	Output HIGH Voltage	VCC= 4.5V, VIH=2.0V, IOH=-1.0mA, VINH=5.5V, VINL=0.0V	1, 3	OUTPUTS	2.5		V	1, 2, 3
VOH3	Output HIGH Voltage	VCC=4.5V, VIH=2.0V, IOH=-3.0mA, VINH=5.5V, VINL=0.8V	1, 3	OUTPUTS	2.4		V	1, 2, 3
IOS	Short Circuit Current	VCC=5.5V, VINH=5.5V, VINL=0.0V, VM=0.0V	1, 3	OUTPUTS	-60	-150	mA	1, 2, 3
VCD	Input Clamp Diode Voltage	VCC=4.5V, IM=-18mA, VINH=5.5V	1, 3	INPUTS		-1.2	V	1, 2, 3
ICCZ	Supply Current	VCC=5.5V, VINH=5.5V	1, 3	VCC		86	mA	1, 2, 3
ICEX	Output HIGH Leakage Current	VCC=5.5V, VINH=5.5V, VM=5.5V, VINL=0.0V	1, 3	OUTPUTS		250	uA	1, 2, 3
IOZH	Output Leakage Current	VCC=5.5V, VM=2.7V, VIH=2.0V, VINL=0.0V	1, 3	OUTPUTS		50	uA	1, 2, 3
IOZL	Output Leakage Current	VCC=5.5V, VM=0.5V, VIH=2.0V, VINH=5.5V	1, 3	OUTPUTS		-50	uA	1, 2, 3

## Electrical Characteristics

### AC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)

AC: CL=50pf, RL=500 OHMS, TR=2.5ns, TF=2.5ns SEE AC FIGS

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
tpLH	Propagation Delay	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	CP to On	4.0	8.5	ns	9
			2, 4	CP to On	4.0	10.5	ns	10, 11
tpHL	Propagation Delay	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	CP to On	4.0	8.5	ns	9
			2, 4	CP to On	4.0	11.0	ns	10, 11
tpZH	Output Enable Time	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	$\overline{OE}$ to On	2.0	11.5	ns	9
			2, 4	$\overline{OE}$ to On	2.0	14.0	ns	10, 11
tpZL	Output Enable Time	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	$\overline{OE}$ to On	2.0	7.5	ns	9
			2, 4	$\overline{OE}$ to On	2.0	10.0	ns	10, 11
tpHZ	Output Disable Time	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	$\overline{OE}$ to On	2.0	7.0	ns	9
			2, 4	$\overline{OE}$ to On	2.0	8.0	ns	10, 11
tpLZ	Output Disable Time	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	$\overline{OE}$ to On	1.5	5.5	ns	9
			2, 4	$\overline{OE}$ to On	1.5	7.5	ns	10, 11
ts(H)	Setup Time	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	5	Dn to CP	2.0		ns	9
			5	Dn to CP	2.5		ns	10, 11
ts(L)	Setup Time	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	5	Dn to CP	2.0		ns	9, 10, 11
th(H)	Setup Time	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	5	Dn to CP	2.0		ns	9, 10, 11
th(L)	Setup Time	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	5	Dn to CP	2.0		ns	9
			5	Dn to CP	2.5		ns	10, 11
tw(H)	Pulse Width	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C TR/TF=1.0ns	5	CP	7.0		ns	9, 10, 11
tw(L)	Pulse Width	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C TR/TF=1.0ns	5	CP	6.0		ns	9, 10, 11

## Electrical Characteristics

### AC PARAMETERS (Continued)

(The following conditions apply to all the following parameters, unless otherwise specified.)  
 AC: CL=50pf, RL=500 OHMS, TR=2.5ns, TF=2.5ns SEE AC FIGS

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
fMAX	Maximum Clock Frequency	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C TR/TF=1.0ns	5		100		MHZ	9
			5		60		MHZ	10, 11

Note 1: Screen tested 100% on each device at +25C, +125C & -55C temperature, subgroups A1, 2, 3, 7 & 8.

Note 2: Screen tested 100% on each device at +25C temperature only, subgroup A9.

Note 3: Sample tested (Method 5005, Table 1) on each MFG. lot at +25C, +125C & -55C temperature, subgroups A1, 2, 3, 7 & 8.

Note 4: Sample tested (Method 5005, Table 1) on each MFG. lot at +25C subgroup A9, and periodically at +125C & -55C temperature, subgroups 10 & 11.

Note 5: GUARANTEED BUT NOT TESTED. (Design Characterization Data)

# National Semiconductor was acquired by Texas Instruments.

[http://www.ti.com/corp/docs/investor\\_relations/pr\\_09\\_23\\_2011\\_national\\_semiconductor.html](http://www.ti.com/corp/docs/investor_relations/pr_09_23_2011_national_semiconductor.html)

This file is the datasheet for the following electronic components:

JM38510/34105BRA - <http://www.ti.com/product/jm38510/34105bra?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/34105BSA - <http://www.ti.com/product/jm38510/34105bsa?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/34105B2A - <http://www.ti.com/product/jm38510/34105b2a?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

54F374DMQB - <http://www.ti.com/product/54f374dmqb?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/34105SRA - <http://www.ti.com/product/jm38510/34105sra?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

54F374FM-MLS - <http://www.ti.com/product/54f374fm-mls?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

54F374FMQB - <http://www.ti.com/product/54f374fmqb?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

54F374LMQB - <http://www.ti.com/product/54f374lmqb?HQS=TI-null-null-dscatalog-df-pf-null-wwe>



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.