

MN54F534-X REV 1A0

Original Creation Date: 05/06/96
 Last Update Date: 07/30/96
 Last Major Revision Date: 05/06/96

OCTAL D-TYPE FLIP-FLOP WITH TRI-STATE OUTPUTS

General Description

The F534 is a high speed, low-power octal D-type flip-flop featuring separate D-type inputs for each flip-flop and TRI-STATE outputs for bus-oriented applications. A buffered Clock (CP) and Output Enable (\overline{OE}) are common to all flip-flops. The F534 is the same as the F374 except that the outputs are inverted.

Industry Part Number

54F534

NS Part Numbers

54F534DMQB
 54F534FMQB
 54F534LMQB

Prime Die

M534

Processing

MIL-STD-883, Method 5004

Quality Conformance Inspection

MIL-STD-883, Method 5005

Subgrp	Description	Temp (°C)
1	Static tests at	+25
2	Static tests at	+125
3	Static tests at	-55
4	Dynamic tests at	+25
5	Dynamic tests at	+125
6	Dynamic tests at	-55
7	Functional tests at	+25
8A	Functional tests at	+125
8B	Functional tests at	-55
9	Switching tests at	+25
10	Switching tests at	+125
11	Switching tests at	-55

Features

- Edge-Triggered D-type inputs
- Buffered Positive Edge - Triggered Clock
- 3-State Output for Bus - Oriented Applications

(Absolute Maximum Ratings)

(Note 1)

Storage Temperature	-65C to +150C
Ambient Temperature under Bias	-55C to +125C
Junction Temperature under Bias	-55C to +175C
Vcc Pin Potential to Ground Pin	-0.5V to +7.0V
Input Voltage (Note 2)	-0.5V to +7.0V
Input Current (Note 2)	-30mA to +5.0mA
Voltage Applied to Output in HIGH State (with Vcc=0V)	
Standard Output	-0.5V to Vcc
TRI-STATE Output	-0.5V to +5.5V
Current Applied to Output in LOW State (Max)	twice the rated I _{ol} (mA)
ESD Last Passing Voltage (Min)	4000V

Note 1: Absolute maximum ratings are values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 2: Either voltage limit or current limit is sufficient to protect inputs.

Recommended Operating Conditions

Free Air Ambient Temperature	
Commercial	0 C to +70 C
Military	-55 C to +125 C
Supply Voltage	
Military	+4.5V to +5.5V
Commercial	+4.5V to +5.5V

Electrical Characteristics

DC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)
DC: VCC 4.5V to 5.5V, Temp range: -55C to 125C

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
IIH	Input High Current	VCC=5.5V, VM=2.7V, VINH=5.5V	1, 3	INPUTS		20	uA	1, 2, 3
IBVI	Input High Current	VCC=5.5V, VM=7.0V, VINH=5.5V	1, 3	INPUTS		100	uA	1, 2, 3
IIL	Input LOW Current	VCC=5.5V, VM=0.5V, VINH=5.5V	1, 3	INPUTS		-0.6	mA	1, 2, 3
VOL	Output LOW Voltage	VCC=4.5V, VIL=0.8V, IOL=20mA, VIH=2.0V, VINH=5.5V, VINL=0.0V	1, 3	OUTPUTS		0.5	V	1, 2, 3
VOH	Output HIGH Voltage	VCC=4.5V, VIL=0.8V, IOH=-1.0mA	1, 3	OUTPUTS	2.5		V	1, 2, 3
VOH3	Output HIGH Voltage	VCC=4.5V, VIL=0.8V, IOH3=-3.0mA, VINH=5.5V	1, 3	OUTPUTS	2.4		V	1, 2, 3
IOS	Short-Circuit Current	VCC=5.5V, VINH=5.5V, VM=0.0V, VINL=0.0V	1, 3	OUTPUTS	-60	-150	mA	1, 2, 3
VCD	Input Clamp Diode Voltage	VCC=4.5V, IM=-18mA, VINH=5.5V	1, 3	INPUTS		-1.2	V	1, 2, 3
ICCZ	Power Supply Current	VCC=5.5V, VINH=5.5V, VINL=0.0V	1, 3	VCC		86	mA	1, 2, 3
ICEX	Output HIGH Leakage Current	VCC=5.5V, VINH=5.5V, VINL=0.0V, VM=5.5V	1, 3	OUTPUTS		250	uA	1, 2, 3
IOZH	Output Leakage Current	VCC=5.5V, VM=2.7V, VINH=5.5V, VINL=0.0V	1, 3	OUTPUTS		50	uA	1, 2, 3
IOZL	Output Leakage Current	VCC=5.5V, VM=0.5V, VINH=5.5V, VINL=0.0V	1, 3	OUTPUTS		-50	uA	1, 2, 3

Electrical Characteristics

AC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)
 AC: CL=50pf, RL=500 OHMS, TR=2.5ns, TF=2.5ns SEE AC FIGS

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
tpLH	Propagation Delay	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	2, 4	CP to $\bar{O}n$	4.0	8.5	ns	9
			2, 4	CP to $\bar{O}n$	4.0	10.5	ns	10, 11
tpHL	Propagation Delay	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	2, 4	CP to $\bar{O}n$	4.0	8.5	ns	9
			2, 4	CP to $\bar{O}n$	4.0	11.0	ns	10, 11
tpZH	Output Enable	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	2, 4	$\bar{O}E$ to $\bar{O}n$	2.0	11.5	ns	9
			2, 4	$\bar{O}E$ to $\bar{O}n$	2.0	14.0	ns	10, 11
tpZL	Output Enable	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	2, 4	$\bar{O}E$ to $\bar{O}n$	2.0	7.5	ns	9
			2, 4	$\bar{O}E$ to $\bar{O}n$	2.0	10.0	ns	10, 11
tpHZ	Output Disable	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	2, 4	$\bar{O}E$ to $\bar{O}n$	1.5	7.0	ns	9
			2, 4	$\bar{O}E$ to $\bar{O}n$	1.5	8.0	ns	10, 11
tpLZ	Output Disable	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	2, 4	$\bar{O}E$ to $\bar{O}n$	1.5	5.5	ns	9
			2, 4	$\bar{O}E$ to $\bar{O}n$	1.5	7.5	ns	10, 11
ts(H)	Setup Time	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	5	D to CP	2.0		ns	9, 10, 11
ts(L)	Setup Time	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	5	D to CP	2.0		ns	9
			5	D to CP	2.5		ns	10, 11
th(H)	Hold Time	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	5	D to CP	2.0		ns	9, 10, 11
th(L)	Hold Time	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	5	D to CP	2.0		ns	9
			5	D to CP	2.5		ns	10, 11
tw(H)	Pulse Width	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C TR/TF=1.0ns	5	CP	7.0		ns	9, 10, 11
tw(L)	Pulse Width	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C TR/TF=1.0ns	5	CP	6.0		ns	9, 10, 11
fMAX	Maximum Clock Frequency	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C TR/TF=1.0ns	5		100		MHZ	9
			5		60		MHZ	10, 11

(Continued)

- Note 1: Screen tested 100% on each device at -55 C, +25 C & +125 C temperature, Subgroups A1, 2, 3, 7 & 8.
- Note 2: Screen tested 100% on each device at +25 C temperature only, Subgroup A9.
- Note 3: Sample tested (Method 5005, Table 1) on each MFG. lot at +25 C, +125 C & -55 C temp., Subgroups A1, 2, 3, 7 & 8.
- Note 4: Sample Tested (Method 5005, Table 1) on each MFG. lot at +25 C Subgroup A9, & periodically at +125 C & -55 C temp., Subgroups 10 & 11.
- Note 5: Guaranteed but not tested. (DESIGN CHARACTERIZATION DATA)

National Semiconductor was acquired by Texas Instruments.

http://www.ti.com/corp/docs/investor_relations/pr_09_23_2011_national_semiconductor.html

This file is the datasheet for the following electronic components:

54F534LMQB - <http://www.ti.com/product/54f534lmbq?HQS=TI-null-null-dscatalog-df-pf-null-ww>

JM38510/34106BRA - <http://www.ti.com/product/jm38510/34106bra?HQS=TI-null-null-dscatalog-df-pf-null-ww>

JM38510/34106B2A - <http://www.ti.com/product/jm38510/34106b2a?HQS=TI-null-null-dscatalog-df-pf-null-ww>

54F534DMQB - <http://www.ti.com/product/54f534dmqb?HQS=TI-null-null-dscatalog-df-pf-null-ww>



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.