

BC182, BC182A, BC182B

Amplifier Transistors

NPN Silicon

Features

- Pb-Free Package is Available*

MAXIMUM RATINGS

Rating	Symbol	BC182	Unit
Collector–Emitter Voltage	V_{CEO}	50	Vdc
Collector–Base Voltage	V_{CBO}	60	Vdc
Emitter–Base Voltage	V_{EBO}	6.0	Vdc
Collector Current – Continuous	I_C	100	mAdc
Total Device Dissipation @ $T_A = 25^\circ\text{C}$ Derate above 25°C	P_D	350 2.8	mW mW/ $^\circ\text{C}$
Total Device Dissipation @ $T_C = 25^\circ\text{C}$ Derate above 25°C	P_D	1.0 8.0	W mW/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	T_J, T_{stg}	-55 to +150	$^\circ\text{C}$

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS



Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction–to–Ambient	$R_{\theta JA}$	357	$^\circ\text{C}/\text{W}$
Thermal Resistance, Junction–to–Case	$R_{\theta JC}$	125	$^\circ\text{C}/\text{W}$

*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.




ON Semiconductor®

<http://onsemi.com>



TO-92
CASE 29
STYLE 17

MARKING DIAGRAM



BC Specific Device Code
x A or B
Y = Year
WW = Work Week

ORDERING INFORMATION

Device	Package	Shipping†
BC182	TO-92	5000 Units / Box
BC182G	TO-92 (Pb-Free)	5000 Units / Box
BC182A	TO-92	5000 Units / Box
BC182B	TO-92	5000 Units / Box
BC182BRL1	TO-92	2000 /Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.






BC182, BC182A, BC182B

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector–Emitter Breakdown Voltage (I _C = 2.0 mA, I _B = 0)	V _{(BR)CEO}	50	–	–	V
Collector–Base Breakdown Voltage (I _C = 10 μA, I _E = 0)	V _{(BR)CBO}	60	–	–	V
Emitter–Base Breakdown Voltage (I _E = 100 μA, I _C = 0)	V _{(BR)EBO}	6.0	–	–	V
Collector Cutoff Current (V _{CB} = 50 V, V _{BE} = 0)	I _{CBO}	–	0.2	15	nA
Emitter–Base Leakage Current (V _{EB} = 4.0 V, I _C = 0)	I _{EBO}	–	–	15	nA
ON CHARACTERISTICS					
DC Current Gain (I _C = 10 μA, V _{CE} = 5.0 V)	h _{FE}	40	–	–	–
(I _C = 2.0 mA, V _{CE} = 5.0 V)		120	–	500	
(I _C = 100 mA, V _{CE} = 5.0 V)		80	–	–	
		120	–	220	
Collector–Emitter On Voltage (I _C = 10 mA, I _B = 0.5 mA)	V _{CE(sat)}	–	0.07	0.25	V
(I _C = 100 mA, I _B = 5.0 mA) (Note 1)		–	0.2	0.6	
Base–Emitter Saturation Voltage (I _C = 100 mA, I _B = 5.0 mA) (Note 1)	V _{BE(sat)}	–	–	1.2	V
Base–Emitter On Voltage (I _C = 100 μA, V _{CE} = 5.0 V)	V _{BE(on)}	–	0.5	–	V
(I _C = 2.0 mA, V _{CE} = 5.0 V)		0.55	0.62	0.7	
(I _C = 100 mA, V _{CE} = 5.0 V) (Note 1)		–	0.83	–	
DYNAMIC CHARACTERISTICS					
Current–Gain — Bandwidth Product (I _C = 0.5 mA, V _{CE} = 3.0 V, f = 100 MHz)	f _T	–	100	–	MHz
(I _C = 10 mA, V _{CE} = 5.0 V, f = 100 MHz)		150	200	–	
Common Base Output Capacitance (V _{CB} = 10 V, I _C = 0, f = 1.0 MHz)	C _{ob}	–	–	5.0	pF
Common Base Input Capacitance (V _{EB} = 0.5 V, I _C = 0, f = 1.0 MHz)	C _{ib}	–	8.0	–	pF
Small–Signal Current Gain (I _C = 2.0 mA, V _{CE} = 5.0 V, f = 1.0 kHz)	h _{fe}	125	–	500	–
		125	–	260	
		240	–	500	
Noise Figure (I _C = 0.2 mA, V _{CE} = 5.0 V, R _S = 2.0 kΩ, f = 1.0 kHz)	NF	–	2.0	10	dB

1. Pulse Test: T_p 300 s, Duty Cycle 2.0%.



BC182, BC182A, BC182B



BC182, BC182A, BC182B

PACKAGE DIMENSIONS

TO-92
TO-226AA
CASE 29-11
ISSUE AL




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.175	0.205	4.45	5.20
B	0.170	0.210	4.32	5.33
C	0.125	0.165	3.18	4.19
D	0.016	0.021	0.407	0.533
G	0.045	0.055	1.15	1.39
H	0.095	0.105	2.42	2.66
J	0.015	0.020	0.39	0.50
K	0.500	---	12.70	---
L	0.250	---	6.35	---
N	0.080	0.105	2.04	2.66
P	---	0.100	---	2.54
R	0.115	---	2.93	---
V	0.135	---	3.43	---

STYLE 17:

1. COLLECTOR
2. BASE
3. EMITTER

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
P.O. Box 61312, Phoenix, Arizona 85082-1312 USA
Phone: 480-829-7710 or 800-344-3860 Toll Free USA/Canada
Fax: 480-829-7709 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051
Phone: 81-3-5773-3850

ON Semiconductor Website: <http://onsemi.com>

Order Literature: <http://www.onsemi.com/litorder>

For additional information, please contact your
local Sales Representative.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.