

# DATA SHEET

**BFQ17**

**NPN 1 GHz wideband transistor**

Product specification  
File under Discrete Semiconductors, SC14

September 1995

# NPN 1 GHz wideband transistor


# BFQ17

### DESCRIPTION

NPN transistor in a SOT89 plastic envelope intended for application in thick and thin-film circuits. The transistor has extremely good intermodulation properties and a high power gain.

### PINNING

PIN	DESCRIPTION
Code: FA	
1	emitter
2	collector
3	base



### QUICK REFERENCE DATA

SYMBOL	PARAMETER	CONDITIONS	TYP.	MAX.	UNIT
$V_{CBO}$	collector-base voltage	open emitter	–	40	V
$V_{CEO}$	collector-emitter voltage	open base	–	25	V
$I_{CM}$	peak collector current		–	300	mA
$P_{tot}$	total power dissipation	up to $T_s = 145\text{ °C}$ (note 1)	–	1	W
$f_T$	transition frequency	$I_C = 150\text{ mA}$ ; $V_{CE} = 15\text{ V}$ ; $f = 500\text{ MHz}$ ; $T_j = 25\text{ °C}$	1.5	–	GHz
$C_{re}$	feedback capacitance	$I_C = 10\text{ mA}$ ; $V_{CE} = 15\text{ V}$ ; $f = 1\text{ MHz}$ ; $T_{amb} = 25\text{ °C}$	1.9	–	pF

### LIMITING VALUES

In accordance with the Absolute Maximum System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
$V_{CBO}$	collector-base voltage	open emitter	–	40	V
$V_{CER}$	collector-emitter voltage	$R_{BE} \leq 50\ \Omega$	–	40	V
$V_{CEO}$	collector-emitter voltage	open base	–	25	V
$V_{EBO}$	emitter-base voltage	open collector	–	2	V
$I_C$	DC collector current		–	150	mA
$I_{CM}$	peak collector current	$f > 1\text{ MHz}$	–	300	mA
$P_{tot}$	total power dissipation	up to $T_s = 145\text{ °C}$ (note 1)	–	1	W
$T_{stg}$	storage temperature		–65	150	°C
$T_j$	junction temperature		–	175	°C

### Note

- $T_s$  is the temperature at the soldering point of the collector tab.

## NPN 1 GHz wideband transistor

BFQ17

## THERMAL RESISTANCE

SYMBOL	PARAMETER	CONDITIONS	THERMAL RESISTANCE
$R_{th\ j-s}$	thermal resistance from junction to soldering point	up to $T_s = 145\text{ °C}$ (note 1)	30 K/W

## Note

- $T_s$  is the temperature at the soldering point of the collector tab.

## CHARACTERISTICS

$T_j = 25\text{ °C}$  unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$I_{CBO}$	collector cut-off current	$I_E = 0$ ; $V_{CB} = 20\text{ V}$ ; $T_j = 50\text{ °C}$	–	–	20	$\mu\text{A}$
$V_{CE\ sat}$	collector-emitter saturation voltage	$I_C = 100\text{ mA}$ ; $I_B = 10\text{ mA}$	–	–	0.5	V
$h_{FE}$	DC current gain	$I_C = 150\text{ mA}$ ; $V_{CE} = 5\text{ V}$	25	80	–	
$C_c$	collector capacitance	$I_E = i_e = 0$ ; $V_{CB} = 15\text{ V}$ ; $f = 1\text{ MHz}$	–	–	4	pF
$C_{re}$	feedback capacitance	$I_C = 10\text{ mA}$ ; $V_{CE} = 15\text{ V}$ ; $f = 1\text{ MHz}$ ; $T_{amb} = 25\text{ °C}$	–	1.9	–	pF
$f_T$	transition frequency	$I_C = 150\text{ mA}$ ; $V_{CE} = 15\text{ V}$ ; $f = 500\text{ MHz}$	–	1.5	–	GHz
$G_{UM}$	maximum unilateral power gain (note 1)	$I_C = 60\text{ mA}$ ; $V_{CE} = 15\text{ V}$ ; $f = 200\text{ MHz}$ ; $T_{amb} = 25\text{ °C}$	–	16	–	dB
		$I_C = 60\text{ mA}$ ; $V_{CE} = 15\text{ V}$ ; $f = 800\text{ MHz}$ ; $T_{amb} = 25\text{ °C}$	–	6.5	–	dB




## Note

- $G_{UM}$  is the maximum unilateral power gain, assuming  $S_{12}$  is zero and

$$G_{UM} = 10 \log \left( \frac{|S_{21}|^2}{(1 - |S_{11}|^2)(1 - |S_{22}|^2)} \right) \text{ dB.}$$

NPN 1 GHz wideband transistor

BFQ17




NPN 1 GHz wideband transistor

BFQ17

PACKAGE OUTLINE

Plastic surface mounted package; collector pad for good heat transfer; 3 leads

SOT89



DIMENSIONS (mm are the original dimensions)

UNIT	A	b <sub>1</sub>	b <sub>2</sub>	b <sub>3</sub>	c	D	E	e	e <sub>1</sub>	H <sub>E</sub>	L min.	w
mm	1.6 1.4	0.48 0.35	0.53 0.40	1.8 1.4	0.44 0.37	4.6 4.4	2.6 2.4	3.0	1.5	4.25 3.75	0.8	0.13

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	EIAJ			
SOT89						97-02-28

## NPN 1 GHz wideband transistor

BFQ17

**DEFINITIONS**

<b>Data Sheet Status</b>	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
<b>Limiting values</b>	
Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
<b>Application information</b>	
Where application information is given, it is advisory and does not form part of the specification.	

**LIFE SUPPORT APPLICATIONS**

These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.