

FAIRCHILD

A Schlumberger Company

FD700/FDLL700
FD777/FDLL777

Ultra Fast Diodes

T-03-09

- C... 1.0 pF (MAX) @ $V_R = 0, f = 1.0$ MHz (FD 700)
- t_{rr} ... 700 ps (MAX) @ $I_f = I_r = 10$ mA, $R_L = 100 \Omega$ (FD 700)
- CONTROLLED FORWARD CONDUCTANCE

PACKAGES

FD700	DO-7
FD777	DO-7
FDLL700	LL-34
FDLL777	LL-34

ABSOLUTE MAXIMUM RATINGS (Note 1)

	FD700	FD777
Temperatures		
Storage Temperature Range	-65°C to +200°C	-65°C to +200°C
Max Junction Operating Temperature	+175°C	+175°C
Lead Temperature	+260°C	+260°C
Power Dissipation		
Maximum Total Dissipation at 25°C Ambient	250 mW	250 mW
Linear Derating Factor (from 25°C)	1.67 mW/°C	1.67 mW/°C
Maximum Voltages and Currents		
WIV Working Inverse Voltage	20 V	8.0 V
I_O Average Rectified Current	50 mA	50 mA
I_F Forward Current Steady State dc	150 mA	150 mA
I_f Recurrent Peak Forward Current	150 mA	150 mA
I_f (surge) Peak Forward Surge Current Pulse Width = 1.0 s	250 mA	250 mA

If you need this device in the SOT package, an electrical equivalent is available. See FDSO1700 family.

3

ELECTRICAL CHARACTERISTICS (25°C Ambient Temperature unless otherwise noted)

SYMBOL	CHARACTERISTIC	FD700		FD777		UNITS	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
V_F	Forward Voltage	0.89	1.10	0.89	1.35	V	$I_F = 50$ mA
		0.81	0.95	0.81	1.00	V	$I_F = 20$ mA
		0.76	0.88	0.76	0.94	V	$I_F = 10$ mA
		0.64	0.74	0.64	0.79	V	$I_F = 1.0$ mA
		0.52	0.61	0.52	0.64	V	$I_F = 0.1$ mA
		0.42	0.50	0.42	0.53	V	$I_F = 0.01$ mA
BV	Breakdown Voltage	30		15		V	$I_R = 5.0 \mu A$
I_R	Reverse Current		50		100	nA	$V_R = 20$ V
			50		50	nA	$V_R = 8.0$ V
					50	μA	$V_R = 20$ V, $T_A = 150^\circ C$
τ	Minority Carrier Lifetime		450		450	ps	(see Note 2)
t_{rr}	Reverse Recovery Time (Note 3)		700		750	ps	$I_f = I_r = 10$ mA, $R_L = 100 \Omega$
C	Capacitance		1.0		1.3	pF	$V_R = 0, f = 1.0$ MHz

- NOTES:
1. The maximum ratings are limiting values above which life or satisfactory performance may be impaired.
 2. Measured as suggested by S. M. Krakeuer, IRE Proceedings, Volume 60, July 1982, pp. 1674 - 1675.
 3. Recovery to 0.1 I_R .
 4. For product family characteristic curves, refer to Chapter 4, D3.

This datasheet has been downloaded from:

www.DatasheetCatalog.com

Datasheets for electronic components.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.