


**MECHANICAL DATA**

Dimensions in mm (inches)



**TO-220M – Metal Package**

Pad 1 – Gate      Pad 2 – Drain      Pad 3 – Source

**N-CHANNEL  
POWER MOSFET  
FOR HI-REL  
APPLICATIONS**

$V_{DSS}$                     **100V**  
 $I_{D(cont)}$                 **11A**  
 $R_{DS(on)}$                 **0.19Ω**

**FEATURES**

- HERMETICALLY SEALED TO-220 METAL PACKAGE
- SIMPLE DRIVE REQUIREMENTS
- LIGHTWEIGHT
- SCREENING OPTIONS AVAILABLE
- ALL LEADS ISOLATED FROM CASE

**ABSOLUTE MAXIMUM RATINGS** ( $T_{case} = 25^{\circ}C$  unless otherwise stated)

$V_{GS}$	Gate – Source Voltage	±20V
$I_D$	Continuous Drain Current @ $T_{case} = 25^{\circ}C$	11A
$I_D$	Continuous Drain Current @ $T_{case} = 100^{\circ}C$	7A
$I_{DM}$	Pulsed Drain Current	44A
$P_D$	Power Dissipation @ $T_{case} = 25^{\circ}C$	45W
	Linear Derating Factor	0.36W/°C
$T_J, T_{stg}$	Operating and Storage Temperature Range	-55 to 150°C
$R_{\theta JC}$	Thermal Resistance Junction to Case	2.8°C/W max.
$R_{\theta JA}$	Thermal Resistance Junction to Ambient	80°C/W max.

**ELECTRICAL CHARACTERISTICS** ( $T_C = 25^\circ\text{C}$  unless otherwise stated)

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
<b>STATIC ELECTRICAL RATINGS</b>					
$BV_{DSS}$	Drain – Source Breakdown Voltage	$V_{GS} = 0$	$I_D = 1\text{mA}$	100	V
$\frac{\Delta BV_{DSS}}{\Delta T_J}$	Temperature Coefficient of Breakdown Voltage	Reference to $25^\circ\text{C}$ $I_D = 1\text{mA}$		0.1	$\text{V}/^\circ\text{C}$
$R_{DS(on)}$	Static Drain – Source On–State Resistance	$V_{GS} = 10\text{V}$	$I_D = 7\text{A}$		0.19
		$V_{GS} = 10\text{V}$	$I_D = 11\text{A}$		0.22
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}$	$I_D = 250\mu\text{A}$	2	4
$g_{fs}$	Forward Transconductance	$V_{DS} \geq 15\text{V}$	$I_{DS} = 7\text{A}$	3	$\text{S}(\bar{v})$
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{GS} = 0$	$V_{DS} = 0.8BV_{DSS}$ $T_J = 125^\circ\text{C}$		25
					250
$I_{GSS}$	Forward Gate – Source Leakage	$V_{GS} = 20\text{V}$			100
$I_{GSS}$	Reverse Gate – Source Leakage	$V_{GS} = -20\text{V}$			-100
<b>DYNAMIC CHARACTERISTICS</b>					
$C_{iss}$	Input Capacitance	$V_{GS} = 0$			650
$C_{oss}$	Output Capacitance	$V_{DS} = 25\text{V}$			240
$C_{rss}$	Reverse Transfer Capacitance	$f = 1\text{MHz}$			44
$Q_g$	Total Gate Charge	$V_{GS} = 10\text{V}$	$I_D = 11\text{A}$	12.8	28.5
$Q_{gs}$	Gate – Source Charge	$I_D = 11\text{A}$		1.0	6.3
$Q_{gd}$	Gate – Drain (“Miller”) Charge	$V_{DS} = 0.5BV_{DSS}$		3.8	16.6
$t_{d(on)}$	Turn–On Delay Time	$V_{DD} = 50\text{V}$ $I_D = 11\text{A}$ $R_G = 7.5\Omega$			30
$t_r$	Rise Time				75
$t_{d(off)}$	Turn–Off Delay Time				40
$t_f$	Fall Time				45
<b>SOURCE – DRAIN DIODE CHARACTERISTICS</b>					
$I_S$	Continuous Source Current				11
$I_{SM}$	Pulse Source Current				43
$V_{SD}$	Diode Forward Voltage	$I_S = 11\text{A}$	$T_J = 25^\circ\text{C}$		1.5
$t_{rr}$	Reverse Recovery Time	$I_S = 11\text{A}$	$T_J = 25^\circ\text{C}$		240
$Q_{rr}$	Reverse Recovery Charge	$d_i / d_t \leq 100\text{A}/\mu\text{s}$ $V_{DD} \leq 50\text{V}$			3
<b>PACKAGE CHARACTERISTICS</b>					
$L_D$	Internal Drain Inductance	(from 6mm down drain lead pad to centre of die)			8.7
$L_S$	Internal Source Inductance	(from 6mm down source lead to centre of source bond pad)			8.7



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.