



Micro Commercial Components  
 21201 Itasca Street Chatsworth  
 CA 91311  
 Phone: (818) 701-4933  
 Fax: (818) 701-4939

# 1N34A

## Germanium Diode 65 Volt

### Features

- Low Leakage Current
- Flat Junction Capacitance
- High Mechanical Strength

### Maximum Ratings

- Operating Temperature: -65°C to +75°C
- Storage Temperature: -65°C to +75°C

### Electrical Characteristics @ 25°C Unless Otherwise Specified

Peak Inverse Voltage	PIV	65V	$I_R=1.0mA$
Average Rectified Current	$I_o$	50mA	
Peak Forward Surge Current	$I_{FSM}$	500mA	8.3ms, half sine
Maximum Instantaneous Forward Voltage	$V_F$	1.00V	$I_{FM} = 5.0mA$ ; $T_J = 25^\circ C^*$
Maximum Reverse Current	$I_R$	30uA 500uA	$T_A = 25^\circ C$ $V_R=10V$ $V_R=50V$
Typical Junction Capacitance	$C_J$	0.8pF	Measured at 1.0MHz, $V_R=0V$

\*Pulse test: Pulse width 300 usec, Duty cycle 2%

DO-7

DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	-----	.300	-----	7.62	
B	-----	.107	-----	2.72	∅
C	.018	.022	0.46	0.56	∅
D	1.000	-----	25.40	-----	

This datasheet has been downloaded from:

[www.DatasheetCatalog.com](http://www.DatasheetCatalog.com)

Datasheets for electronic components.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.