

2N3684 - 2N3687

N-Channel JFET Low Noise Amplifier



T-27-25

2N3684 - 2N3687

FEATURES

- Low Noise
- High Input Impedance
- Low Capacitance

APPLICATIONS

- Low Level Choppers
- Data Switches
- Multiplexers
- Low Noise Amplifiers

ABSOLUTE MAXIMUM RATINGS

(T_A = 25°C unless otherwise noted)


Gate-Source or Gate-Drain Voltage	-50V
Gate Current	50mA
Storage Temperature Range	-65°C to +200°C
Operating Temperature Range	-55°C to +175°C
Lead Temperature (Soldering, 10sec)	+300°C
Power Dissipation	300mW
Derate above 25°C2.0mW/°C

NOTE: Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions above those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ORDERING INFORMATION

Part	Package	Temperature Range
2N3684	Hermetic TO-72	-55°C to +175°C
X2N3684	Sorted Chips in Carriers	-55°C to +175°C
2N3685	Hermetic TO-72	-55°C to +175°C
X2N3685	Sorted Chips in Carriers	-55°C to +175°C
2N3686	Hermetic TO-72	-55°C to +175°C
X2N3686	Sorted Chips in Carriers	-55°C to +175°C
2N3687	Hermetic TO-72	-55°C to +175°C
X2N3687	Sorted Chips in Carriers	-55°C to +175°C

PIN CONFIGURATION



5010

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise specified)

SYMBOL	PARAMETER	2N3684		2N3685		2N3686		2N3687		UNITS	TEST CONDITIONS
		MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX		
BV _{GSS}	Gate to Source Breakdown Voltage	-50		-50		-50		-50		V	V _{DS} = 0, I _G = 1.0μA
V _P	Pinch-Off Voltage	-2.0	-5.0	-1.0	-3.5	-0.6	-2.0	-0.3	-1.2		V _{DS} = 20V, I _D = 0.001μA
I _{GSS}	Gate Leakage Current		-0.1		-0.1		-0.1		-0.1	nA	V _{GS} = -30V, V _{DS} = 0
			-0.5		-0.5		-0.5		-0.5	μA	T _A = 150°C
I _{DSS}	Saturation Current, Drain-to-Source	2.5	7.5	1.0	3.0	-0.4	1.2	0.1	0.5	mA	V _{GS} = 0, V _{DS} = 20V
Y _{ts}	Forward Transadmittance	2000	3000	1500	2500	1000	2000	500	1500	μS	V _{DS} = 20V, V _{GS} = 0 f = 1kHz
G _{CS}	Common Source Output Conductance		50		25		10		5	μS	
C _{ISS}	Common Source Input Capacitance		4.0		4.0		4.0		4.0	pF	V _{DS} = 20V, V _{GS} = 0 f = 1MHz (Note 1)
C _{RSS}	Common Source Short Circuit Reverse Transfer Capacitance		1.2		1.2		1.2		1.2	pF	
r _{DS(on)}	On Resistance		600		800		1200		2400	ohms	V _{DS} = 0, V _{GS} = 0
NF	Noise Figure (Note 1)		0.5		0.5		0.5		0.5	dB	f = 100Hz, R _G = 10MΩ, NBW = 6Hz, V _{DS} = 10V, V _{GS} = 0V

NOTE 1: For design reference only, not 100% tested

This datasheet has been downloaded from:

www.DatasheetCatalog.com

Datasheets for electronic components.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.