



**MILITARY DATA SHEET**

**MN54F08-X REV 1A0**

Original Creation Date: 03/06/96  
Last Update Date: 07/30/96  
Last Major Revision Date: 03/06/96

**QUAD 2 INPUT AND GATE**

**General Description**

This device contains four independent gates, each of which performs the logic AND function.

**Industry Part Number**

54F08

**NS Part Numbers**

54F08DMQB  
54F08FMQB  
54F08LMQB

**Prime Die**

M008

**Processing**

MIL-STD-883, Method 5004

**Quality Conformance Inspection**

MIL-STD-883, Method 5005

| <b>Subgrp</b> | <b>Description</b>  | <b>Temp ( °C)</b> |
|---------------|---------------------|-------------------|
| 1             | Static tests at     | +25               |
| 2             | Static tests at     | +125              |
| 3             | Static tests at     | -55               |
| 4             | Dynamic tests at    | +25               |
| 5             | Dynamic tests at    | +125              |
| 6             | Dynamic tests at    | -55               |
| 7             | Functional tests at | +25               |
| 8A            | Functional tests at | +125              |
| 8B            | Functional tests at | -55               |
| 9             | Switching tests at  | +25               |
| 10            | Switching tests at  | +125              |
| 11            | Switching tests at  | -55               |

**Features**

- Guaranteed 4000V minimum ESD protection

**(Absolute Maximum Ratings)**

(Note 1)

|   |                         |
|---|-------------------------|
| Storage Temperature                                   | -65 C to +150 C         |
| Ambient Temperature under Bias                        | -55 C to +125 C         |
| Junction Temperature under Bias                       | -55 C to +175 C         |
| Vcc Pin Potential to Ground Pin                       | -0.5V to +7.0V          |
| Input Voltage<br>(Note 2)                             | -0.5V to +7.0V          |
| Input Current<br>(Note 2)                             | -30 mA to +5.0mA        |
| Voltage Applied to Output in HIGH State (with Vcc=0V) |                         |
| Standard Output                                       | -0.5V to Vcc            |
| TRI-STATE Output                                      | -0.5V to +5.5V          |
| Current Applied to Output in LOW State (Max)          | twice the rated Iol(mA) |
| ESD Last Passing Voltage (Min)                        | 4000V                   |

Note 1: Absolute Maximum ratings are those values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 2: Either voltage limit or current limit is sufficient to protect inputs.

**Recommended Operating Conditions**

|                              |                 |
|------------------------------|-----------------|
| Free Air Ambient Temperature |                 |
| Commercial                   | 0 C to +70 C    |
| Military                     | -55 C to +125 C |
| Supply Voltage               |                 |
| Military                     | +4.5V to +5.5V  |
| Commercial                   | +4.5V to +5.5V  |

## Electrical Characteristics

### DC PARAMETER

(The following conditions apply to all the following parameters, unless otherwise specified.)  
 DC: VCC 4.5V to 5.5V, Temp range: -55C to 125C

| SYMBOL | PARAMETER                   | CONDITIONS                                | NOTES | PIN-NAME | MIN | MAX  | UNIT | SUB-GROUPS |
|--------|-----------------------------|---|-------|----------|-----|------|------|------------|
| IIH    | Input High Current          | VCC=5.5V, VM=2.7V, VINH=5.5V, VINL=0.0V   | 1, 3  | INPUTS   |     | 20   | uA   | 1, 2, 3    |
| IBVI   | Input High Current          | VCC=5.5V, VM=7.0V, VINH=5.5V, VINL=0.0V   | 1, 3  | INPUTS   |     | 100  | uA   | 1, 2, 3    |
| IIL    | Input LOW Current           | VCC=5.5V, VM=0.5V, VINH=5.5V              | 1, 3  | INPUTS   |     | -0.6 | mA   | 1, 2, 3    |
| VOL    | Output LOW Voltage          | VCC=4.5V, VIL=0.8V, IOL=20mA, VINH=5.5V   | 1, 3  | OUTPUTS  |     | 0.5  | V    | 1, 2, 3    |
| VOH    | Output HIGH Voltage         | VCC=4.5V, VIH=2.0V, IOH=-1.0mA, VINH=5.5V | 1, 3  | OUTPUTS  | 2.5 |      | V    | 1, 2, 3    |
| IOS    | Short-Circuit Current       | VCC=5.5V, VINH=5.5V, VOUT=0.0V            | 1, 3  | OUTPUTS  | -60 | -150 | mA   | 1, 2, 3    |
| VCD    | Input Clamp Diode Voltage   | VCC=4.5V, IM=-18mA, VINH=5.5V             | 1, 3  | INPUTS   |     | -1.2 | V    | 1, 2, 3    |
| ICCH   | Supply Current              | VCC=5.5V, VINH=5.5V                       | 1, 3  | VCC      |     | 8.3  | mA   | 1, 2, 3    |
| ICCL   | Supply Current              | VCC=5.5V, VINL=0.0V                       | 1, 3  | VCC      |     | 12.9 | mA   | 1, 2, 3    |
| ICEX   | Output HIGH Leakage Current | VCC=5.5V, VINL=0.0V, VINH=5.5V, VM=5.5V   | 1, 3  | OUTPUTS  |     | 250  | uA   | 1, 2, 3    |

### AC PARAMETER

(The following conditions apply to all the following parameters, unless otherwise specified.)  
 AC: CL=50pf, RL=500 OHMS TR=2.5ns, TF=2.5ns SEE AC FIGS

|      |                   |  |      |             |     |     |    |        |
|------|-------------------|--|------|-------------|-----|-----|----|--------|
| tpLH | Propagation Delay | VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C | 2, 4 | An/Bn to On | 3.0 | 5.6 | ns | 9      |
|      |                   |  | 2, 4 | An/Bn to On | 2.5 | 7.5 | ns | 10, 11 |
| tpHL | Propagation Delay | VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C | 2, 4 | An/Bn to On | 2.5 | 5.3 | ns | 9      |
|      |                   |  | 2, 4 | An/Bn to On | 2.0 | 7.5 | ns | 10, 11 |

Note 1: Screen tested 100% on each device at -55C, +25C & +125C temperature, subgroups A1, 2, 3, 7 & 8.

Note 2: Screen tested 100% on each device at +25C temperature only, subgroup A9.

Note 3: Sample tested (Method 5005, Table 1) on each MFG. lot at +25C, +125C & -55C temperature, subgroups A1, 2, 3, 7 & 8.

Note 4: Sample tested (Method 5005, Table 1) on each MFG. lot at +25C subgroup A9, and at +125C & -55C temperature, subgroups 10 & 11.

# National Semiconductor was acquired by Texas Instruments.

[http://www.ti.com/corp/docs/investor\\_relations/pr\\_09\\_23\\_2011\\_national\\_semiconductor.html](http://www.ti.com/corp/docs/investor_relations/pr_09_23_2011_national_semiconductor.html)

This file is the datasheet for the following electronic components:

54F08LMQB - <http://www.ti.com/product/54f08lmbq?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/34001SCA - <http://www.ti.com/product/jm38510/34001sca?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

54F08DMQB - <http://www.ti.com/product/54f08dmqb?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/34001BDA - <http://www.ti.com/product/jm38510/34001bda?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/34001BCA - <http://www.ti.com/product/jm38510/34001bca?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/34001B2A - <http://www.ti.com/product/jm38510/34001b2a?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/34001SDA - <http://www.ti.com/product/jm38510/34001sda?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

54F08FMQB - <http://www.ti.com/product/54f08fmqb?HQS=TI-null-null-dscatalog-df-pf-null-wwe>



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.